

**Iowa Department of Natural Resources  
Title V Operating Permit**

**Name of Permitted Facility: Polaris Industries, Inc – Spirit Lake**  
**Facility Location: 1900 Highway 71, Spirit Lake, Iowa 51360**  
**Air Quality Operating Permit Number: 00-TV-023R4-M002**  
**Expiration Date: February 1, 2027**  
**Permit Renewal Application Deadline: August 1, 2026**

**EIQ Number: 92-6845**  
**Facility File Number: 30-01-012**

---

**Responsible Official**

**Name: Keith Otterstatter**  
**Title: Plant Director**  
**Mailing Address: 1900 Highway 71, Spirit Lake, IA 51360**  
**Phone #: 712-336-8099**  
**keith.otterstatter@polaris.com**

**Permit Contact Person for the Facility**

**Name: Jacob Larson**  
**Title: Environmental Specialist**  
**Mailing Address: 1900 Highway 71, Spirit Lake, IA 51360**  
**Phone #: (712) 336-6721**  
**jacob.larson2@polaris.com**

---

This permit is issued in accordance with 567 Iowa Administrative Code Chapter 24, and is issued subject to the terms and conditions contained in this permit.

**For the Director of the Department of Natural Resources**

*Marnie Stein*

9/12/2024

---

Marnie Stein, Supervisor of Air Operating Permits Section

Date

# Table of Contents

<b>I. Facility Description and Equipment List.....</b>	<b>4</b>
<b>II. Plant - Wide Conditions .....</b>	<b>6</b>
<b>III. Emission Point Specific Conditions.....</b>	<b>9</b>
<b>IV. General Conditions .....</b>	<b>88</b>
G1.Duty to Comply	
G2.Permit Expiration	
G3.Certification Requirement for Title V Related Documents	
G4.Annual Compliance Certification	
G5.Semi-Annual Monitoring Report	
G6.Annual Fee	
G7.Inspection of Premises, Records, Equipment, Methods and Discharges	
G8.Duty to Provide Information	
G9.General Maintenance and Repair Duties	
G10. Recordkeeping Requirements for Compliance Monitoring	
G11. Evidence used in establishing that a violation has or is occurring.	
G12. Prevention of Accidental Release: Risk Management Plan Notification and Compliance Certification	
G13. Hazardous Release	
G14. Excess Emissions and Excess Emissions Reporting Requirements	
G15. Permit Deviation Reporting Requirements	
G16. Notification Requirements for Sources That Become Subject to NSPS and NESHAP Regulations	
G17. Requirements for Making Changes to Emission Sources That Do Not Require Title V Permit Modification	
G18. Duty to Modify a Title V Permit	
G19. Duty to Obtain Construction Permits	
G20. Asbestos	
G21. Open Burning	
G22. Acid Rain (Title IV) Emissions Allowances	
G23. Stratospheric Ozone and Climate Protection (Title VI) Requirements	
G24. Permit Reopenings	
G25. Permit Shield	
G26. Severability	
G27. Property Rights	
G28. Transferability	
G29. Disclaimer	
G30. Notification and Reporting Requirements for Stack Tests or Monitor Certification	
G31. Prevention of Air Pollution Emergency Episodes	
G32. Contacts List	
<b>V. Appendix A: .....</b>	<b>102</b>
<b>VI. Appendix B: Executive Order 10 (EO10) Rules Crosswalk.....</b>	<b>103</b>

## Abbreviations

acfm	actual cubic feet per minute
CFR	Code of Federal Regulation
CE	control equipment
CEM	continuous emission monitor
°F	degrees Fahrenheit
EIQ	emissions inventory questionnaire
EP	emission point
EU	emission unit
gr./dscf	grains per dry standard cubic foot
gr./100 cf	grains per one hundred cubic feet
IAC	Iowa Administrative Code
IDNR	Iowa Department of Natural Resources
MVAC	motor vehicle air conditioner
NAICS	North American Industry Classification System
NSPS	new source performance standard
NESHAP	National Emission Standards for Hazardous Air Pollutants
ppmv	parts per million by volume
lb./hr	pounds per hour
lb./MMBtu	pounds per million British thermal units
SCC	Source Classification Codes
scfm	standard cubic feet per minute
SIC	Standard Industrial Classification
TPY	tons per year
USEPA	United States Environmental Protection Agency

### Pollutants

PM	particulate matter
PM <sub>10</sub>	particulate matter ten microns or less in diameter
SO <sub>2</sub>	sulfur dioxide
NO <sub>x</sub>	nitrogen oxides
VOC	volatile organic compound
CO	carbon monoxide
HAP	hazardous air pollutant

# I. Facility Description and Equipment List

Facility Name: Polaris Industries, Inc – Spirit Lake

Permit Number: 00-TV-023R4-M002

Facility Description: Transportation Equipment Manufacturer (SIC 3799)

## Equipment List

Emission Point Number	Emission Unit Number	Emission Unit Description	DNR Construction Permit Number
EP-6	EU-6	Spray Paint Booth #0	09-A-162-S2
EP-18	EU-18	Electrocoat Dip Tank	96-A-184-S3
EP-19	EU-19	Electrocoat Cure Oven	96-A-185-S2
EP-20	EU-20.1	Powdercoat Paint Booth #1	96-A-186-S6
	EU-20.2	Powdercoat Paint Booth #2	
	EU-20.3	Powdercoat Cure Oven	
EP-23	EU-23	Metal Paint Oven Cooling Tunnel	96-A-187-S2
EP Indoors	EU-29	Welding Cell	17-A-311-S1
EP-AMU	EU-AMU	Air Make-up Units	NA
EP-45	EU-45	Unpaved Roads (Fugitive)	NA
EP-47	EU-47	Paint Burn-Off Oven #2	00-A-960-S2
EP-58	EU-58	Powdercoat Paint Booth #3	NA
EP-39A	EU-39A	Metallic Paints Part Washer Heaters	NA
EP-62	EU-46	Sanding Booth	13-A-285-S1
EP-63	EU-63	Primer Booth	13-A-286-S3
EP-64	EU-64	Base Coat #1 Booth	13-A-287-S3
EP-65	EU-65	Base Coat #2 Booth	13-A-288-S3
EP-66	EU-66	Clear Coat #1 Booth	13-A-289-S3
EP-67	EU-67	Clear Coat #2 Booth	13-A-290-S3
EP-68	EU-68	Clear Coat #3 Booth	13-A-291-S3
EP-71	EU-71	Dry-off Oven	13-A-292-S1
EP-72A	EU-72	Cure Oven	13-A-293-S2
EP-72B			15-A-279-S1
EP-73	EU-73	Parts Washer Heater	13-A-294-S1
EP-74	EU-74	Spray Booth Boiler	13-A-295-S2
EP-74B	EU-74B	Spray Booth Boiler (Backup)	16-A-275
EP-75	EU-75	Flash Enclosure Heater	13-A-296-S1
EP-76	EU-76	Automated Abrasive Blasting Unit	19-A-621
EP-77	EU-77	Emergency Natural Gas Backup Generator	NA
EP-78	EP-78	Humidifier; 1.2 MMBtu/hr	NA
EP-79	EP-79	Humidifier; 1.2 MMBtu/hr	NA
EP-80	EU-80	Parts Washer (Annex)	19-A-622-S1
EP-82	EU-82	Emergency Diesel Backup Generator	NA

### **Insignificant Activities Equipment List**

<b>Insignificant Emission Unit Number</b>	<b>Insignificant Emission Unit Description</b>
EU-40	Diesel Fuel Storage Tank (560 Gallons)
EU-41	Gasoline Storage Tank (560 gallons)
EU-81	Graphics Cleaning Booth <sup>(1)</sup>

<sup>(1)</sup>EU-81 qualifies for Small Unit Exemption under 567 IAC 22.1(2)"w". Records shall be kept in accordance with 567 IAC 22.1(2)"w"(3).

## II. Plant-Wide Conditions

Facility Name: Polaris Industries, Inc – Spirit Lake  
Permit Number: 00-TV-023R4-M002

Permit conditions are established in accord with 567 Iowa Administrative Code rule 24.108. When 567 IAC as amended May 15, 2024, and cited in this permit becomes State Implementation Plan (SIP) approved, it will supersede 567 IAC as amended February 8, 2023. Prior to May 15, 2024, all Title V rule citations in this Title V permit were found and cited in 567 IAC Chapter 22. During the period from May 15, 2024, to the date that 567 IAC as amended May 15, 2024, is approved into the SIP, both 567 IAC as amended May 15, 2024 and 567 IAC as amended February 8, 2023 form the legal basis for the applicable requirements included in this permit. A crosswalk showing the citation changes is attached to this permit in Appendix B.

---

### Permit Duration

The term of this permit is: 5 years from permit issuance.  
Commencing on: February 2, 2022  
Ending on: February 1, 2027

Amendments, modifications and reopenings of the permit shall be obtained in accordance with 567 Iowa Administrative Code rules 24.110 - 24.114. Permits may be suspended, terminated, or revoked as specified in 567 Iowa Administrative Code Rules 24.115.

---

### Emission Limits

*Unless specified otherwise in the Source Specific Conditions, the following limitations and supporting regulations apply to all emission points at this plant:*

Opacity (visible emissions): 40% opacity  
Authority for Requirement: 567 IAC 23.3(2)"d"

Sulfur Dioxide (SO<sub>2</sub>): 500 parts per million by volume  
Authority for Requirement: 567 IAC 23.3(3)"e"

### Particulate Matter:

No person shall cause or allow the emission of particulate matter from any source in excess of the emission standards specified in this chapter, except as provided in 567 – Chapter 24. For sources constructed, modified or reconstructed on or after July 21, 1999, the emission of particulate matter from any process shall not exceed an emission standard of 0.1 grain per dry standard cubic foot of exhaust gas, except as provided in 567 – 21.2(455B), 23.1(455B), 23.4(455B) and 567 – Chapter 24. For sources constructed, modified or reconstructed prior to July 21, 1999, the emission of particulate matter from any process shall not exceed the amount determined from Table I, or amount specified in a permit if based on an emission standard of 0.1 grain per standard cubic foot of exhaust gas or established from standards provided in 23.1(455B) and 23.4(455B).

Authority for Requirement: 567 IAC 23.3(2)"a"

**Fugitive Dust:** Attainment and Unclassified Areas - No person shall allow, cause or permit any materials to be handled, transported or stored; or a building, its appurtenances or a construction haul road to be used, constructed, altered repaired or demolished, with the exception of farming operations or dust generated by ordinary travel on unpaved public roads, without taking reasonable precautions to prevent particulate matter in quantities sufficient to create a nuisance, as defined in Iowa Code section 657.1, from becoming airborne. All persons, with the above exceptions, shall take reasonable precautions to prevent the discharge of visible emissions of fugitive dusts beyond the lot line of the property on which the emissions originate. The highway authority shall be responsible for taking corrective action in those cases where said authority has received complaints of or has actual knowledge of dust conditions which require abatement pursuant to this subrule. Reasonable precautions may include, but not limited to, the following procedures.

1. Use, where practical, of water or chemicals for control of dusts in the demolition of existing buildings or structures, construction operations, the grading of roads or the clearing of land.
2. Application of suitable materials, such as but not limited to asphalt, oil, water or chemicals on unpaved roads, material stockpiles, race tracks and other surfaces which can give rise to airborne dusts.
3. Installation and use of containment or control equipment, to enclose or otherwise limit the emissions resulting from the handling and transfer of dusty materials, such as but not limited to grain, fertilizers or limestone.
4. Covering at all times when in motion, open-bodied vehicles transporting materials likely to give rise to airborne dusts.
5. Prompt removal of earth or other material from paved streets or to which earth or other material has been transported by trucking or earth-moving equipment, erosion by water or other means.

Authority for Requirement: 567 IAC 23.3(2)"c"

Pollutant: VOC

Emission Limit: 233.0 tpy from the surface coating operations listed in the following Table

Authority for Requirement: Construction Permits in the Following Table

Table 1 - Surface Coating Operations with a 233.0 tpy VOC Bubble Limit

EP	EU	EU Description	DNR Construction Permits
EP-6	EU-6	Spray Paint Booth #0	09-A-162-S2
EP-18	EU-18	Electrocoat Dip Tank	96-A-184-S3
EP-20	EU-20.1	Powdercoat Paint Booth #1	96-A-186-S6
	EU-20.2	Powdercoat Paint Booth #2	
EP-23	EU-23	Metal Paint Oven Cooling Tunnel	96-A-187-S2
EP-58	EU-58	Powdercoat Paint Booth #3	NA
EP-63	EU-63	Primer Booth	13-A-286-S3
EP-64	EU-64	Base Coat #1 Booth	13-A-287-S3
EP-65	EU-65	Base Coat #2 Booth	13-A-288-S3
EP-66	EU-66	Clear Coat #1 Booth	13-A-289-S3
EP-67	EU-67	Clear Coat #2 Booth	13-A-290-S3
EP-68	EU-68	Clear Coat #3 Booth	13-A-291-S3

#### **40 CFR 63 Subpart A Requirements**

This facility's coating operation is subject to 40 CFR Part 63 Subpart A – General Provisions. See Appendix for the Internet link to the complete text of the Standard.

Authority for Requirements: 40 CFR 63 Subpart A  
567 IAC 23.1(4)

#### **40 CFR 63 Subpart MMMM Requirements**

This facility's coating operation is subject to the National Emission Standard for Hazardous Air Pollutants for Surface Coating of Miscellaneous Metal Parts and Products – 40 CFR 63 Subpart MMMM. See Table 1 for affected units. See Appendix for the Internet link to the complete text of the Standard.

Authority for Requirements: 40 CFR 63 Subpart MMMM  
567 IAC 23.1(4) "cm"

#### **40 CFR 63 Subpart PPPP Requirements**

This facility's coating operation is subject to the National Emission Standard for Hazardous Air Pollutants for Surface Coating of Plastic Parts and Products MACT – 40 CFR 63 Subpart PPPP. See Table 1 for affected units. See Appendix for the Internet link to the complete text of the Standard.

Authority for Requirements: 40 CFR 63 Subpart PPPP  
567 IAC 23.1(4) "cp"

#### **40 CFR 63 Subpart DDDDD Requirements**

This facility is subject to the following federal regulation: National Emission Standards for Hazardous Air Pollutants for Major Sources: Industrial, Commercial, and Institutional Boilers and Process Heaters [40 CFR Part 63 Subpart DDDDD]. The affected units are EP-74, EP-74B, EP-78, and EP-79. See Appendix for the Internet link to the complete text of the Standard.

Authority for Requirements: 40 CFR 63 Subpart DDDDD

#### **40 CFR 63 Subpart ZZZZ Requirements**

The facility's emergency backup generator, EP-77 is subject to the National Emissions Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines. See Appendix for the Internet link to the complete text of the Standard.

Authority for Requirements: 40 CFR 63 Subpart ZZZZ  
567 IAC 23.1(4)"cz"



### III. Emission Point-Specific Conditions

Facility Name: Polaris Industries, Inc.  
Permit Number: 00-TV-023R4-M002

---

#### **Emission Point ID Number: EP-6**

##### Associated Equipment

Associated Emission Unit ID Numbers: EU-6  
Emissions Control Equipment ID Number: CE-6  
Emissions Control Equipment Description: Dry Filters

---

Emission Unit vented through this Emission Point: EU-6  
Emission Unit Description: Spray Paint Booth #0  
Raw Material/Fuel: Paint  
Rated Capacity: 4 HVLP Gun @ 9.0 gal/hr

#### **Applicable Requirements**

##### **Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity  
Emission Limit(s): 40% <sup>(1)</sup>  
Authority for Requirement: 567 IAC 23.3(2) "d"  
DNR Construction Permit 09-A-162-S2

<sup>(1)</sup>An exceedance of the indicator opacity of "10%" will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM<sub>10</sub>)  
Emission Limit(s): 0.97 lb/hr  
Authority for Requirement: DNR Construction Permit 09-A-162-S2

Pollutant: Particulate (PM)  
Emission Limit(s): 0.97 lb/hr; 0.01 gr/dscf  
Authority for Requirement: 567 IAC 23.4(13)  
DNR Construction Permit 09-A-162-S2

Pollutant: VOC  
Emission Limit(s): 233.0 tons/yr<sup>(2)</sup>  
Authority for Requirement: DNR Construction Permit 09-A-162-S2  
<sup>(2)</sup>Total VOC emissions from all non-combustion sources at this facility shall not exceed 233.0 tons per rolling 12-month period. All VOC-containing non-fuel materials used at the facility shall be included in the emissions calculations.

## **Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

### **National Emission Standards for Hazardous Air Pollutants (NESHAP) Applicability**

This unit is subject to the National Emission Standard for Hazardous Air Pollutants (NESHAP) for the Surface Coating of Miscellaneous Metal Parts and Products (40 CFR 63 Subpart Mmmm; 567 IAC 23.1(4)"cm") and the NESHAP for the Surface Coating of Plastic Parts and Products (40 CFR 63 Subpart Pppp; 567 IAC 23.1(4)"cp").

Authority for Requirement: 40 CFR 63 Subpart Mmmm & Pppp  
567 IAC 23.1(4) "cm" & "cp"  
DNR Construction Permit 09-A-162-S2

### **Operating Limits**

Operating limits for this emission unit shall be:

- A. All spray materials shall meet the emission requirements per §63.3890 for the coating of miscellaneous metal parts and §63.4490 for the coating of plastic parts which includes, but is not limited to, limiting the VHAP emissions from finishing operations, contact adhesives and strippable spray booth coatings.
- B. The owner or operator shall comply with the work practice standards outlined in §63.3893 for the coating of miscellaneous metal parts and §63.4493 for the coating of plastic parts.
- C. The owner or operator shall comply with the compliance procedures and monitoring requirements of §63.3900 for the coating of metal parts.
- D. The owner or operator shall comply with the compliance procedures and monitoring requirements of §63.4500 for the coating of plastic parts.
- E. Total VOC emissions from all non-combustion sources at this facility shall not exceed 233.0 tons per daily rolling 365-day period. All VOC-containing non-fuel materials used at the facility shall be included in the emissions calculations.

### **Reporting and Recordkeeping**

Unless specified by a federal regulation, all records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the Department. Records shall be legible and maintained in an orderly manner. These records shall show the following:

- A. The owner or operator shall perform the Recordkeeping requirements of §63.3930 and reporting requirements of §63.3920 for the coating of miscellaneous metal parts.
- B. The owner or operator shall perform the Recordkeeping requirements of §63.4530 and reporting requirements of §63.4520 for the coating of plastic parts.

- C. The facility shall maintain a log of all materials used at the facility (Plant Number 30-01-012). The log shall contain the materials respective VOC, Single HAP and Total HAP content, (in lb/gal).
- D. The permittee (or owner or operator) shall maintain the following daily records:
- a. The identification of each VOC-containing non-fuel material used at the facility.
  - b. The amount, in gallons, of each VOC-containing non-fuel material used at the facility. For the purposes of calculating emissions, all VOC may be considered emitted on the day the materials are delivered to the facility or to the production line.
- E. The permittee shall maintain the following monthly records:
- a. The identification of each VOC-containing non-fuel material used at the facility.
  - b. The amount, in gallons, of each VOC-containing non-fuel material used at the facility. For the purposes of calculating emissions, all VOC may be considered emitted on the day the materials are delivered to the facility or to the production line.
  - c. The amount of VOC emissions from all non-combustion sources, in tons.
  - d. The 12-month rolling total of the amount of VOC emissions from all non-combustion sources, in tons.
- F. If the 12-month rolling total of the VOC emissions exceeds 186.4 tons, the permittee shall immediately begin keeping the following daily records:
- a. The amount of VOC emissions from all non-combustion sources, in tons.
  - b. The 365-day rolling total of the amount of VOC emissions from all non-combustion sources, in tons.
- Daily calculations for VOC emissions shall continue until the 365-day rolling total of the amount of VOC emissions from all non-combustion sources drops below 186.4 tons for the remainder of the current calendar month plus one additional calendar month. At that time, rolling daily calculation of VOC emissions will cease per Section C (shown above) of this permit. If the emissions once again exceed 186.4 tons, daily recordkeeping will be required per Section C (shown above) of this permit.
- G. The permittee may take credit for any waste VOC shipped off-site. The permittee shall record the amount of the waste shipped off-site each day, and analyze the VOC content of the waste once every calendar quarter. The sample analyzed shall be taken as a representative sample (as defined in 40 CFR §260.10) of the waste sent off-site for that quarter and shall be used as representative until the subsequent quarter's analysis is received. The credit (calculated from the most current analysis and the amount shipped off-site) may be subtracted from the VOC rolling totals as of the date the waste is shipped off-site.

Authority for Requirement: DNR Construction Permit 09-A-162-S2

**Emission Point Characteristics**

*The emission point shall conform to the specifications listed below.*

- Stack Height, (ft, from the ground): 13.5
- Stack Opening, (inches, dia.): 40" x 40"
- Exhaust Flow Rate (scfm): 9,900
- Exhaust Temperature (°F): 70°
- Discharge Style: Horizontal
- Authority for Requirement: DNR Construction Permit 09-A-162-S2

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that either the temperature or flowrate above are different than the values stated, the owner or operator shall submit a request to the Department within thirty (30) days of the discovery to determine if a permit amendment is required or submit a permit application requesting to amend the permit.

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

- Agency Approved Operation & Maintenance Plan Required?** Yes  No
- Facility Maintained Operation & Maintenance Plan Required?** Yes  No
- Compliance Assurance Monitoring (CAM) Plan Required?** Yes  No

**Paint Booth Agency Operation & Maintenance Plan**

**Weekly**

- Inspect the paint booth system for conditions that reduce the operating efficiency of the collection system. This will include a visual inspection of the condition of the filter material.
- Maintain a written record of the observation and any action resulting from the inspection.

**Recordkeeping and Reporting**

- Maintenance and inspection records will be kept for five years and available upon request.

**Quality Control**

- The filter equipment will be operated and maintained according to the manufacturer's recommendations.

Authority for Requirement: 567 IAC 22.108(3)

## **Emission Point ID Number: EP-18**

### Associated Equipment

Associated Emission Unit ID Numbers: EU-18

---

Emission Unit vented through this Emission Point: EU-18

Emission Unit Description: Electrocoat Dip Tank

Raw Material/Fuel: Paint

Rated Capacity: 7.50 gal/hr

### **Applicable Requirements**

#### **Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity

Emission Limit(s): 40% <sup>(1)</sup>

Authority for Requirement: DNR Construction Permit 96-A-184-S3  
567 IAC 23.3(2) "d"

<sup>(1)</sup> An exceedance of the indicator opacity of 10% will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.01 gr/dscf

Authority for Requirement: DNR Construction Permit 96-A-184-S3  
567 IAC 23.4(13)

Pollutant: VOC

Emission Limit(s): 233.0 tons/yr<sup>(2)</sup>

Authority for Requirement: DNR Construction Permit 96-A-184-S3

<sup>(2)</sup> Total VOC emissions from all non-combustion sources at this facility shall not exceed 233.0 tons per rolling 12-month period. All VOC-containing non-fuel materials used at the facility shall be included in the emissions calculations.

## **Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

### **NESHAP Applicability**

This unit is subject to the National Emission Standard for Hazardous Air Pollutants (NESHAP) for the Surface Coating of Miscellaneous Metal Parts and Products, 40 CFR 63 Subpart M MMM and the NESHAP for the Surface Coating of Plastic Parts and Products, 40 CFR 63 Subpart P PPP.

Authority for Requirement: 40 CFR 63 Subparts M MMM & P PPP  
567 IAC 23.1(4) "cm" & "cp"  
DNR Construction Permit 96-A-184-S3

### **Operating Limits**

Operating limits for this emission unit shall be:

- A. Total VOC emissions from all non-combustion sources at this facility shall not exceed 233.0 tons per daily rolling 365-day period. All VOC-containing materials used at the facility shall be included in the emissions calculations.

### **Reporting and Recordkeeping**

All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner. These records shall show the following:

- A. The permittee (or owner or operator) shall maintain the following daily records:
  - i. The identification of each VOC-containing non-fuel material used at the facility.
  - ii. The amount, in gallons, of each VOC-containing non-fuel material used at the facility. For the purposes of calculating emissions, all VOC may be considered emitted on the day the materials are delivered to the facility or to the production line.
- B. The permittee shall maintain the following monthly records:
  - i. The identification of each VOC-containing non-fuel material used at the facility.
  - ii. The amount, in gallons, of each VOC-containing non-fuel material used at the facility. For the purposes of calculating emissions, all VOC may be considered emitted on the day the materials are delivered to the facility or to the production line.
  - iii. The amount of VOC emissions from all non-combustion sources, in tons.
  - iv. The 12-month rolling total of the amount of VOC emissions from all non-combustion sources, in tons.
- C. If the 12-month rolling total of the VOC emissions exceeds 186.4 tons, the permittee shall immediately begin keeping the following daily records:
  - i. The amount of VOC emissions from all non-combustion sources, in tons.
  - ii. The 365-day rolling total of the amount of VOC emissions from all non-combustion sources, in tons.

Daily calculations for VOC emissions shall continue until the 365-day rolling total of the amount of VOC emissions from all non-combustion sources drops below 186.4 tons for the remainder of the current calendar month plus one additional calendar month. At that time, rolling daily calculation of VOC emissions will cease per Section C of this permit. If the emissions once again exceed 186.4 tons, daily recordkeeping will be required per Section C of this permit.

- D. The permittee may take credit for any waste VOC shipped off-site. The permittee shall record the amount of the waste shipped off-site each day, and analyze the VOC content of the waste once every calendar quarter. The sample analyzed shall be taken as a representative sample (as defined in 40 CFR §260.10) of the waste sent off-site for that quarter and shall be used as representative until the subsequent quarter's analysis is received. The credit (calculated from the most current analysis and the amount shipped off-site) may be subtracted from the VOC rolling totals as of the date the waste is shipped off-site.

Authority for Requirement: DNR Construction Permit 96-A-184-S3

**Emission Point Characteristics**

*The emission point shall conform to the specifications listed below.*

Stack Height, (ft, from the ground): 35

Stack Opening, (inches, dia.): 18

Exhaust Flow Rate (scfm): 3,750

Exhaust Temperature (°F): Ambient (70°F)

Discharge Style: Vertical Unobstructed

Authority for Requirement: DNR Construction Permit 96-A-184-S3

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that either the temperature or flowrate above are different than the values stated, the owner or operator shall submit a request to the Department within thirty (30) days of the discovery to determine if a permit amendment is required or submit a permit application requesting to amend the permit.

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

**Agency Approved Operation & Maintenance Plan Required?** Yes  No

**Facility Maintained Operation & Maintenance Plan Required?** Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?** Yes  No

Authority for Requirement: 567 IAC 22.108(3)

**Emission Point ID Number: EP-19**

Associated Equipment

Associated Emission Unit ID Numbers: EU-19

---

Emission Unit vented through this Emission Point: EU-19

Emission Unit Description: Electrocoat Cure Oven

Raw Material/Fuel: Natural Gas

Rated Capacity: 4.0 MMBtu/hr

**Applicable Requirements**

**Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity

Emission Limit(s): 40% <sup>(1)</sup>

Authority for Requirement: 567 IAC 23.3(2) "d"  
DNR Construction Permit 96-A-185-S2

<sup>(1)</sup> An exceedance of the indicator opacity of 10% will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.1 gr/dscf

Authority for Requirement: 567 IAC 23.3(2) "a"  
DNR Construction Permit 96-A-185-S2

Pollutant: Sulfur Dioxide (SO<sub>2</sub>)

Emission Limit(s): 500 ppmv

Authority for Requirement: 567 IAC 23.3(3) "e"  
DNR Construction Permit 96-A-185-S2



## **Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

### **NESHAP Applicability**

Drying and curing operations are part of the system that is defined as a coating operation under the National Emission Standards for Hazardous Air Pollutants. Therefore, this unit is subject to the requirements of the NESHAP for the Surface Coating of Miscellaneous Metal Parts and Products, 40 CFR 63 Subpart Mmmm and the NESHAP for the Surface Coating of Plastic Parts and Products, 40 CFR 63 Subpart Pppp.

Authority for Requirement: 40 CFR 63 Subparts Mmmm & Pppp  
567 IAC 23.1(4) "cm" & "cp"  
DNR Construction Permit 96-A-185-S2

### **Operating Limits**

Operating limits for this emission unit shall be:

- A. This unit shall use natural gas only as fuel.

### **Reporting and Recordkeeping**

All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner. These records shall show the following:

- A. The owner/operator shall maintain all records required under the NESHAP standards that apply to this unit.

Authority for Requirement: DNR Construction Permit 96-A-185-S2

### **Emission Point Characteristics**

*The emission point shall conform to the specifications listed below.*

Stack Height, (ft, from the ground): 32

Stack Opening, (inches, dia.): 22

Exhaust Flow Rate (scfm): 1,260

Exhaust Temperature (°F): 450

Discharge Style: Vertical Unobstructed

Authority for Requirement: DNR Construction Permit 96-A-185-S2

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that either the temperature or flowrate above are different than the values stated, the owner or operator shall submit a request to the Department within thirty (30) days of the discovery to determine if a permit amendment is required or submit a permit application requesting to amend the permit.

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

**Agency Approved Operation & Maintenance Plan Required?**      Yes  No

**Facility Maintained Operation & Maintenance Plan Required?**      Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?**      Yes  No

Authority for Requirement: 567 IAC 22.108(3)

## Emission Point ID Number: EP-20

### Associated Equipment

Associated Emission Unit ID Numbers: EU-20.1; EU-20.2; EU-20.3

Emissions Control Equipment ID Number: CE-20.1 and CE-20.2

Emissions Control Equipment Description: Wagner Filtration System

---

Emission Unit Descriptions, Raw Material/Fuel and Rated Capacity are listed in the following table:

---

EP	EU	Emission Unit Description	Raw Material	Rated Capacity	CE ID &Description
EP-20	EU-20.1	Powdercoat Paint Booth #1	Paint	31 lb/hr (Powder)	CE-20.1, CE-20.2 in series Cartridge Filters, Mat Filter
	EU-20.2	Powdercoat Paint Booth #2	Paint		
	EU-20.3	Powdercoat Cure Oven	Natural Gas	1.42 MMBtu/hr	None

### Applicable Requirements

#### Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity

Emission Limit(s): 40% <sup>(1)</sup>

Authority for Requirement: 567 IAC 23.3(2) "d"

DNR Construction Permit 96-A-186-S6

<sup>(1)</sup>An exceedance of the indicator opacity of 10% will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.01 gr/dscf

Authority for Requirement: 567 IAC 23.4(13)

DNR Construction Permit 96-A-186-S6

Pollutant: Volatile Organic Compounds (VOC)

Emission Limit(s): 233.0 ton/yr <sup>(2)</sup>

Authority for Requirement: DNR Construction Permit 96-A-186-S6

<sup>(2)</sup> Total VOC emissions from all non-combustion sources at this facility shall not exceed 233.0 tons per rolling 12-month period. All VOC-containing non-fuel materials used at the facility shall be included in the emissions calculations.

## **Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

### **NESHAP Applicability**

This unit is subject to NESHAP 40 CFR 63 Subpart M MMM – National Emission Standards for Hazardous Air Pollutants for Surface Coating of Miscellaneous Metal Parts and Products and NESHAP 40 CFR 63 Subpart P PPP – National Emission Standards for Hazardous Air Pollutants for Surface Coating of Plastic Parts and Products.

Authority for Requirement: 40 CFR 63 Subparts M MMM & P PPP  
567 IAC 23.1(4) "cm" & "cp"  
DNR Construction Permit 96-A-186-S6

### **Operating Limits**

Operating limits for this emission unit shall be:

- A. Total VOC emissions from all non-combustion sources at this facility shall not exceed 233.0 tons per daily rolling 365-day period. All VOC emissions at the facility shall be included in the emissions calculations.

### **Reporting and Recordkeeping**

All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner. These records shall show the following:

- A. The permittee (or owner or operator) shall maintain the following daily records:
  - i. The identification of each powdercoat material used at the facility.
  - ii. The amount, in pounds, of each powdercoat material used at the facility. For the purposes of calculating emissions, all material may be considered used on the day the materials are delivered to the facility or to the production line.
- B. The permittee shall maintain the following monthly records:
  - i. The identification of each powdercoat material used at the facility.
  - ii. The amount, in pounds, of each powdercoat material used at the facility. For the purposes of calculating emissions, all material may be considered used on the day the materials are delivered to the facility or to the production line.
  - iii. The amount of VOC emissions from all non-combustion sources, in tons. When calculating the VOC emissions from the powdercoating operations, it shall be assumed that 2.5% by weight of the powdercoat material is emitted as VOCs.
  - iv. The 12-month rolling total of the amount of VOC emissions from all non-combustion sources, in tons.

- C. If the 12-month rolling total of the VOC emissions exceeds 186.4 tons, the permittee shall immediately begin keeping the following daily records:
- i. The amount of VOC emissions from all non-combustion sources, in tons. When calculating the VOC emissions from the powdercoating operations, it shall be assumed that 2.5% by weight of the powdercoat material is emitted as VOCs.
  - ii. The 365-day rolling total of the amount of VOC emissions from all non-combustion sources, in tons.

Daily calculations for VOC emissions shall continue until the 365-day rolling total of the amount of VOC emissions from all non-combustion sources drops below 186.4 tons for the remainder of the current calendar month plus one additional calendar month. At that time, rolling daily calculation of VOC emissions will cease per Section C of this permit. If the emissions once again exceed 186.4 tons, daily recordkeeping will be required per Section C of this permit.

- D. The permittee may take credit for any waste VOC shipped off-site. The permittee shall record the amount of the waste shipped off-site each day, and analyze the VOC content of the waste once every calendar quarter. The sample analyzed shall be taken as a representative sample (as defined in 40 CFR §260.10) of the waste sent off-site for that quarter and shall be used as representative until the subsequent quarter's analysis is received. The credit (calculated from the most current analysis and the amount shipped off-site) may be subtracted from the VOC rolling totals as of the date the waste is shipped off-site.

Authority for Requirement: DNR Construction Permit 96-A-186-S6

**Emission Point Characteristics**

*The emission point shall conform to the specifications listed below.*

Stack Height, (ft, from the ground): 33

Stack Opening, (inches, dia.): 16

Exhaust Flow Rate (scfm): 6,000

Exhaust Temperature (°F): 400 °F

Discharge Style: Vertical Unobstructed

Authority for Requirement: DNR Construction Permit 96-A-186-S6

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that either the temperature or flowrate above are different than the values stated, the owner or operator shall submit a request to the Department within thirty (30) days of the discovery to determine if a permit amendment is required or submit a permit application requesting to amend the permit.

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

- Agency Approved Operation & Maintenance Plan Required?**      Yes  No
- Facility Maintained Operation & Maintenance Plan Required?**      Yes  No
- Compliance Assurance Monitoring (CAM) Plan Required?**      Yes  No

**Paint Booth Agency Operation & Maintenance Plan**

**Weekly**

- Inspect the paint booth system for conditions that reduce the operating efficiency of the collection system. This will include a visual inspection of the condition of the filter material.
- Maintain a written record of the observation and any action resulting from the inspection.

**Recordkeeping and Reporting**

- Maintenance and inspection records will be kept for five years and available upon request.

**Quality Control**

- The filter equipment will be operated and maintained according to the manufacturer’s recommendations.

Authority for Requirement: 567 IAC 22.108(3)

**Emission Point ID Number: EP-23**

Associated Equipment

Associated Emission Unit ID Numbers: EU-23

---

Emission Unit vented through this Emission Point: EU-23  
Emission Unit Description: Metal Paint Oven Cooling Tunnel  
Raw Material/Fuel: Paint  
Rated Capacity: 10.0 gal/hr

**Applicable Requirements**

**Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity

Emission Limit(s): 40% <sup>(1)</sup>

Authority for Requirement: 567 IAC 23.3(2) "d"  
DNR Construction Permit 96-A-187-S2

<sup>(1)</sup>An exceedance of the indicator opacity of "no visible emissions" will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.1 gr/dscf

Authority for Requirement: 567 IAC 23.3(2) "a"  
DNR Construction Permit 96-A-187-S2

**Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

**NESHAP Applicability**

Drying and curing operations are part of the system that is defined as a coating operation under the National Emission Standards for Hazardous Air Pollutants. Therefore, this unit is subject to the requirements of the NESHAP for the Surface Coating of Miscellaneous Metal Parts and Products (40 CFR 63 Subpart M MMM) and the NESHAP for the Surface Coating of Plastic Parts and Products, (40 CFR 63 Subpart P PPP).

Authority for Requirement: 40 CFR 63 Subparts MMM & PPP  
567 IAC 23.1(4) "cm" & "cp"  
DNR Construction Permit 96-A-187-S2

**Reporting and Recordkeeping**

All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner. These records shall show the following:

- A. The owner/operator shall maintain all records required under the NESHAP standards that apply to this unit.

Authority for Requirement: DNR Construction Permit 96-A-187-S2

**Emission Point Characteristics**

*The emission point shall conform to the specifications listed below.*

Stack Height, (ft, from the ground): 37

Stack Opening, (inches, dia.): 40

Exhaust Flow Rate (scfm): 19,875

Exhaust Temperature (°F): 100

Discharge Style: Vertical Unobstructed

Authority for Requirement: DNR Construction Permit 96-A-187-S2

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that either the temperature or flowrate above are different than the values stated, the owner or operator shall submit a request to the Department within thirty (30) days of the discovery to determine if a permit amendment is required or submit a permit application requesting to amend the permit.

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

**Agency Approved Operation & Maintenance Plan Required?** Yes  No

**Facility Maintained Operation & Maintenance Plan Required?** Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?** Yes  No

Authority for Requirement: 567 IAC 22.108(3)



## **Emission Point ID Number: EP Indoors**

### Associated Equipment

Associated Emission Unit ID Numbers: EU 29

Emissions Control Equipment ID Number: CE 29a – CE 29d

Emissions Control Equipment Description: 1 to 4 Cartridge Filters depending on rod type used

---

Emission Unit vented through this Emission Point: EU 29

Emission Unit Description: Welding Cells

Raw Material/Fuel and Capacity: 1551 pounds of steel welding rod per hour, 729.6 pounds aluminum welding rod per hour

### **Applicable Requirements**

#### **Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity

Emission Limit(s): 40%<sup>(1)</sup>

Authority for Requirement: 567 IAC 23.3(2)"d"

<sup>(1)</sup>An exceedance of the indicator opacity of No Visible Emissions will require the owner or operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the Department may require additional proof to demonstrate compliance (e.g., stack testing)

Pollutant: Particulate Matter (PM)

Emission Limit(s): 4.22 lb./hr, 0.1 gr./dscf

Authority for Requirement: 567 IAC 23.3(2)"a"

DNR Construction Permit 17-A-311-S1

Pollutant: PM<sub>10</sub>

Emission Limit(s): 4.22 lb./hr

Authority for Requirement: DNR Construction Permit 17-A-311-S1

#### **Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below. Unless specified by a federal regulation, all records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the Department. Records shall be legible and maintained in an orderly manner.*

#### **EP Indoors Only**

1. The owner or operator shall conduct an inspection of the emission units and the associated control equipment at a minimum of once per year and correct/repair any issues discovered during the inspection. The owner or operator shall maintain a log of all inspections and maintenance activities performed on the emission units and the associated control equipment. This log shall include, but is not necessarily limited to:

- a. The date and time any inspection and/or maintenance was performed on the emission unit and/or control equipment;
  - b. Any issues identified during the inspection and the date each issue was resolved; and,
  - c. Any issues addressed during the maintenance activities and the date each issue was resolved.
- Authority for Requirement: DNR Construction Permit 17-A-311-S1

**Emission Point Characteristics**

*The emission point shall conform to the specifications listed below.*

<b>Emission Point Number</b>	<b>Stack Height</b> (feet from ground)	<b>Stack Opening</b> (inches, dia.)	<b>Exhaust Flow Rate</b> (scfm)	<b>Exhaust Temp.</b> (°F)	<b>Discharge Style</b>
EP Indoors	Indoors	Indoors	4,000	70	Indoors

Authority for Requirement: DNR Construction Permit 17-A-311-S1

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point characteristics above are different than the values stated, the owner or operator shall submit a request either by electronic mail or written correspondence to the Department within 30 days of the discovery to determine if a permit amendment is required, or submit a permit application requesting to amend the permit.

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

**Agency Approved Operation & Maintenance Plan Required?**      Yes  No

**Facility Maintained Operation & Maintenance Plan Required?**      Yes  No

*Required for CE 28, CE 29, CE 29a-29d*

**Compliance Assurance Monitoring (CAM) Plan Required?**      Yes  No

*Facility operation and maintenance plans must be sufficient to yield reliable data from the relevant time period that are representative of the source’s compliance with the applicable requirements.*

*The data pertaining to the plan shall be maintained on site for at least 5 years. The plan and associated recordkeeping provides documentation of this facility’s implementation of its obligation to operate according to good air pollution control practice.*

*Good air pollution control practice is achieved by adoption of quality control standards in the operation and maintenance procedures for air pollution control that are comparable to industry quality control standards for the production processes associated with this emission point.*

Authority for Requirement: 567 IAC 22.108(3)

**Emission Point ID Number: EP-AMU**

Associated Equipment

Associated Emission Unit ID Numbers: EU-AMU  
Emissions Control Equipment ID Number: None  
Emissions Control Equipment Description: NA  
Continuous Emissions Monitors ID Numbers: None

---

Emission Unit vented through this Emission Point: EU-AMU  
Emission Unit Description: Air Make-up Units (9 units)  
Raw Material/Fuel: Natural Gas  
Rated Capacity: 38.05 MMBtu/hr

**Applicable Requirements**

**Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity  
Emission Limit: 40%  
Authority for Requirement: 567 IAC 23.3(2)"d"

Pollutant: Particulate Matter  
Emission Limits: 0.8 lb/MMBtu  
Authority for Requirement: 567 IAC 23.3(2)"b"

Pollutant: Sulfur Dioxide (SO2)  
Emission Limit: 500 ppmv  
Authority for Requirement: 567 IAC 23.3(3)"e"

**Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

Operational limits are not required at this time.

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

**Agency Approved Operation & Maintenance Plan Required?** Yes  No

**Facility Maintained Operation & Maintenance Plan Required?** Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?** Yes  No

Authority for Requirement: 567 IAC 22.108(3)

**Emission Point ID Number: EP-45**

Associated Equipment

Associated Emission Unit ID Numbers: EU-45  
Emissions Control Equipment ID Number: None  
Emissions Control Equipment Description: NA  
Continuous Emissions Monitors ID Numbers: None

---

Emission Unit vented through this Emission Point: EU-45  
Emission Unit Description: Unpaved Roads (Fugitive)  
Raw Material/Fuel: Fugitive Dust  
Rated Capacity: 0.55 VMT/hr

**Applicable Requirements**

**Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Fugitive Dust

Emission Limit: No person shall allow, cause or permit any materials to be handled, transported or stored; or a building, its appurtenances or a construction haul road to be used, constructed, altered, repaired or demolished, without taking reasonable precautions to prevent a nuisance. All persons shall take reasonable precautions to prevent the discharge of visible emissions of fugitive dusts beyond the lot line of the property on which the emissions originate.

Authority for requirement: 567 IAC 23.3(2)"c"

**Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

Operational limits are not required at this time.

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

**Agency Approved Operation & Maintenance Plan Required?** Yes  No

**Facility Maintained Operation & Maintenance Plan Required?** Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?** Yes  No

Authority for Requirement: 567 IAC 22.108(3)

## **Emission Point ID Number: EP-47**

### Associated Equipment

Associated Emission Unit ID Numbers: EU-47  
Emissions Control Equipment ID Number: None  
Emissions Control Equipment Description: NA  
Continuous Emissions Monitors ID Numbers: None

---

Emission Unit vented through this Emission Point: EU-47  
Emission Unit Description: Paint Burn-Off Oven #2  
Raw Material/Fuel: Natural Gas  
Rated Capacity: 0.625 MMBtu/hr

### **Applicable Requirements**

#### **Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity

Emission Limit(s): 40% <sup>(1), (2)</sup>

Authority for Requirement: 567 IAC 23.3(2) "d"

DNR Construction Permit 00-A-960-S2

<sup>(1)</sup>An exceedance of the indicator opacity of "no visible emissions" will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

<sup>(2)</sup>Visible air contaminants in excess of 40% opacity may be emitted for a period or period aggregating not more than 3 minutes in any 60-minute period an operation breakdown or during the cleaning of air pollution control equipment.

Pollutant: Particulate Matter (PM<sub>10</sub>)

Emission Limit(s): 0.38 lb/hr

Authority for Requirement: DNR Construction Permit 00-A-960-S2

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.35 gr/dscf

Authority for Requirement: 567 IAC 23.4 (12)

DNR Construction Permit 00-A-960-S2

Pollutant: Sulfur Dioxide (SO<sub>2</sub>)

Emission Limit(s): 500 ppmv

Authority for Requirement: 567 IAC 23.3(3) "e"

DNR Construction Permit 00-A-960-S2

**Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

**NESHAP Applicability**

This unit is subject to NESHAP 40 CFR 63 Subpart M MMMM – National Emission Standards for Hazardous Air Pollutants for Surface Coating of Miscellaneous Metal Parts and Products and NESHAP 40 CFR 63 Subpart P PPPP – National Emission Standards for Hazardous Air Pollutants for Surface Coating of Plastic Parts and Products.

Authority for Requirement: 40 CFR 63 Subparts M MMMM & P PPPP  
567 IAC 23.1(4) "cm" & "cp"  
DNR Construction Permit 00-A-960-S2

**Emission Point Characteristics**

*The emission point shall conform to the specifications listed below.*

Stack Height, (ft, from the ground): 34  
Stack Opening, (inches, dia.): 18  
Exhaust Flow Rate (scfm): 130  
Exhaust Temperature (°F): 1,400 °F  
Discharge Style: Vertical Obstructed  
Authority for Requirement: DNR Construction Permit 00-A-960-S2

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that either the temperature or flowrate above are different than the values stated, the owner or operator shall submit a request to the Department within thirty (30) days of the discovery to determine if a permit amendment is required or submit a permit application requesting to amend the permit.

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

**Agency Approved Operation & Maintenance Plan Required?** Yes  No

**Facility Maintained Operation & Maintenance Plan Required?** Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?** Yes  No

Authority for Requirement: 567 IAC 22.108(3)

## Emission Point ID Number: EP-58

### Associated Equipment

Associated Emission Unit ID Number: EU-58

Emissions Control Equipment ID Number: CE-58

Emissions Control Equipment Description: Mat Filters

**Table 1- Ovens and Booth**

EP	EU	Emission Unit Description	Raw Material	Rated Capacity	CE	Con. Permit
EP-58	EU-58	R & D Powdercoat Paint Booth #3	Powder Paints	5.0 lb/hr	None	None

### Applicable Requirements

#### Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

*The emissions from this emission point shall not exceed the levels specified below.*

**Table 2- Ovens and Booth**

EP	EU	Opacity	PM (gr/dscf)	SO <sub>2</sub> ppmv	VOC ton/yr
EP-58	EU-58	40%	0.01	NA	233.0 <sup>(1)</sup>

<sup>(1)</sup> Total VOC emissions from all non-combustion sources at this facility shall not exceed 233.0 tons per rolling 12-month period. All VOC-containing non-fuel materials used at the facility shall be included in the emissions calculations.

#### Operational Limits & Requirements

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

#### **NESHAP Applicability**

Drying and curing operations are part of the system that is defined as a coating operation under the National Emission Standards for Hazardous Air Pollutants. Therefore, this unit is subject to the requirements of the NESHAP for the Surface Coating of Miscellaneous Metal Parts and Products (40 CFR 63 Subpart MMMM) and the NESHAP for the Surface Coating of Plastic Parts and Products, (40 CFR 63 Subpart PPPP).

Authority for Requirement: 40 CFR 63 Subparts MMMM & PPPP  
567 IAC 23.1(4) "cm" & "cp"

#### **Operating Limits**

Operating limits for this emission unit shall be:

- A. Total VOC emissions from all non-combustion sources at this facility shall not exceed 233.0 tons per daily rolling 365-day period. All VOC emissions at the facility shall be included in the emissions calculations.

## Reporting and Recordkeeping

All records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the DNR. Records shall be legible and maintained in an orderly manner. These records shall show the following:

- A. The permittee (or owner or operator) shall maintain the following daily records:
  - i. The identification of each powdercoat material used at the facility.
  - ii. The amount, in pounds, of each powdercoat material used at the facility. For the purposes of calculating emissions, all material may be considered used on the day the materials are delivered to the facility or to the production line.
- B. The permittee shall maintain the following monthly records:
  - i. The identification of each powdercoat material used at the facility.
  - ii. The amount, in pounds, of each powdercoat material used at the facility. For the purposes of calculating emissions, all material may be considered used on the day the materials are delivered to the facility or to the production line.
  - iii. The amount of VOC emissions from all non-combustion sources, in tons. When calculating the VOC emissions from the powdercoating operations, it shall be assumed that 2.5% by weight of the powdercoat material is emitted as VOCs.
  - iv. The 12-month rolling total of the amount of VOC emissions from all non-combustion sources, in tons.
- C. If the 12-month rolling total of the VOC emissions exceeds 186.4 tons, the permittee shall immediately begin keeping the following daily records:
  - i. The amount of VOC emissions from all non-combustion sources, in tons. When calculating the VOC emissions from the powdercoating operations, it shall be assumed that 2.5% by weight of the powdercoat material is emitted as VOCs.
  - ii. The 365-day rolling total of the amount of VOC emissions from all non-combustion sources, in tons.

Daily calculations for VOC emissions shall continue until the 365-day rolling total of the amount of VOC emissions from all non-combustion sources drops below 186.4 tons for the remainder of the current calendar month plus one additional calendar month. At that time, rolling daily calculation of VOC emissions will cease per Section C of this permit. If the emissions once again exceed 186.4 tons, daily recordkeeping will be required per Section C of this permit.

- D. The permittee may take credit for any waste VOC shipped off-site. The permittee shall record the amount of the waste shipped off-site each day, and analyze the VOC content of the waste once every calendar quarter. The sample analyzed shall be taken as a representative sample (as defined in 40 CFR §260.10) of the waste sent off-site for that quarter and shall be used as representative until the subsequent quarter's analysis is received. The credit (calculated from the most current analysis and the amount shipped off-site) may be subtracted from the VOC rolling totals as of the date the waste is shipped off-site.

Authority for Requirement: DNR Construction Permits: 96-A-186-S6



**Monitoring Requirements**

The owner/operator of this equipment shall comply with the monitoring requirements listed below.

**Agency Approved Operation & Maintenance Plan Required?**      Yes  No

**Facility Maintained Operation & Maintenance Plan Required?**      Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?**      Yes  No

Authority for Requirement:567 IAC 22.108(3)

**Emission Point ID Number: EP-39A**

Associated Equipment

Associated Emission Unit ID Numbers: EU-39A

---

Emission Unit vented through this Emission Point: EU-39A  
Emission Unit Description: Metallic Paints Part Washer Heaters  
Raw Material/Fuel: Natural Gas  
Rated Capacity: 6.30 MMBtu/hr

**Applicable Requirements**

**Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity  
Emission Limit(s): 40%  
Authority for Requirement: 567 IAC 23.3(2) "d"

Pollutant: Particulate Matter (PM)  
Emission Limit(s): 0.8 lb/MMBtu  
Authority for Requirement: 567 IAC 23.3(2) "b"

Pollutant: Sulfur Dioxide (SO<sub>2</sub>)  
Emission Limit(s): 500 ppmv  
Authority for Requirement: 567 IAC 23.3(3) "e"

**Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

**Operating Limits**

Operating limits for this emission unit shall be:

- A. This emission unit shall combust pipeline quality natural gas only.

Authority for Requirement: 567 IAC 22.108 (14)

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

**Agency Approved Operation & Maintenance Plan Required?** Yes  No

**Facility Maintained Operation & Maintenance Plan Required?** Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?** Yes  No

Authority for Requirement: 567 IAC 22.108(3)

**Emission Point ID Number: EP-62**

Associated Equipment

Associated Emission Unit ID Numbers: EU-46

Emission Unit vented through this Emission Point: EU-46  
Emission Unit Description: Sanding Booth  
Raw Material/Fuel: Abrasives and Metal Parts  
Rated Capacity: 250.0 Parts/Day

**Applicable Requirements**

**Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity

Emission Limit(s): 40% <sup>(1)</sup>

Authority for Requirement: 567 IAC 23.3(2) "d"  
DNR Construction Permit 13-A-285-S1

<sup>(1)</sup>An exceedance of the indicator opacity of 10% will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM<sub>10</sub>)

Emission Limit(s): 0.21 lb/hr

Authority for Requirement: DNR Construction Permit 13-A-285-S1

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.05 gr/dscf

Authority for Requirement: 567 IAC 23.4(6)  
DNR Construction Permit 13-A-285-S1

**Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

Operational limits are not required at this time.

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

**Agency Approved Operation & Maintenance Plan Required?** Yes  No

**Facility Maintained Operation & Maintenance Plan Required?** Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?** Yes  No

Authority for Requirement: 567 IAC 22.108(3)

## **Emission Point ID Number: EP-63**

### Associated Equipment

Associated Emission Unit ID Numbers: EU-63  
Emissions Control Equipment ID Number: CE-63  
Emissions Control Equipment Description: Scrubber/ Water Wash  
Continuous Emissions Monitors ID Numbers: None

---

Emission Unit vented through this Emission Point: EU-63  
Emission Unit Description: Primer Booth  
Raw Material/Fuel: Primer Paint  
Rated Capacity: 2 guns @ 7.9 gallons per hour each

### **Applicable Requirements**

#### **Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity

Emission Limit(s): 40% <sup>(1)</sup>

Authority for Requirement: 567 IAC 23.3(2) "d"

DNR Construction Permit 13-A-286-S3

<sup>(1)</sup>An exceedance of the indicator opacity of "no visible emissions" will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.01 gr/dscf

Authority for Requirement: 567 IAC 23.4(13)

DNR Construction Permit 13-A-286-S3

Pollutant: Volatile Organic Compounds (VOC)

Emission Limit(s): 233.0 tons/yr<sup>(2)</sup>

Authority for Requirement: DNR Construction Permit 13-A-286-S3

<sup>(2)</sup>Total VOC emissions from all non-combustion sources at this facility shall not exceed 233.0 tons per rolling 12-month period. All VOC-containing non-fuel materials used at the facility shall be included in the emissions calculations.

Pollutant: Organic HAP

Emission Limit(s): See footnote (3) and (4)

Authority for Requirement: 40 CFR 63 Subparts M MMM & P PPP

567 IAC 23.1(4) "cm" & "cp"

DNR Construction Permit 13-A-286-S3

<sup>(3)</sup>Per 40 CFR §63.3890(b)(1), each existing general use coating affected source is limited to organic hazardous air pollutant (HAP) emissions of no more than 0.31 kg (2.6 lb) organic HAP emitted per liter (gal) coating solids used during each 12-month compliance period.

<sup>(4)</sup>Per 40 CFR §63.4490(b)(1), each existing general use coating affected source is limited to organic HAP emissions of no more than 0.16 kg (0.16 lb) organic HAP emitted per kg (lb) coating solids used during each 12-month compliance period.

**Operating Requirements with Associated Monitoring and Recordkeeping:**

*Unless specified by a federal regulation, all records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the Department. Records shall be legible and maintained in an orderly manner. The operating requirements and associated recordkeeping for this permit shall be:*

- A. The permittee (owner or operator) shall maintain the following daily records:
  - i. The identification of each VOC-containing, non-fuel material used at the facility.
  - ii. The amount, in gallons, of each VOC-containing non-fuel material used at the facility. For the purposes of calculating emissions, all VOC may be considered emitted on the day the materials are delivered to the facility or to the production line.
- B. The permittee shall maintain the following monthly records:
  - i. The identification and the VOC content of each VOC-containing, non-fuel material used at the facility.
  - ii. The amount, in gallons, of each VOC-containing non-fuel material used at the facility. For the purposes of calculating emissions, all VOC may be considered emitted on the day the materials are delivered to the facility or to the production line.
  - iii. The amount of VOC emissions from all non-combustion sources at the facility, in tons.
  - iv. The 12-month rolling total amount of VOC emissions from all non-combustion sources, in tons.
- C. If the 12-month rolling total amount of VOC emissions from all non-combustion sources at this facility exceeds 186.4 tons per rolling 12-month period, the permittee shall maintain the following daily records:
  - i. The total VOC emissions of (tons) from all sources at this facility; and
  - ii. The 365-day rolling total amount of VOC emissions from all sources at this facility.  
Daily calculations for VOC emissions from all non-combustion sources shall continue until the 365-day rolling total amount of VOC emissions drops below 186.4 tons for the remainder of the calendar month plus one additional calendar month. Monthly calculation of VOC emissions will then begin in the following month.
- D. The permittee may take credit for any waste VOC shipped off-site. The permittee shall record the amount of the waste shipped off-site each day, and analyze the VOC content of the waste once every calendar quarter. The sample analyzed shall be taken as a representative sample (as defined in 40 CFR §260.10) of the waste sent off-site for that quarter and shall be used as representative until the subsequent quarter's analysis is received. The credit (calculated from the most current analysis and the amount shipped off-site) may be subtracted from the VOC rolling totals as of the date the waste is shipped off-site.
- E. The permittee shall maintain minimum pressure drop across the control device (CE 63) greater than 6.5 inches of water column.
  - i. The permittee shall properly operate and maintain equipment to continuously monitor the differential pressure drop for the control device (CE 63).
    - a) The permittee shall collect and record the differential pressure drop, at a minimum of once per day.
    - b) If the pressure drop deviates below the minimum pressure drop required, then record the time, date and actions taken to correct the situation and when the pressure drop is back above the minimum pressure drop required.
  - ii. This requirement shall not apply on those days that the equipment the water wall (CE 63) controls is not in operation.

- F. This emission unit is subject to all applicable requirements set forth in NESHAP Subpart MMMM (40 CFR §63.3880 – 40 CFR §63.3981).
  - i. All spray materials shall meet the emission requirements per §63.3890 for the coating of miscellaneous metal parts, which includes, but is not limited to, limiting organic HAP emissions from finishing operations, contact adhesives and strippable spray booth coatings.
  - ii. The permittee shall comply with the work practice standards outlined in §63.3893 for the coating of miscellaneous metal parts and products.
  - iii. The owner or operator shall comply with the compliance procedures and monitoring requirements of §63.3900 for the coating of miscellaneous metal parts and products.
  - iv. The owner or operator shall perform the record keeping requirements of §63.3930 and reporting requirements of §63.3920 for the coating of miscellaneous metal parts and products.
- G. This emission unit is subject to all applicable requirements set forth in NESHAP Subpart PPPP (40 CFR §63.4480 – 40 CFR §63.4581).
  - i. All spray materials shall meet the emission requirements per §63.4490 for the coating of plastic parts, which includes, but is not limited to, limiting organic HAP emissions from finishing operations, contact adhesives and strippable spray booth coatings.
  - ii. The permittee shall comply with the work practice standards outlined in §63.4493 for the coating of plastic parts and products.
  - iii. The owner or operator shall comply with the compliance procedures and monitoring requirements of §63.4500 for the coating of plastic parts and products.
  - iv. The owner or operator shall perform the record keeping requirements of §63.4530 and reporting requirements of §63.4520 for the coating of plastic parts and products.
- H. Retain Safety Data Sheets (SDS) for all VOC and HAP containing materials used at the facility.
- I. The permittee shall inspect and maintain the control equipment (water wall), CE 63, according to the facility's operation and maintenance plan or manufacturer's specifications with inspections occurring at a minimum of once per calendar year.

Authority for Requirement: 40 CFR 63 Subparts MMMM & PPPP  
 567 IAC 23.1(4) "cm" & "cp"  
 DNR Construction Permit 13-A-286-S3

**NESHAP Applicability**

This unit is subject to the National Emission Standard for Hazardous Air Pollutants (NESHAP) for the Surface Coating of Miscellaneous Metal Parts and Products, 40 CFR 63 Subpart MMMM and the NESHAP for the Surface Coating of Plastic Parts and Products, 40 CFR 63 Subpart PPPP.

Authority for Requirement: 40 CFR 63 Subparts MMMM & PPPP  
 567 IAC 23.1(4) "cm" & "cp"  
 DNR Construction Permits: 13-A-286-S3

**Emission Point Characteristics**

*The emission point shall conform to the specifications listed below.*

Stack Height, (ft, from the ground): 47

Stack Opening, (inches, dia.): 16

Exhaust Flow Rate (scfm): 3,000

Exhaust Temperature (°F): 70

Discharge Style: Vertical Unobstructed

Authority for Requirement: DNR Construction Permit 13-A-286-S3

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that either the temperature or flowrate above are different than the values stated, the owner or operator shall submit a request to the Department within thirty (30) days of the discovery to determine if a permit amendment is required or submit a permit application requesting to amend the permit.

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed*

**Agency Approved Operation & Maintenance Plan Required?** Yes  No

**Facility Maintained Operation & Maintenance Plan Required?** Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?** Yes  No

**Paint Booth Agency Operation & Maintenance Plan**

**Weekly**

- Inspect the paint booth system for conditions that reduce the operating efficiency of the collection system. This will include a visual inspection of the condition of the filter material and/or water wall.
- Maintain a written record of the observation and any action resulting from the inspection.

**Recordkeeping and Reporting**

- Maintenance and inspection records will be kept for five years and available upon request.

**Quality Control**

- The filter equipment will be operated and maintained according to the manufacturer's recommendations.

Authority for Requirement: 567 IAC 22.108(3)

**Emission Point ID Number: EP-64**

Associated Equipment

Associated Emission Unit ID Numbers: EU-64  
Emissions Control Equipment ID Number: CE-64  
Emissions Control Equipment Description: Scrubber/ Water Wash  
Continuous Emissions Monitors ID Numbers: None

---

Emission Unit vented through this Emission Point: EU-64  
Emission Unit Description: Base Coat #1 Booth  
Raw Material/Fuel: Paint  
Rated Capacity: 2 guns @ 7.9 gallons per hour each

**Applicable Requirements**

**Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity

Emission Limit(s): 40% <sup>(1)</sup>

Authority for Requirement: 567 IAC 23.3(2) "d"  
DNR Construction Permit 13-A-287-S3

<sup>(1)</sup>An exceedance of the indicator opacity of "no visible emissions" will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.01 gr/dscf

Authority for Requirement: 567 IAC 23.4(13)  
DNR Construction Permit 13-A-287-S3

Pollutant: Volatile Organic Compounds (VOC)

Emission Limit(s): 233.0 tons/yr<sup>(2)</sup>

Authority for Requirement: DNR Construction Permit 13-A-287-S3

<sup>(2)</sup> Total VOC emissions from all non-combustion sources at this facility shall not exceed 233.0 tons per rolling 12-month period. All VOC-containing non-fuel materials used at the facility shall be included in the emissions calculations.

Pollutant: Organic HAP

Emission Limit(s): See footnote (3) and (4)

Authority for Requirement: 40 CFR 63 Subparts M MMM & PPPP  
567 IAC 23.1(4) "cm" & "cp"  
DNR Construction Permit 13-A-287-S3

<sup>(3)</sup> Per 40 CFR §63.3890(b)(1), each existing general use coating affected source is limited to organic hazardous air pollutant (HAP) emissions of no more than 0.31 kg (2.6 lb) organic HAP emitted per liter (gal) coating solids used during each 12-month compliance period.

<sup>(4)</sup> Per 40 CFR §63.4490(b)(1), each existing general use coating affected source is limited to organic HAP emissions of no more than 0.16 kg (0.16 lb) organic HAP emitted per kg (lb) coating solids used during each 12-month compliance period.



**Operating Requirements with Associated Monitoring and Recordkeeping:**

*Unless specified by a federal regulation, all records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the Department. Records shall be legible and maintained in an orderly manner. The operating requirements and associated recordkeeping for this permit shall be:*

- A. The permittee (owner or operator) shall maintain the following daily records:
  - i. The identification of each VOC-containing, non-fuel material used at the facility.
  - ii. The amount, in gallons, of each VOC-containing non-fuel material used at the facility. For the purposes of calculating emissions, all VOC may be considered emitted on the day the materials are delivered to the facility or to the production line.
- B. The permittee shall maintain the following monthly records:
  - i. The identification and the VOC content of each VOC-containing, non-fuel material used at the facility.
  - ii. The amount, in gallons, of each VOC-containing non-fuel material used at the facility. For the purposes of calculating emissions, all VOC may be considered emitted on the day the materials are delivered to the facility or to the production line.
  - iii. The amount of VOC emissions from all non-combustion sources at the facility, in tons.
  - iv. The 12-month rolling total amount of VOC emissions from all non-combustion sources, in tons.
- C. If the 12-month rolling total amount of VOC emissions from all non-combustion sources at this facility exceeds 186.4 tons per rolling 12-month period, the permittee shall maintain the following daily records:
  - i. The total VOC emissions of (tons) from all sources at this facility; and
  - ii. The 365-day rolling total amount of VOC emissions from all sources at this facility.  
Daily calculations for VOC emissions from all non-combustion sources shall continue until the 365-day rolling total amount of VOC emissions drops below 186.4 tons for the remainder of the calendar month plus one additional calendar month. Monthly calculation of VOC emissions will then begin in the following month.
- D. The permittee may take credit for any waste VOC shipped off-site. The permittee shall record the amount of the waste shipped off-site each day, and analyze the VOC content of the waste once every calendar quarter. The sample analyzed shall be taken as a representative sample (as defined in 40 CFR §260.10) of the waste sent off-site for that quarter and shall be used as representative until the subsequent quarter's analysis is received. The credit (calculated from the most current analysis and the amount shipped off-site) may be subtracted from the VOC rolling totals as of the date the waste is shipped off-site.
- E. The permittee shall maintain minimum pressure drop across the control device (CE 64) greater than 6.5 inches of water column.
  - i. The permittee shall properly operate and maintain equipment to continuously monitor the differential pressure drop for the control device (CE 64).
    - a) The permittee shall collect and record the differential pressure drop, at a minimum of once per day.
    - b) If the pressure drop deviates below the minimum pressure drop required, then record the time, date and actions taken to correct the situation and when the pressure drop is back above the minimum pressure drop required.
  - ii. This requirement shall not apply on those days that the equipment the water wall (CE 64) controls is not in operation.

- F. This emission unit is subject to all applicable requirements set forth in NESHAP Subpart MMMM (40 CFR §63.3880 – 40 CFR §63.3981).
  - i. All spray materials shall meet the emission requirements per §63.3890 for the coating of miscellaneous metal parts, which includes, but is not limited to, limiting organic HAP emissions from finishing operations, contact adhesives and strippable spray booth coatings.
  - ii. The permittee shall comply with the work practice standards outlined in §63.3893 for the coating of miscellaneous metal parts and products.
  - iii. The owner or operator shall comply with the compliance procedures and monitoring requirements of §63.3900 for the coating of miscellaneous metal parts and products.
  - iv. The owner or operator shall perform the record keeping requirements of §63.3930 and reporting requirements of §63.3920 for the coating of miscellaneous metal parts and products.
- G. This emission unit is subject to all applicable requirements set forth in NESHAP Subpart PPPP (40 CFR §63.4480 – 40 CFR §63.4581).
  - i. All spray materials shall meet the emission requirements per §63.4490 for the coating of plastic parts, which includes, but is not limited to, limiting organic HAP emissions from finishing operations, contact adhesives and strippable spray booth coatings.
  - ii. The permittee shall comply with the work practice standards outlined in §63.4493 for the coating of plastic parts and products.
  - iii. The owner or operator shall comply with the compliance procedures and monitoring requirements of §63.4500 for the coating of plastic parts and products.
  - iv. The owner or operator shall perform the record keeping requirements of §63.4530 and reporting requirements of §63.4520 for the coating of plastic parts and products.
- H. Retain Safety Data Sheets (SDS) for all VOC and HAP containing materials used at the facility.
- I. The permittee shall inspect and maintain the control equipment (water wall), CE 64, according to the facility’s operation and maintenance plan or manufacturer’s specifications with inspections occurring at a minimum of once per calendar year.

Authority for Requirement: 40 CFR 63 Subparts MMMM & PPPP  
 567 IAC 23.1(4) "cm" & "cp"  
 DNR Construction Permit: 13-A-287-S3

**NESHAP Applicability**

This unit is subject to the National Emission Standard for Hazardous Air Pollutants (NESHAP) for the Surface Coating of Miscellaneous Metal Parts and Products (40 CFR 63 Subpart MMMM; 567 IAC 23.1(4) "cm") and the NESHAP for the Surface Coating of Plastic Parts and Products (40 CFR 63 Subpart PPPP; 567 IAC 23.1(4) "cp").

Authority for Requirement: 40 CFR 63 Subparts MMMM & PPPP  
 567 IAC 23.1(4) "cm" & "cp"  
 DNR Construction Permit: 13-A-287-S3

**Emission Point Characteristics**

*The emission point shall conform to the specifications listed below.*

Stack Height, (ft, from the ground): 47

Stack Opening, (inches, dia.): 16

Exhaust Flow Rate (scfm): 3,000

Exhaust Temperature (°F): 70

Discharge Style: Vertical Unobstructed

Authority for Requirement: DNR Construction Permit 13-A-287-S3

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that either the temperature or flowrate above are different than the values stated, the owner or operator shall submit a request to the Department within thirty (30) days of the discovery to determine if a permit amendment is required or submit a permit application requesting to amend the permit.

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed*

**Agency Approved Operation & Maintenance Plan Required?** Yes  No

**Facility Maintained Operation & Maintenance Plan Required?** Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?** Yes  No

**Paint Booth Agency Operation & Maintenance Plan Weekly**

- Inspect the paint booth system for conditions that reduce the operating efficiency of the collection system. This will include a visual inspection of the condition of the filter material and/or water wall.
- Maintain a written record of the observation and any action resulting from the inspection.

**Recordkeeping and Reporting**

- Maintenance and inspection records will be kept for five years and available upon request.

**Quality Control**

- The filter equipment will be operated and maintained according to the manufacturer's recommendations.

Authority for Requirement: 567 IAC 22.108(3)

## **Emission Point ID Number: EP-65**

### Associated Equipment

Associated Emission Unit ID Numbers: EU-65  
Emissions Control Equipment ID Number: CE-65  
Emissions Control Equipment Description: Scrubber/ Water Wash  
Continuous Emissions Monitors ID Numbers: None

---

Emission Unit vented through this Emission Point: EU-65  
Emission Unit Description: Base Coat #2 Booth  
Raw Material/Fuel: Paint  
Rated Capacity: 2 guns @ 7.9 gallons per hour each

### **Applicable Requirements**

#### **Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity

Emission Limit(s): 40% <sup>(1)</sup>

Authority for Requirement: 567 IAC 23.3(2) "d"

DNR Construction Permit 13-A-288-S3

<sup>(1)</sup>An exceedance of the indicator opacity of "no visible emissions" will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.01 gr/dscf

Authority for Requirement: 567 IAC 23.4(13)

DNR Construction Permit 13-A-288-S3

Pollutant: Volatile Organic Compounds (VOC)

Emission Limit(s): 233.0 tons/yr<sup>(2)</sup>

Authority for Requirement: DNR Construction Permit 13-A-288-S3

<sup>(2)</sup>Total VOC emissions from all non-combustion sources at this facility shall not exceed 233.0 tons per rolling 12-month period. All VOC-containing non-fuel materials used at the facility shall be included in the emissions calculations.

Pollutant: Organic HAP

Emission Limit(s): See footnote (3) and (4)

Authority for Requirement: 40 CFR 63 Subparts M MMM & P PPP

567 IAC 23.1(4) "cm" & "cp"

DNR Construction Permit: 13-A-288-S3

<sup>(3)</sup>Per 40 CFR §63.3890(b)(1), each existing general use coating affected source is limited to organic hazardous air pollutant (HAP) emissions of no more than 0.31 kg (2.6 lb) organic HAP emitted per liter (gal) coating solids used during each 12-month compliance period .

<sup>(4)</sup>Per 40 CFR §63.4490(b)(1), each existing general use coating affected source is limited to organic HAP emissions of no more than 0.16 kg (0.16 lb) organic HAP emitted per kg (lb) coating solids used during each 12-month compliance period.

**Operating Requirements with Associated Monitoring and Recordkeeping:**

*Unless specified by a federal regulation, all records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the Department. Records shall be legible and maintained in an orderly manner. The operating requirements and associated recordkeeping for this permit shall be:*

- A. The permittee (owner or operator) shall maintain the following daily records:
  - i. The identification of each VOC-containing, non-fuel material used at the facility.
  - ii. The amount, in gallons, of each VOC-containing non-fuel material used at the facility. For the purposes of calculating emissions, all VOC may be considered emitted on the day the materials are delivered to the facility or to the production line.
- B. The permittee shall maintain the following monthly records:
  - i. The identification and the VOC content of each VOC-containing, non-fuel material used at the facility.
  - ii. The amount, in gallons, of each VOC-containing non-fuel material used at the facility. For the purposes of calculating emissions, all VOC may be considered emitted on the day the materials are delivered to the facility or to the production line.
  - iii. The amount of VOC emissions from all non-combustion sources at the facility, in tons.
  - iv. The 12-month rolling total amount of VOC emissions from all non-combustion sources, in tons.
- C. If the 12-month rolling total amount of VOC emissions from all non-combustion sources at this facility exceeds 186.4 tons per rolling 12-month period, the permittee shall maintain the following daily records:
  - i. The total VOC emissions of (tons) from all sources at this facility; and
  - ii. The 365-day rolling total amount of VOC emissions from all sources at this facility.  
Daily calculations for VOC emissions from all non-combustion sources shall continue until the 365-day rolling total amount of VOC emissions drops below 186.4 tons for the remainder of the calendar month plus one additional calendar month. Monthly calculation of VOC emissions will then begin in the following month.
- D. The permittee may take credit for any waste VOC shipped off-site. The permittee shall record the amount of the waste shipped off-site each day, and analyze the VOC content of the waste once every calendar quarter. The sample analyzed shall be taken as a representative sample (as defined in 40 CFR §260.10) of the waste sent off-site for that quarter and shall be used as representative until the subsequent quarter's analysis is received. The credit (calculated from the most current analysis and the amount shipped off-site) may be subtracted from the VOC rolling totals as of the date the waste is shipped off-site.
- E. The permittee shall maintain minimum pressure drop across the control device (CE 65) greater than 6.5 inches of water column.
  - i. The permittee shall properly operate and maintain equipment to continuously monitor the differential pressure drop for the control device (CE 65).
    - a) The permittee shall collect and record the differential pressure drop, at a minimum of once per day.
    - b) If the pressure drop deviates below the minimum pressure drop required, then record the time, date and actions taken to correct the situation and when the pressure drop is back above the minimum pressure drop required.
  - ii. This requirement shall not apply on those days that the equipment the water wall (CE 65) controls is not in operation.

- F. This emission unit is subject to all applicable requirements set forth in NESHAP Subpart MMMM (40 CFR §63.3880 – 40 CFR §63.3981).
  - i. All spray materials shall meet the emission requirements per §63.3890 for the coating of miscellaneous metal parts, which includes, but is not limited to, limiting organic HAP emissions from finishing operations, contact adhesives and strippable spray booth coatings.
  - ii. The permittee shall comply with the work practice standards outlined in §63.3893 for the coating of miscellaneous metal parts and products.
  - iii. The owner or operator shall comply with the compliance procedures and monitoring requirements of §63.3900 for the coating of miscellaneous metal parts and products.
  - iv. The owner or operator shall perform the record keeping requirements of §63.3930 and reporting requirements of §63.3920 for the coating of miscellaneous metal parts and products.
- G. This emission unit is subject to all applicable requirements set forth in NESHAP Subpart PPPP (40 CFR §63.4480 – 40 CFR §63.4581).
  - i. All spray materials shall meet the emission requirements per §63.4490 for the coating of plastic parts, which includes, but is not limited to, limiting organic HAP emissions from finishing operations, contact adhesives and strippable spray booth coatings.
  - ii. The permittee shall comply with the work practice standards outlined in §63.4493 for the coating of plastic parts and products.
  - iii. The owner or operator shall comply with the compliance procedures and monitoring requirements of §63.4500 for the coating of plastic parts and products.
  - iv. The owner or operator shall perform the record keeping requirements of §63.4530 and reporting requirements of §63.4520 for the coating of plastic parts and products.
- H. Retain Safety Data Sheets (SDS) for all VOC and HAP containing materials used at the facility.
- I. The permittee shall inspect and maintain the control equipment (water wall), CE 65, according to the facility’s operation and maintenance plan or manufacturer’s specifications with inspections occurring at a minimum of once per calendar year.

Authority for Requirement: 40 CFR 63 Subparts MMMM & PPPP  
 567 IAC 23.1(4) "cm" & "cp"  
 DNR Construction Permit: 13-A-288-S3

**NESHAP Applicability**

This unit is subject to the National Emission Standard for Hazardous Air Pollutants (NESHAP) for the Surface Coating of Miscellaneous Metal Parts and Products (40 CFR 63 Subpart MMMM; 567 IAC 23.1(4) "cm") and the NESHAP for the Surface Coating of Plastic Parts and Products (40 CFR 63 Subpart PPPP; 567 IAC 23.1(4) "cp").

Authority for Requirement: 40 CFR 63 Subparts MMMM & PPPP  
 567 IAC 23.1(4) "cm" & "cp"  
 DNR Construction Permit: 13-A-288-S3

**Emission Point Characteristics**

*The emission point shall conform to the specifications listed below.*

Stack Height, (ft, from the ground): 47

Stack Opening, (inches, dia.): 16

Exhaust Flow Rate (scfm): 3,000

Exhaust Temperature (°F): 70

Discharge Style: Vertical Unobstructed

Authority for Requirement: DNR Construction Permit 13-A-288-S3

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that either the temperature or flowrate above are different than the values stated, the owner or operator shall submit a request to the Department within thirty (30) days of the discovery to determine if a permit amendment is required or submit a permit application requesting to amend the permit.

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed*

**Agency Approved Operation & Maintenance Plan Required?** Yes  No

**Facility Maintained Operation & Maintenance Plan Required?** Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?** Yes  No

**Paint Booth Agency Operation & Maintenance Plan**

**Weekly**

- Inspect the paint booth system for conditions that reduce the operating efficiency of the collection system. This will include a visual inspection of the condition of the filter material and/or water wall.
- Maintain a written record of the observation and any action resulting from the inspection.

**Recordkeeping and Reporting**

- Maintenance and inspection records will be kept for five years and available upon request.

**Quality Control**

- The filter equipment will be operated and maintained according to the manufacturer's recommendations.

Authority for Requirement: 567 IAC 22.108(3)

**Emission Point ID Number: EP-66**

Associated Equipment

Associated Emission Unit ID Numbers: EU-66  
Emissions Control Equipment ID Number: CE-66  
Emissions Control Equipment Description: Scrubber/ Water Wash  
Continuous Emissions Monitors ID Numbers: None

---

Emission Unit vented through this Emission Point: EU-66  
Emission Unit Description: Clear Coat #1 Booth  
Raw Material/Fuel: Paint  
Rated Capacity: 2 guns @ 7.9 gallons per hour each

**Applicable Requirements**

**Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity

Emission Limit(s): 40% <sup>(1)</sup>

Authority for Requirement: 567 IAC 23.3(2) "d"  
DNR Construction Permit 13-A-289-S3

<sup>(1)</sup>An exceedance of the indicator opacity of "no visible emissions" will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.01 gr/dscf

Authority for Requirement: 567 IAC 23.4(13)  
DNR Construction Permit 13-A-289-S3

Pollutant: Volatile Organic Compounds (VOC)

Emission Limit(s): 233.0 tons/yr<sup>(2)</sup>

Authority for Requirement: DNR Construction Permit 13-A-289-S3

<sup>(2)</sup> Total VOC emissions from all non-combustion sources at this facility shall not exceed 233.0 tons per rolling 12-month period. All VOC-containing non-fuel materials used at the facility shall be included in the emissions calculations.

Pollutant: Organic HAP

Emission Limit(s): See footnote <sup>(3)</sup> and <sup>(4)</sup>

Authority for Requirement: 40 CFR 63 Subparts M MMM & PPPP  
567 IAC 23.1(4) "cm" & "cp"  
DNR Construction Permit: 13-A-289-S3

<sup>(3)</sup> Per 40 CFR §63.3890(b)(1), each existing general use coating affected source is limited to organic hazardous air pollutant (HAP) emissions of no more than 0.31 kg (2.6 lb) organic HAP emitted per liter (gal) coating solids used during each 12-month compliance period .

<sup>(4)</sup> Per 40 CFR §63.4490(b)(1), each existing general use coating affected source is limited to organic HAP emissions of no more than 0.16 kg (0.16 lb) organic HAP emitted per kg (lb) coating solids used during each 12-month compliance period.



**Operating Requirements with Associated Monitoring and Recordkeeping:**

*Unless specified by a federal regulation, all records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the Department. Records shall be legible and maintained in an orderly manner. The operating requirements and associated recordkeeping for this permit shall be:*

- A. The permittee (owner or operator) shall maintain the following daily records:
  - i. The identification of each VOC-containing, non-fuel material used at the facility.
  - ii. The amount, in gallons, of each VOC-containing non-fuel material used at the facility. For the purposes of calculating emissions, all VOC may be considered emitted on the day the materials are delivered to the facility or to the production line.
- B. The permittee shall maintain the following monthly records:
  - i. The identification and the VOC content of each VOC-containing, non-fuel material used at the facility.
  - ii. The amount, in gallons, of each VOC-containing non-fuel material used at the facility. For the purposes of calculating emissions, all VOC may be considered emitted on the day the materials are delivered to the facility or to the production line.
  - iii. The amount of VOC emissions from all non-combustion sources at the facility, in tons.
  - iv. The 12-month rolling total amount of VOC emissions from all non-combustion sources, in tons.
- C. If the 12-month rolling total amount of VOC emissions from all non-combustion sources at this facility exceeds 186.4 tons per rolling 12-month period, the permittee shall maintain the following daily records:
  - i. The total VOC emissions of (tons) from all sources at this facility; and
  - ii. The 365-day rolling total amount of VOC emissions from all sources at this facility.  
Daily calculations for VOC emissions from all non-combustion sources shall continue until the 365-day rolling total amount of VOC emissions drops below 186.4 tons for the remainder of the calendar month plus one additional calendar month. Monthly calculation of VOC emissions will then begin in the following month.
- D. The permittee may take credit for any waste VOC shipped off-site. The permittee shall record the amount of the waste shipped off-site each day, and analyze the VOC content of the waste once every calendar quarter. The sample analyzed shall be taken as a representative sample (as defined in 40 CFR §260.10) of the waste sent off-site for that quarter and shall be used as representative until the subsequent quarter's analysis is received. The credit (calculated from the most current analysis and the amount shipped off-site) may be subtracted from the VOC rolling totals as of the date the waste is shipped off-site.
- E. The permittee shall maintain minimum pressure drop across the control device (CE 66) greater than 6.5 inches of water column.
  - i. The permittee shall properly operate and maintain equipment to continuously monitor the differential pressure drop for the control device (CE 66).
    - a) The permittee shall collect and record the differential pressure drop, at a minimum of once per day.
    - b) If the pressure drop deviates below the minimum pressure drop required, then record the time, date and actions taken to correct the situation and when the pressure drop is back above the minimum pressure drop required.
  - ii. This requirement shall not apply on those days that the equipment the water wall (CE 66) controls is not in operation.

- F. This emission unit is subject to all applicable requirements set forth in NESHAP Subpart MMMM (40 CFR §63.3880 – 40 CFR §63.3981).
  - i. All spray materials shall meet the emission requirements per §63.3890 for the coating of miscellaneous metal parts, which includes, but is not limited to, limiting organic HAP emissions from finishing operations, contact adhesives and strippable spray booth coatings.
  - ii. The permittee shall comply with the work practice standards outlined in §63.3893 for the coating of miscellaneous metal parts and products.
  - iii. The owner or operator shall comply with the compliance procedures and monitoring requirements of §63.3900 for the coating of miscellaneous metal parts and products.
  - iv. The owner or operator shall perform the record keeping requirements of §63.3930 and reporting requirements of §63.3920 for the coating of miscellaneous metal parts and products.
- G. This emission unit is subject to all applicable requirements set forth in NESHAP Subpart PPPP (40 CFR §63.4480 – 40 CFR §63.4581).
  - i. All spray materials shall meet the emission requirements per §63.4490 for the coating of plastic parts, which includes, but is not limited to, limiting organic HAP emissions from finishing operations, contact adhesives and strippable spray booth coatings.
  - ii. The permittee shall comply with the work practice standards outlined in §63.4493 for the coating of plastic parts and products.
  - iii. The owner or operator shall comply with the compliance procedures and monitoring requirements of §63.4500 for the coating of plastic parts and products.
  - iv. The owner or operator shall perform the record keeping requirements of §63.4530 and reporting requirements of §63.4520 for the coating of plastic parts and products.
- H. Retain Safety Data Sheets (SDS) for all VOC and HAP containing materials used at the facility.
- I. The permittee shall inspect and maintain the control equipment (water wall), CE 66, according to the facility’s operation and maintenance plan or manufacturer’s specifications with inspections occurring at a minimum of once per calendar year.

Authority for Requirement: 40 CFR 63 Subparts MMMM & PPPP  
 567 IAC 23.1(4) "cm" & "cp"  
 DNR Construction Permit: 13-A-289-S3

**NESHAP Applicability**

This unit is subject to the National Emission Standard for Hazardous Air Pollutants (NESHAP) for the Surface Coating of Miscellaneous Metal Parts and Products (40 CFR 63 Subpart MMMM; 567 IAC 23.1(4) "cm") and the NESHAP for the Surface Coating of Plastic Parts and Products (40 CFR 63 Subpart PPPP; 567 IAC 23.1(4) "cp").

Authority for Requirement: 40 CFR 63 Subparts MMMM & PPPP  
 567 IAC 23.1(4) "cm" & "cp"  
 DNR Construction Permit: 13-A-289-S3

**Emission Point Characteristics**

*The emission point shall conform to the specifications listed below.*

Stack Height, (ft, from the ground): 47  
Stack Opening, (inches, dia.): 16  
Exhaust Flow Rate (scfm): 3,000  
Exhaust Temperature (°F): 70  
Discharge Style: Vertical Unobstructed  
Authority for Requirement: DNR Construction Permit 13-A-289-S3

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that either the temperature or flowrate above are different than the values stated, the owner or operator shall submit a request to the Department within thirty (30) days of the discovery to determine if a permit amendment is required or submit a permit application requesting to amend the permit.

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed*

**Agency Approved Operation & Maintenance Plan Required?**      Yes  No   
**Facility Maintained Operation & Maintenance Plan Required?**      Yes  No   
**Compliance Assurance Monitoring (CAM) Plan Required?**      Yes  No

**Paint Booth Agency Operation & Maintenance Plan**

**Weekly**

- Inspect the paint booth system for conditions that reduce the operating efficiency of the collection system. This will include a visual inspection of the condition of the filter material and/or water wall.
- Maintain a written record of the observation and any action resulting from the inspection.

**Recordkeeping and Reporting**

- Maintenance and inspection records will be kept for five years and available upon request.

**Quality Control**

- The filter equipment will be operated and maintained according to the manufacturer's recommendations.

Authority for Requirement: 567 IAC 22.108(3)

## **Emission Point ID Number: EP-67**

### Associated Equipment

Associated Emission Unit ID Numbers: EU-67  
Emissions Control Equipment ID Number: CE-67  
Emissions Control Equipment Description: Scrubber/ Water Wash  
Continuous Emissions Monitors ID Numbers: None

---

Emission Unit vented through this Emission Point: EU-67  
Emission Unit Description: Clear Coat #2 Booth  
Raw Material/Fuel: Paint  
Rated Capacity: 2 guns @ 7.9 gallons per hour each

### **Applicable Requirements**

#### **Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity

Emission Limit(s): 40% <sup>(1)</sup>

Authority for Requirement: 567 IAC 23.3(2) "d"  
DNR Construction Permit 13-A-290-S3

<sup>(1)</sup>An exceedance of the indicator opacity of "no visible emissions" will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.01 gr/dscf

Authority for Requirement: 567 IAC 23.4(13)  
DNR Construction Permit 13-A-290-S3

Pollutant: Volatile Organic Compounds (VOC)

Emission Limit(s): 233.0 tons/yr<sup>(2)</sup>

Authority for Requirement: DNR Construction Permit 13-A-290-S3

<sup>(2)</sup> Total VOC emissions from all non-combustion sources at this facility shall not exceed 233.0 tons per rolling 12-month period. All VOC-containing non-fuel materials used at the facility shall be included in the emissions calculations.

Pollutant: Organic HAP

Emission Limit(s): See footnote <sup>(2)</sup> and <sup>(3)</sup>

Authority for Requirement: DNR Construction Permit 13-A-290-S3

<sup>(2)</sup> Per 40 CFR §63.3890(b)(1), each existing general use coating affected source is limited to organic hazardous air pollutant (HAP) emissions of no more than 0.31 kg (2.6 lb) organic HAP emitted per liter (gal) coating solids used during each 12-month compliance period .

<sup>(3)</sup> Per 40 CFR §63.4490(b)(1), each existing general use coating affected source is limited to organic HAP emissions of no more than 0.16 kg (0.16 lb) organic HAP emitted per kg (lb) coating solids used during each 12-month compliance period.

**Operating Requirements with Associated Monitoring and Recordkeeping:**

*Unless specified by a federal regulation, all records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the Department. Records shall be legible and maintained in an orderly manner. The operating requirements and associated recordkeeping for this permit shall be:*

- A. The permittee (owner or operator) shall maintain the following daily records:
  - i. The identification of each VOC-containing, non-fuel material used at the facility.
  - ii. The amount, in gallons, of each VOC-containing non-fuel material used at the facility. For the purposes of calculating emissions, all VOC may be considered emitted on the day the materials are delivered to the facility or to the production line.
- B. The permittee shall maintain the following monthly records:
  - i. The identification and the VOC content of each VOC-containing, non-fuel material used at the facility.
  - ii. The amount, in gallons, of each VOC-containing non-fuel material used at the facility. For the purposes of calculating emissions, all VOC may be considered emitted on the day the materials are delivered to the facility or to the production line.
  - iii. The amount of VOC emissions from all non-combustion sources at the facility, in tons.
  - iv. The 12-month rolling total amount of VOC emissions from all non-combustion sources, in tons.
- C. If the 12-month rolling total amount of VOC emissions from all non-combustion sources at this facility exceeds 186.4 tons per rolling 12-month period, the permittee shall maintain the following daily records:
  - i. The total VOC emissions of (tons) from all sources at this facility; and
  - ii. The 365-day rolling total amount of VOC emissions from all sources at this facility.  
Daily calculations for VOC emissions from all non-combustion sources shall continue until the 365-day rolling total amount of VOC emissions drops below 186.4 tons for the remainder of the calendar month plus one additional calendar month. Monthly calculation of VOC emissions will then begin in the following month.
- D. The permittee may take credit for any waste VOC shipped off-site. The permittee shall record the amount of the waste shipped off-site each day, and analyze the VOC content of the waste once every calendar quarter. The sample analyzed shall be taken as a representative sample (as defined in 40 CFR §260.10) of the waste sent off-site for that quarter and shall be used as representative until the subsequent quarter's analysis is received. The credit (calculated from the most current analysis and the amount shipped off-site) may be subtracted from the VOC rolling totals as of the date the waste is shipped off-site.
- E. The permittee shall maintain minimum pressure drop across the control device (CE 67) greater than 6.5 inches of water column.
  - i. The permittee shall properly operate and maintain equipment to continuously monitor the differential pressure drop for the control device (CE 67).
    - a) The permittee shall collect and record the differential pressure drop, at a minimum of once per day.
    - b) If the pressure drop deviates below the minimum pressure drop required, then record the time, date and actions taken to correct the situation and when the pressure drop is back above the minimum pressure drop required.
  - ii. This requirement shall not apply on those days that the equipment the water wall (CE 67) controls is not in operation.

- F. This emission unit is subject to all applicable requirements set forth in NESHAP Subpart MMMM (40 CFR §63.3880 – 40 CFR §63.3981).
  - i. All spray materials shall meet the emission requirements per §63.3890 for the coating of miscellaneous metal parts, which includes, but is not limited to, limiting organic HAP emissions from finishing operations, contact adhesives and strippable spray booth coatings.
  - ii. The permittee shall comply with the work practice standards outlined in §63.3893 for the coating of miscellaneous metal parts and products.
  - iii. The owner or operator shall comply with the compliance procedures and monitoring requirements of §63.3900 for the coating of miscellaneous metal parts and products.
  - iv. The owner or operator shall perform the record keeping requirements of §63.3930 and reporting requirements of §63.3920 for the coating of miscellaneous metal parts and products.
- G. This emission unit is subject to all applicable requirements set forth in NESHAP Subpart PPPP (40 CFR §63.4480 – 40 CFR §63.4581).
  - i. All spray materials shall meet the emission requirements per §63.4490 for the coating of plastic parts, which includes, but is not limited to, limiting organic HAP emissions from finishing operations, contact adhesives and strippable spray booth coatings.
  - ii. The permittee shall comply with the work practice standards outlined in §63.4493 for the coating of plastic parts and products.
  - iii. The owner or operator shall comply with the compliance procedures and monitoring requirements of §63.4500 for the coating of plastic parts and products.
  - iv. The owner or operator shall perform the record keeping requirements of §63.4530 and reporting requirements of §63.4520 for the coating of plastic parts and products.
- H. Retain Safety Data Sheets (SDS) for all VOC and HAP containing materials used at the facility.
- I. The permittee shall inspect and maintain the control equipment (water wall), CE 67, according to the facility’s operation and maintenance plan or manufacturer’s specifications with inspections occurring at a minimum of once per calendar year.

Authority for Requirement: DNR Construction Permit 13-A-290-S3

**NESHAP Applicability**

This unit is subject to the National Emission Standard for Hazardous Air Pollutants (NESHAP) for the Surface Coating of Miscellaneous Metal Parts and Products (40 CFR 63 Subpart MMMM; 567 IAC 23.1(4)“cm”) and the NESHAP for the Surface Coating of Plastic Parts and Products (40 CFR 63 Subpart PPPP; 567 IAC 23.1(4)“cp”).

Authority for Requirement: 40 CFR 63 Subparts MMMM & PPPP  
 567 IAC 23.1(4) "cm" & "cp"  
 DNR Construction Permits: 13-A-290-S3

**Emission Point Characteristics**

*The emission point shall conform to the specifications listed below.*

Stack Height, (ft, from the ground): 47  
Stack Opening, (inches, dia.): 16  
Exhaust Flow Rate (scfm): 3,000  
Exhaust Temperature (°F): 70  
Discharge Style: Vertical Unobstructed  
Authority for Requirement: DNR Construction Permit 13-A-290-S3

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that either the temperature or flowrate above are different than the values stated, the owner or operator shall submit a request to the Department within thirty (30) days of the discovery to determine if a permit amendment is required or submit a permit application requesting to amend the permit.

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed*

**Agency Approved Operation & Maintenance Plan Required?**                      Yes  No   
**Facility Maintained Operation & Maintenance Plan Required?**                      Yes  No   
**Compliance Assurance Monitoring (CAM) Plan Required?**                      Yes  No

**Paint Booth Agency Operation & Maintenance Plan**

**Weekly**

- Inspect the paint booth system for conditions that reduce the operating efficiency of the collection system. This will include a visual inspection of the condition of the filter material and/or water wall.
- Maintain a written record of the observation and any action resulting from the inspection.

**Recordkeeping and Reporting**

- Maintenance and inspection records will be kept for five years and available upon request.

**Quality Control**

- The filter equipment will be operated and maintained according to the manufacturer’s recommendations.

Authority for Requirement: 567 IAC 22.108(3)

## **Emission Point ID Number: EP-68**

### Associated Equipment

Associated Emission Unit ID Numbers: EU-68  
Emissions Control Equipment ID Number: CE-68  
Emissions Control Equipment Description: Scrubber/ Water Wash  
Continuous Emissions Monitors ID Numbers: None

Emission Unit vented through this Emission Point: EU-68  
Emission Unit Description: Clear Coat #3 Booth  
Raw Material/Fuel: Paint  
Rated Capacity: 2 guns @ 7.9 gallons per hour each

### **Applicable Requirements**

#### **Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity

Emission Limit(s): 40% <sup>(1)</sup>

Authority for Requirement: 567 IAC 23.3(2) "d"  
DNR Construction Permit 13-A-291-S3

<sup>(1)</sup>An exceedance of the indicator opacity of "no visible emissions" will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.01 gr/dscf

Authority for Requirement: 567 IAC 23.4(13)  
DNR Construction Permit 13-A-291-S3

Pollutant: Volatile Organic Compounds (VOC)

Emission Limit(s): 233.0 tons/yr<sup>(2)</sup>

Authority for Requirement: DNR Construction Permit 13-A-291-S3

<sup>(2)</sup>Total VOC emissions from all non-combustion sources at this facility shall not exceed 233.0 tons per rolling 12-month period. All VOC-containing non-fuel materials used at the facility shall be included in the emissions calculations.

Pollutant: Organic HAP

Emission Limit(s): See footnote <sup>(3)</sup> and <sup>(4)</sup>

Authority for Requirement: 40 CFR 63 Subparts M MMM & P PPP  
567 IAC 23.1(4) "cm" & "cp"  
DNR Construction Permit: 13-A-291-S3

<sup>(3)</sup>Per 40 CFR §63.3890(b)(1), each existing general use coating affected source is limited to organic hazardous air pollutant (HAP) emissions of no more than 0.31 kg (2.6 lb) organic HAP emitted per liter (gal) coating solids used during each 12-month compliance period.

<sup>(4)</sup>Per 40 CFR §63.4490(b)(1), each existing general use coating affected source is limited to organic HAP emissions of no more than 0.16 kg (0.16 lb) organic HAP emitted per kg (lb) coating solids used during each 12-month compliance period.



**Operating Requirements with Associated Monitoring and Recordkeeping:**

*Unless specified by a federal regulation, all records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the Department. Records shall be legible and maintained in an orderly manner. The operating requirements and associated recordkeeping for this permit shall be:*

- A. The permittee (owner or operator) shall maintain the following daily records:
  - i. The identification of each VOC-containing, non-fuel material used at the facility.
  - ii. The amount, in gallons, of each VOC-containing non-fuel material used at the facility. For the purposes of calculating emissions, all VOC may be considered emitted on the day the materials are delivered to the facility or to the production line.
- B. The permittee shall maintain the following monthly records:
  - i. The identification and the VOC content of each VOC-containing, non-fuel material used at the facility.
  - ii. The amount, in gallons, of each VOC-containing non-fuel material used at the facility. For the purposes of calculating emissions, all VOC may be considered emitted on the day the materials are delivered to the facility or to the production line.
  - iii. The amount of VOC emissions from all non-combustion sources at the facility, in tons.
  - iv. The 12-month rolling total amount of VOC emissions from all non-combustion sources, in tons.
- C. If the 12-month rolling total amount of VOC emissions from all non-combustion sources at this facility exceeds 186.4 tons per rolling 12-month period, the permittee shall maintain the following daily records:
  - i. The total VOC emissions of (tons) from all sources at this facility; and
  - ii. The 365-day rolling total amount of VOC emissions from all sources at this facility.  
Daily calculations for VOC emissions from all non-combustion sources shall continue until the 365-day rolling total amount of VOC emissions drops below 186.4 tons for the remainder of the calendar month plus one additional calendar month. Monthly calculation of VOC emissions will then begin in the following month.
- D. The permittee may take credit for any waste VOC shipped off-site. The permittee shall record the amount of the waste shipped off-site each day, and analyze the VOC content of the waste once every calendar quarter. The sample analyzed shall be taken as a representative sample (as defined in 40 CFR §260.10) of the waste sent off-site for that quarter and shall be used as representative until the subsequent quarter's analysis is received. The credit (calculated from the most current analysis and the amount shipped off-site) may be subtracted from the VOC rolling totals as of the date the waste is shipped off-site.
- E. The permittee shall maintain minimum pressure drop across the control device (CE 68) greater than 6.5 inches of water column.
  - i. The permittee shall properly operate and maintain equipment to continuously monitor the differential pressure drop for the control device (CE 68).
    - a) The permittee shall collect and record the differential pressure drop, at a minimum of once per day.
    - b) If the pressure drop deviates below the minimum pressure drop required, then record the time, date and actions taken to correct the situation and when the pressure drop is back above the minimum pressure drop required.
  - ii. This requirement shall not apply on those days that the equipment the water wall (CE 68) controls is not in operation.

- F. This emission unit is subject to all applicable requirements set forth in NESHAP Subpart MMMM (40 CFR §63.3880 – 40 CFR §63.3981).
  - i. All spray materials shall meet the emission requirements per §63.3890 for the coating of miscellaneous metal parts, which includes, but is not limited to, limiting organic HAP emissions from finishing operations, contact adhesives and strippable spray booth coatings.
  - ii. The permittee shall comply with the work practice standards outlined in §63.3893 for the coating of miscellaneous metal parts and products.
  - iii. The owner or operator shall comply with the compliance procedures and monitoring requirements of §63.3900 for the coating of miscellaneous metal parts and products.
  - iv. The owner or operator shall perform the record keeping requirements of §63.3930 and reporting requirements of §63.3920 for the coating of miscellaneous metal parts and products.
- G. This emission unit is subject to all applicable requirements set forth in NESHAP Subpart PPPP (40 CFR §63.4480 – 40 CFR §63.4581).
  - i. All spray materials shall meet the emission requirements per §63.4490 for the coating of plastic parts, which includes, but is not limited to, limiting organic HAP emissions from finishing operations, contact adhesives and strippable spray booth coatings.
  - ii. The permittee shall comply with the work practice standards outlined in §63.4493 for the coating of plastic parts and products.
  - iii. The owner or operator shall comply with the compliance procedures and monitoring requirements of §63.4500 for the coating of plastic parts and products.
  - iv. The owner or operator shall perform the record keeping requirements of §63.4530 and reporting requirements of §63.4520 for the coating of plastic parts and products.
- H. Retain Safety Data Sheets (SDS) for all VOC and HAP containing materials used at the facility.
- I. The permittee shall inspect and maintain the control equipment (water wall), CE 68, according to the facility’s operation and maintenance plan or manufacturer’s specifications with inspections occurring at a minimum of once per calendar year.

Authority for Requirement: 40 CFR 63 Subparts MMMM & PPPP  
 567 IAC 23.1(4) "cm" & "cp"  
 DNR Construction Permit: 13-A-291-S3

**NESHAP Applicability**

This unit is subject to the National Emission Standard for Hazardous Air Pollutants (NESHAP) for the Surface Coating of Miscellaneous Metal Parts and Products (40 CFR 63 Subpart MMMM; 567 IAC 23.1(4) "cm") and the NESHAP for the Surface Coating of Plastic Parts and Products (40 CFR 63 Subpart PPPP; 567 IAC 23.1(4) "cp").

Authority for Requirement: 40 CFR 63 Subparts MMMM & PPPP  
 567 IAC 23.1(4) "cm" & "cp"  
 DNR Construction Permit: 13-A-291-S3

**Emission Point Characteristics**

*The emission point shall conform to the specifications listed below.*

Stack Height, (ft, from the ground): 47

Stack Opening, (inches, dia.): 16

Exhaust Flow Rate (scfm): 3,000

Exhaust Temperature (°F): 70

Discharge Style: Vertical Unobstructed

Authority for Requirement: DNR Construction Permit 13-A-291-S3

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that either the temperature or flowrate above are different than the values stated, the owner or operator shall submit a request to the Department within thirty (30) days of the discovery to determine if a permit amendment is required or submit a permit application requesting to amend the permit.

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

**Agency Approved Operation & Maintenance Plan Required?** Yes  No

**Facility Maintained Operation & Maintenance Plan Required?** Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?** Yes  No

**Paint Booth Agency Operation & Maintenance Plan**

**Weekly**

- Inspect the paint booth system for conditions that reduce the operating efficiency of the collection system. This will include a visual inspection of the condition of the filter material and/or water wall.
- Maintain a written record of the observation and any action resulting from the inspection.

**Recordkeeping and Reporting**

- Maintenance and inspection records will be kept for five years and available upon request.

**Quality Control**

- The filter equipment will be operated and maintained according to the manufacturer’s recommendations.

Authority for Requirement: 567 IAC 22.108(3)

**Emission Point ID Number: EP-71**

Associated Equipment

Associated Emission Unit ID Numbers: EU-71

---

Emission Unit vented through this Emission Point: EU-71

Emission Unit Description: Dry-off Oven

Raw Material/Fuel: Natural Gas

Rated Capacity: 2.0 MMBtu/hr

**Applicable Requirements**

**Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity

Emission Limit(s): 40% <sup>(1)</sup>

Authority for Requirement: 567 IAC 23.3(2) "d"

DNR Construction Permit 13-A-292-S1

<sup>(1)</sup>An exceedance of the indicator opacity of "no visible emissions" will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.1 gr/dscf

Authority for Requirement: 567 IAC 23.3(2) "a"

DNR Construction Permit 13-A-292-S1

Pollutant: Sulfur Dioxide (SO<sub>2</sub>)

Emission Limit(s): 500 ppmv

Authority for Requirement: 567 IAC 23.3(3) "e"

DNR Construction Permit 13-A-292-S1

**Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

**NESHAP Applicability**

Drying and curing operations are part of the system that is defined as a coating operation under the National Emission Standards for Hazardous Air Pollutants. Therefore, this unit is subject to the requirements of the NESHAP for the Surface Coating of Miscellaneous Metal Parts and Products, 40 CFR 63 Subpart M and the NESHAP for the Surface Coating of Plastic Parts and Products, 40 CFR 63 Subpart PPPP.

Authority for Requirement: 40 CFR 63 Subparts M & PPPP

567 IAC 23.1(4) "cm" & "cp"

DNR Construction Permit 13-A-292-S1

**Operating Limits**

Operating limits for this emission unit shall be:

- A. This unit shall use natural gas only as fuel.

**Reporting and Recordkeeping**

Unless specified by a federal regulation, all records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the Department. Records shall be legible and maintained in an orderly manner. These records shall show the following:

- A. The owner/operator shall maintain all records required under the NESHAP standards that apply to this unit.

Authority for Requirement: DNR Construction Permit 13-A-292-S1

**Emission Point Characteristics**

*The emission point shall conform to the specifications listed below.*

Stack Height, (ft, from the ground): 40

Stack Opening, (inches, dia.): 22

Exhaust Flow Rate (scfm): 6,100

Exhaust Temperature (°F): 250

Discharge Style: Vertical Unobstructed

Authority for Requirement: DNR Construction Permit 13-A-292-S1

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that either the temperature or flowrate above are different than the values stated, the owner or operator shall submit a request to the Department within thirty (30) days of the discovery to determine if a permit amendment is required or submit a permit application requesting to amend the permit.

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

**Agency Approved Operation & Maintenance Plan Required?** Yes  No

**Facility Maintained Operation & Maintenance Plan Required?** Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?** Yes  No

Authority for Requirement: 567 IAC 22.108(3)

**Emission Point ID Number: EP-72A, EP-72B**

Associated Equipment

Associated Emission Unit ID Numbers: EU-72

---

Emission Unit vented through this Emission Point: EU-72

Emission Unit Description: Cure Oven

Raw Material/Fuel: Natural Gas

Rated Capacity: 8.0 MMBtu/hr

**Applicable Requirements**

**Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from each emission point shall not exceed the levels specified below.*

Pollutant: Opacity

Emission Limit(s): 40% <sup>(1)</sup>

Authority for Requirement: 567 IAC 23.3(2) "d"

DNR Construction Permit 13-A-293-S2, 15-A-279-S1

<sup>(1)</sup>An exceedance of the indicator opacity of "no visible emissions" will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.1 gr/dscf

Authority for Requirement: 567 IAC 23.3(2) "a"

DNR Construction Permit 13-A-293-S2, 15-A-279-S1

Pollutant: Sulfur Dioxide (SO<sub>2</sub>)

Emission Limit(s): 500 ppmv

Authority for Requirement: 567 IAC 23.3(3) "e"

DNR Construction Permit 13-A-293-S2, 15-A-279-S1

**Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

National Emission Standards for Hazardous Air Pollutants (NESHAP):

The following subparts apply to this Emission Unit:

<b>Subpart</b>	<b>Title</b>	<b>Type</b>	<b>State Reference (567 IAC)</b>	<b>Federal Reference (40 CFR)</b>
A	General Provisions	NA	23.1(4)	§63.1 – §63.15
MMMM	Surface Coating of Miscellaneous Metal Parts and Products	Existing	23.1(4)"cm"	§63.3880 – §63.3981
PPPP	Surface Coating of Plastic Parts and Products	Existing	23.1(4)"cp"	§63.4480 – §63.4581

NOTE: The absence of the inclusion of any NESHAP requirements as part of this permit does not relieve the owner or operator from any obligation to comply with all applicable NESHAP conditions.

Authority for Requirement: 40 CFR 63 Subparts A, MMMM & PPPP  
567 IAC 23.1(4) "cm" & "cp"  
DNR Construction Permits 13-A-293-S2, 15-A-279-S1

**Operating Limits**

Operating limits for this emission unit shall be:

- A. This unit shall use natural gas only as fuel.
- B. The owner or operator shall maintain all records required as specified by 40 CFR §63.3930 and 40 CFR §63.4530.

Authority for Requirement: DNR Construction Permits 13-A-293-S2, 15-A-279-S1

**Emission Point Characteristics**

*Each emission point shall conform to the specifications listed below.*

Stack Height, (ft, from the ground): 47

Stack Opening, (inches, dia.): 18

Exhaust Flow Rate (scfm): 3,850

Exhaust Temperature (°F): 300

Discharge Style: Vertical Unobstructed

Authority for Requirement: DNR Construction Permits 13-A-293-S2, 15-A-279-S1

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that any of the emission point characteristics above are different than the values stated, the owner or operator shall submit a request either by electronic mail or written correspondence to the Department within thirty (30) days of the discovery to determine if a permit amendment is required, or submit a permit application requesting to amend the permit.

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

**Agency Approved Operation & Maintenance Plan Required?**      Yes  No

**Facility Maintained Operation & Maintenance Plan Required?**      Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?**      Yes  No

Authority for Requirement: 567 IAC 22.108(3)



**Emission Point ID Number: EP-73**

Associated Equipment

Associated Emission Unit ID Numbers: EU-73

---

Emission Unit vented through this Emission Point: EU-73

Emission Unit Description: Parts Washer Heater

Raw Material/Fuel: Natural Gas

Rated Capacity: 2.0 MMBtu/hr

**Applicable Requirements**

**Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity

Emission Limit(s): 40% <sup>(1)</sup>

Authority for Requirement: 567 IAC 23.3(2) "d"

DNR Construction Permit 13-A-294-S1

<sup>(1)</sup>An exceedance of the indicator opacity of "no visible emissions" will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.1 gr/dscf

Authority for Requirement: 567 IAC 23.3(2) "a"

DNR Construction Permit 13-A-294-S1

Pollutant: Sulfur Dioxide (SO<sub>2</sub>)

Emission Limit(s): 500 ppmv

Authority for Requirement: 567 IAC 23.3(3) "e"

DNR Construction Permit 13-A-294-S1

**Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

**Operating Limits**

Operating limits for this emission unit shall be:

- A. This unit shall use natural gas only as fuel.

**Reporting and Recordkeeping**

Unless specified by a federal regulation, all records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the Department. Records shall be legible and maintained in an orderly manner. These records shall show the following:

- A. The owner/operator shall maintain all records required under the NESHAP standards that apply to this unit.

Authority for Requirement: DNR Construction Permit 13-A-294-S1

**Emission Point Characteristics**

*The emission point shall conform to the specifications listed below.*

Stack Height, (ft, from the ground): 40

Stack Opening, (inches, dia.): 10

Exhaust Flow Rate (scfm): 1,150

Exhaust Temperature (°F): 1,000

Discharge Style: Vertical Obstructed

Authority for Requirement: DNR Construction Permit 13-A-294-S1

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that either the temperature or flowrate above are different than the values stated, the owner or operator shall submit a request to the Department within thirty (30) days of the discovery to determine if a permit amendment is required or submit a permit application requesting to amend the permit.

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

**Agency Approved Operation & Maintenance Plan Required?** Yes  No

**Facility Maintained Operation & Maintenance Plan Required?** Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?** Yes  No

Authority for Requirement: 567 IAC 22.108(3)

**Emission Point ID Number: EP-74**

Associated Equipment

Associated Emission Unit ID Numbers: EU-74

---

Emission Unit vented through this Emission Point: EU-74

Emission Unit Description: Spray Booth Boiler

Raw Material/Fuel: Natural Gas

Rated Capacity: 2.0 MMBtu/hr

**Applicable Requirements**

**Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity

Emission Limit(s): 40% <sup>(1)</sup>

Authority for Requirement: 567 IAC 23.3(2) "d"

DNR Construction Permit 13-A-295-S2

<sup>(1)</sup>An exceedance of the indicator opacity of "no visible emissions" will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.6 lb/MMBtu

Authority for Requirement: 567 IAC 23.3(2) "b"

DNR Construction Permit 13-A-295-S2

Pollutant: Sulfur Dioxide (SO<sub>2</sub>)

Emission Limit(s): 500 ppmv

Authority for Requirement: 567 IAC 23.3(3) "e"

DNR Construction Permit 13-A-295-S2

**Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

**NESHAP Applicability**

This emission unit is subject to the *National Emission Standard for Hazardous Air Pollutants for Major Sources: Industrial-Commercial-Institutional Boilers and Process Heaters* (40 CFR 63

Subpart DDDDD

Authority for Requirement: 40 CFR 63 Subpart DDDDD

**Operating Limits**

Operating limits for this emission unit shall be:

- A. This unit shall use natural gas only as fuel.
- B. This unit (EU 74) shall only operate when the Backup Spray Booth Boiler (EU 74B) is not in operation.

Authority for Requirement: DNR Construction Permit 13-A-295-S2

**Emission Point Characteristics**

*The emission point shall conform to the specifications listed below.*

Stack Height, (ft, from the ground): 40

Stack Opening, (inches, dia.): 8

Exhaust Flow Rate (scfm): 1,000

Exhaust Temperature (°F): 400

Discharge Style: Vertical Unobstructed

Authority for Requirement: DNR Construction Permit 13-A-295-S2

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that either the temperature or flowrate above are different than the values stated, the owner or operator shall submit a request to the Department within thirty (30) days of the discovery to determine if a permit amendment is required or submit a permit application requesting to amend the permit.

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

**Agency Approved Operation & Maintenance Plan Required?** Yes  No

**Facility Maintained Operation & Maintenance Plan Required?** Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?** Yes  No

Authority for Requirement: 567 IAC 22.108(3)

**Emission Point ID Number: EP-74B**

Associated Equipment

Associated Emission Unit ID Numbers: EU-74B

---

Emission Unit vented through this Emission Point: EU-74B

Emission Unit Description: Backup Spray Booth Boiler

Raw Material/Fuel: Natural Gas

Rated Capacity: 2.0 MMBtu/hr

**Applicable Requirements**

**Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity

Emission Limit(s): 40% <sup>(1)</sup>

Authority for Requirement: 567 IAC 23.3(2) "d"

DNR Construction Permit 16-A-275

<sup>(1)</sup>An exceedance of the indicator opacity of "no visible emissions" will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.6 lb/MMBtu

Authority for Requirement: 567 IAC 23.3(2) "b"

DNR Construction Permit 16-A-275

Pollutant: Sulfur Dioxide (SO<sub>2</sub>)

Emission Limit(s): 500 ppmv

Authority for Requirement: 567 IAC 23.3(3) "e"

DNR Construction Permit 16-A-275

**Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

**NESHAP Applicability**

This emission unit is subject to the *National Emission Standard for Hazardous Air Pollutants for Major Sources: Industrial-Commercial-Institutional Boilers and Process Heaters* (40 CFR 63 Subpart DDDDD

Authority for Requirement: 40 CFR 63 Subpart DDDDD

**Operating Limits**

Operating limits for this emission unit shall be:

A. This unit shall use natural gas only as fuel.

B. This unit (EU 74B) shall only operate when Spray Booth Boiler (EU 74) is not in operation.

Authority for Requirement: DNR Construction Permit 16-A-275

**Emission Point Characteristics**

*The emission point shall conform to the specifications listed below.*

Stack Height, (ft, from the ground): 40

Stack Opening, (inches, dia.): 8

Exhaust Flow Rate (scfm): 1,000

Exhaust Temperature (°F): 400

Discharge Style: Vertical Unobstructed

Authority for Requirement: DNR Construction Permit 16-A-275

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that either the temperature or flowrate above are different than the values stated, the owner or operator shall submit a request to the Department within thirty (30) days of the discovery to determine if a permit amendment is required or submit a permit application requesting to amend the permit.

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

**Agency Approved Operation & Maintenance Plan Required?** Yes  No

**Facility Maintained Operation & Maintenance Plan Required?** Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?** Yes  No

Authority for Requirement: 567 IAC 22.108(3)

**Emission Point ID Number: EP-75**

Associated Equipment

Associated Emission Unit ID Numbers: EU-75  
Emissions Control Equipment ID Number: NA  
Emissions Control Equipment Description: None  
Continuous Emissions Monitors ID Numbers: None

---

Emission Unit vented through this Emission Point: EU-75  
Emission Unit Description: Flash Enclosure Heater  
Raw Material/Fuel: Natural Gas  
Rated Capacity: 3.0 MMBtu/hr

**Applicable Requirements**

**Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity

Emission Limit(s): 40% <sup>(1)</sup>

Authority for Requirement: 567 IAC 23.3(2) "d"

DNR Construction Permit 13-A-296-S1

<sup>(1)</sup>An exceedance of the indicator opacity of "no visible emissions" will require the owner/operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g., stack testing).

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.1 gr/scf

Authority for Requirement: 567 IAC 23.3(2) "a"

DNR Construction Permit 13-A-296-S1

Pollutant: Sulfur Dioxide (SO<sub>2</sub>)

Emission Limit(s): 500 ppmv

Authority for Requirement: 567 IAC 23.3(3) "e"

DNR Construction Permit 13-A-296-S1

**Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

**NESHAP Applicability**

Drying and curing operations are part of the system that is defined as a coating operation under the National Emission Standards for Hazardous Air Pollutants. Therefore, this unit is subject to the requirements of the NESHAP for the Surface Coating of Miscellaneous Metal Parts and Products (40 CFR 63 Subpart Mmmm; 567 IAC 23.1(4) "cm") and the NESHAP for the Surface Coating of Plastic Parts and Products (40 CFR 63 Subpart Pppp; 567 IAC 23.1(4) "cp").

Authority for Requirement: 40 CFR 63 Subparts Mmmm & Pppp  
567 IAC 23.1(4) "cm" & "cp"  
DNR Construction Permit 13-A-296-S1

**Operating Limits**

Operating limits for this emission unit shall be:

- A. This unit shall use natural gas only as fuel.

**Reporting and Recordkeeping**

Unless specified by a federal regulation, all records as required by this permit shall be kept on-site for a minimum of five (5) years and shall be available for inspection by the Department. Records shall be legible and maintained in an orderly manner. These records shall show the following:

- A. The owner/operator shall maintain all records required under the NESHAP standards that apply to this unit.

Authority for Requirement: DNR Construction Permit 13-A-296-S1

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

**Agency Approved Operation & Maintenance Plan Required?** Yes  No

**Facility Maintained Operation & Maintenance Plan Required?** Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?** Yes  No

Authority for Requirement: 567 IAC 22.108(3)



## **Emission Point ID Number: EP-76**

### Associated Equipment

Emissions Control Equipment ID Number: CE-69  
Emissions Control Equipment Description: Cartridge Filter

---

Emission Unit vented through this Emission Point: EU-76  
Emission Unit Description: Automated Abrasive Blasting Unit  
Raw Material/Fuel: Steel Abrasive Blasting Beads  
Rated Capacity: 23,400 lb shot/ hr

### **Applicable Requirements**

#### **Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity

Emission Limit(s): 40%<sup>(1)</sup>

Authority for Requirement: 567 IAC 23.3(2)"d"  
DNR Construction Permit 19-A-621

<sup>(1)</sup>An exceedance of the indicator opacity of 10% will require the owner to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the Department may require additional proof to demonstrate compliance (e.g. stack testing)

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.05 gr/dscf

Authority for Requirement: 567 IAC 23.4(6)  
DNR Construction Permit 19-A-621

Pollutant: PM<sub>10</sub>

Emission Limit(s): 2.57 lb/hr

Authority for Requirement: DNR Construction Permit 19-A-621

Pollutant: PM<sub>2.5</sub>

Emission Limit(s): 0.46 lb/hr

Authority for Requirement: DNR Construction Permit 19-A-621

**Operational Limits & Reporting/Record keeping Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

*Records shall be kept on site for at least five years and shall be available for inspection by the Department.*

- A. The owner or operator shall maintain the Cartridge Filter (CE 69) according to the facility’s maintenance schedule. The owner or operator shall maintain a log of all maintenance and inspection activities performed on the Cartridge Filter (CE 69). This log shall include, but is not necessarily limited to:
  - i. The date and time any inspection and/or maintenance was performed on the Cartridge Filter (CE 69);
  - ii. Any issues identified during the inspection and the date each issue was resolved;
  - iii. Any issues addressed during the maintenance activities and the date each issue was resolved; and
  - iv. Identification of the staff member performing the maintenance or inspection.

Authority for Requirement: DNR Construction Permit 19-A-621

**Emission Point Characteristics**

*The emission point shall conform to the specifications listed below.*

Stack Height, (ft, from the ground): 18

Stack Opening, (inches): 12 x 18

Exhaust Flow Rate (scfm): 6,000

Exhaust Temperature (°F): 70

Discharge Style: Horizontal

Authority for Requirement: DNR Construction Permit 19-A-621

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that either the temperature or flowrate above are different than the values stated, the owner or operator shall submit a request to the Department within thirty (30) days of the discovery to determine if a permit amendment is required or submit a permit application requesting to amend the permit.

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

**Agency Approved Operation & Maintenance Plan Required?** Yes  No

**Facility Maintained Operation & Maintenance Plan Required?** Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?** Yes  No

Authority for Requirement: 567 IAC 22.108(3)

**COMPLIANCE ASSURANCE MONITORING (CAM)  
MONITORING APPROACH SUBMITTAL**

**Facility Name:** Polaris Industries, Inc. –Spirit Lake

**EIQ Number:** 92-6845

**Applicable Requirements:** PM, PM10, and PM2.5 Permit

**Limits; BACKGROUND**

Seven spray booth emission units and one automated abrasive blasting booth at the Polaris Industries, Inc. –Spirit Lake facility are subject to CAM requirements due to uncontrolled potential emissions (total particulate, particulate matter less than 10 microns in size, and particulate matter less than 2.5 microns in size) that exceed the federal major source threshold of 100 tons per year. Please note only the automated abrasive blasting booth is subject to CAM requirements for particulate matter less than 2.5 microns in size.

**Applicable Emission Units and Control Equipment:**

<i>EU</i>	<i>CE</i>
76	69

**Control Technology:**

These spray booths feature particulate matter control equipment that utilize either panel filters or water walls. The automate abrasive blasting booth features particulate matter control equipment that utilizes cartridge filters.

**Monitoring Requirements:**

Weekly visual filter inspections and operation and maintenance plan.

**Recordkeeping Requirements:**

Maintenance and inspection records will be kept for five years and available upon request.

**RATIONALE FOR SELECTION OF PERFORMANCE INDICATORS:**

Visual inspection was selected as a performance indicator because it is indicative of good operation and maintenance of the filters and water walls. When a control system is operating optimally, there will be no visible misalignment, tears, saturation, holes or any other condition that may reduce the performance of the filter or water wall.

Implementation of a control equipment inspection and maintenance program provides assurance that the control equipment is in good repair and operating properly. At least quarterly inspections of the control equipment ensure that the operation of the moving parts, nonmoving parts, and filters are all in proper operating condition.

**RATIONALE FOR SELECTION OF INDICATOR RANGES:**

The indicator range is the visual inspection of the condition of each filter or water wall with respect to alignment, saturation, tears, holes and other condition that may reduce filter performance. This indicator was established based upon the facility’s permit requirements and historical operating data. Generally, under normal operating conditions, filters that are operating properly will exhibit no visible misalignment, tears, saturation, holes or any other condition that may reduce the filter performance.

No performance tests have been conducted on these control units. Manufacturer data indicates that the filters and water walls will operate at a capture efficiency of 100% and a control efficiency of 99% for the spray booths. Manufacture data indicates that the cartridge filter will operate at a total control efficiency of 98% for the automated abrasive blasting booth.

**MONITORING APPROACH:**

	<b>Indicator #1: Filter/Water Wall Condition Inspection</b>	<b>Indicator #2: Inspection/Maintenance</b>
<b><u>Measurement Approach</u></b>	Visual inspection of the condition of each filter with respect to alignment, saturation, tears, holes, and any other condition that may reduce filter performance.	Control equipment components are inspected at least once per calendar quarter or more frequently if required by manufacturer’s specifications.

<b><u>Indicator Range</u></b>	Any visual condition that may reduce filter/water wall performance.	N/A
<b><u>Performance Criteria</u></b> <b>A. Data Representativeness</b>  <b>B. Verification of Operational Status</b>  <b>C. Quality Assurance &amp; Control</b>  <b>D. Monitoring Frequency</b>  <b>E. Data Collection Procedures</b>	A. Observations are performed in front of the filters/water wall during operation.  B. N/A  C. Observer (booth operator) is trained to perform visual inspections. Equipment will be operated according to the manufacturers' recommendations.  D. Weekly.  E. Recorded by personnel on log.	A. N/A  B. N/A  C. Qualified maintenance personnel perform inspection. Equipment will be maintained according to the manufacturers' recommendations.  D. Minimum quarterly inspections.  E. Records are maintained to document the inspections and maintenance performed.

## **Emission Point ID Number: EP-77**

### Associated Equipment

Associated Emission Unit ID Number: EU-77

---

Emission Unit vented through this Emission Point: EU-77

Emission Unit Description: Emergency Natural Gas Backup Generator (certified, spark ignition, 4-stroke, lean burn, date of construction: 2014)

Raw Material/Fuel: Natural Gas

Rated Capacity: 134 BHP

### **Applicable Requirements**

#### **Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity

Emission Limits: 40 %

Authority for Requirement: 567 IAC 23.3(2)"d"

Pollutant: Particulate Matter

Emission Limits: 0.1 gr/dscf

Authority for Requirement: 567 IAC 23.3(2)"a"

Pollutant: Sulfur Dioxide (SO<sub>2</sub>)

Emission Limits: 500 ppmv

Authority for Requirement: 567 IAC 23.3(3)"e"

#### **Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

#### **NESHAP:**

The emergency engine is subject to 40 CFR Part 63 Subpart ZZZZ - National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines (RICE). According to 40 CFR 63.6590(a)(2)(ii) this spark ignition emergency engine, located at a major source, is a new stationary RICE as it was constructed on or after June 12, 2006.

According to 40 CFR 63.6590(c)(6), this emergency engine must meet the requirements of subpart ZZZZ by meeting the requirements of 40 CFR 60 Subpart JJJJ for spark ignition engines. No further requirements apply for this engine under subpart ZZZZ.

Authority for Requirement: 40 CFR Part 63 Subpart ZZZZ  
567 IAC 23.1(4)"cz"

### NSPS Subpart JJJJ Requirements

Emission Standards:

(40 CFR 60.4233(e) and Table 1 to Subpart JJJJ)

Maximum Engine Power	Manufacture Date	Emission Standards <sup>(1)</sup>						
		g/HP-hr				ppmvd at 15% O <sub>2</sub>		
		NO <sub>x</sub>	HC + NO <sub>x</sub>	CO	VOC <sup>(2)</sup>	NO <sub>x</sub>	CO	VOC
HP ≥ 130	1/1/2009+	2.0	N/A	4.0	1.0	160	540	86

<sup>(1)</sup> Owners and operators of stationary non-certified SI engines may choose to comply with the emission standards in units of either g/HP-hr or ppmvd at 15 percent O<sub>2</sub>.

<sup>(2)</sup> Formaldehyde emissions are not included.

Compliance Demonstrations:

1. You must demonstrate compliance with the emission standards according to one of following methods (40 CFR 60.4243(b)):
  - a) Purchasing a certified engine that complies with the emission standards, or
2. Owners and operators of SI engines that are required to be certified and who operate and maintain the engine according to the manufacturer’s written instructions must keep records of required maintenance. 40 CFR 60.4243(b)(1), 4243(a) and 4245(a)(2).
3. Owners and operators of natural gas fired engines may operate their engines using propane for a maximum of 100 hours per year as an alternative fuel solely during emergency operations, but must keep records of such use. If propane is used for more than 100 hours per year in an engine that is not certified to the emission standards when using propane, a performance test must be conducted to demonstrate compliance with the emission standards. 40 CFR 60.4243(e).
4. Owners and operators of certified engines must keep a record from the manufacturer that the engines are certified to meet applicable emission standards. 40 CFR 60.4245(a)(3).

Operating and Recordkeeping Requirements (40 CFR 4243(d))

1. Owners and operators of the following emergency SI engines that do not meet the applicable standards for non-emergency engines must install a non-resettable hour meter. 40 CFR 60.4237.

Maximum Engine Power	Engine Was Built On Or After
130 ≤ HP < 500	1/1/2011

2. The engine may be operated for the purpose of maintenance checks and readiness testing a maximum of 100 hours/year. There is no time limit on use for emergency situations.
3. The engine may be operated for up to 50 hours per year for non-emergency purposes. This operating time cannot be used to generate income for the facility (e.g. supplying power to the grid) and should be included in the total of 100 hours allowed for maintenance checks and readiness testing.

4. Owners and operators of an emergency engine must keep records of all operation of the engine. The owner must record the date and time of operation of the engine and the reason the engine was in operation.
5. Owners and operators of the following emergency SI that does not meet the applicable standards for a non-emergency engine must keep the following records. 40 CFR 60.4245(b).

Maximum Engine Power	Manufactured On Or After	Recordkeeping Requirement
130 ≤ HP < 500	7/1/2011	Hours of operation recorded through a non-resettable hour meter. The owner or operator must document how many hours are spent for emergency operation, including what classified the operation as emergency and how many hours are spent for non-emergency operation.

Authority for Requirement: 40 CFR Part 60 Subpart JJJJ  
567 IAC 23.1(2)"zzz"

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

**Agency Approved Operation & Maintenance Plan Required?**      Yes  No

**Facility Maintained Operation & Maintenance Plan Required?**      Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?**      Yes  No

Authority for Requirement: 567 IAC 22.108(3)



## **Emission Point ID Number: EP-78 & EP-79**

### Associated Equipment

Associated Emission Unit ID Number: EU-78 & EU-79

---

Emission Unit vented through this Emission Point: EU-78 & EU-79

Emission Unit Description: Humidifiers

Raw Material/Fuel: Natural Gas

Rated Capacity: 1.2 MMBtu/hr

### **Applicable Requirements**

#### **Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity

Emission Limits: 40 %

Authority for Requirement: 567 IAC 23.3(2)"d"

Pollutant: Particulate Matter (PM)

Emission Limit(s): 0.6 lb/MMBtu

Authority for Requirement: 567 IAC 23.3(2) "b"

Pollutant: Sulfur Dioxide (SO<sub>2</sub>)

Emission Limits: 500 ppmv

Authority for Requirement: 567 IAC 23.3(3)"e"

#### **Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

#### **NESHAP Applicability**

These emission units are subject to the *National Emission Standard for Hazardous Air Pollutants for Major Sources: Industrial-Commercial-Institutional Boilers and Process Heaters* (40 CFR 63 Subpart DDDDD)

Authority for Requirement: 40 CFR 63 Subpart DDDDD

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

**Agency Approved Operation & Maintenance Plan Required?**      Yes  No

**Facility Maintained Operation & Maintenance Plan Required?**      Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?**      Yes  No

Authority for Requirement: 567 IAC 22.108(3)

**Emission Point ID Number: EP-80**

Associated Equipment

Emissions Control Equipment Description: None

---

Emission Unit vented through this Emission Point: EU-80

Emission Unit Description: Parts Washer (Annex)

Raw Material/Fuel: Natural Gas

Rated Capacity: 3.50 MMBtu/ hr

**Applicable Requirements**

**Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)**

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity

Emission Limit(s): 40%<sup>(1)</sup>

Authority for Requirement: 567 IAC 23.3(2)"d"

DNR Construction Permit 19-A-622-S1

<sup>(1)</sup> An exceedance of the indicator opacity of "No Visible Emissions" will require the owner/ operator to promptly investigate the emission unit and make corrections to operations or equipment associated with the exceedance. If exceedances continue after the corrections, the DNR may require additional proof to demonstrate compliance (e.g. stack testing)

Pollutant: Particulate Matter

Emission Limit(s): 0.03 lb/hr, 0.1 gr/dscf

Authority for Requirement: 567 IAC 23.3(2)"a"

DNR Construction Permit 19-A-622-S1

Pollutant: Sulfur Dioxide (SO<sub>2</sub>)

Emission Limit(s): 500 ppm<sub>v</sub>

Authority for Requirement: 567 IAC 23.3(3)"e"

DNR Construction Permit 19-A-622-S1

**Operational Limits & Requirements**

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below.*

- A. The owner or operator shall only combust natural gas in the Parts Washer Heater (EU 80).

Authority for Requirement: DNR Construction Permit 19-A-622-S1

**Emission Point Characteristics**

*The emission point shall conform to the specifications listed below.*

Stack Height, (ft, from the ground): 25  
Stack Opening, (inches): 18  
Exhaust Flow Rate (scfm): 2,000  
Exhaust Temperature (°F): 1,000  
Discharge Style: Vertical, unobstructed  
Authority for Requirement: 19-A-622-S1

The temperature and flowrate are intended to be representative and characteristic of the design of the permitted emission point. The Department recognizes that the temperature and flow rate may vary with changes in the process and ambient conditions. If it is determined that either the temperature or flowrate above are different than the values stated, the owner or operator shall submit a request to the Department within thirty (30) days of the discovery to determine if a permit amendment is required or submit a permit application requesting to amend the permit.

**Agency Approved Operation & Maintenance Plan Required?**      Yes  No

**Facility Maintained Operation & Maintenance Plan Required?**      Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?**      Yes  No

Authority for Requirement: 567 IAC 22.108(3)

## **Emission Point ID Number: EP 82**

### Associated Equipment

Associated Emission Unit ID Numbers EU-82

---

Emission Unit vented through this Emission Point: EU-82  
Emission Unit Description: Emergency Diesel Backup Generator  
Raw Material/Fuel: Diesel  
Rated Capacity: 389 bhp

### Applicable Requirements

#### Emission Limits (lb./hr, gr./dscf, lb./MMBtu, % opacity, etc.)

*The emissions from this emission point shall not exceed the levels specified below.*

Pollutant: Opacity  
Emission Limit(s): 40%  
Authority for Requirement: 567 IAC 23.3(2)"d"

Pollutant: Particulate Matter (PM)  
Emission Limit(s): 0.1 gr/dscf  
Authority for Requirement: 567 IAC 23.3(2)"a"

Pollutant: SO<sub>2</sub>  
Emission Limit(s): 500 ppm<sub>v</sub>  
Authority for Requirement: 567 IAC 23.3(3)"e"

See NSPS requirements below for additional emission limits.

#### Operational Limits & Reporting/Record keeping Requirements

*The owner/operator of this equipment shall comply with the operational limits and requirements listed below. Records shall be kept on site for at least five years and shall be available for inspection by the Department.*

#### NESHAP:

The emergency engine is subject to 40 CFR 63 Subpart ZZZZ - National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines (RICE). According to 40 CFR 63.6590(a)(2)(ii) this compression ignition emergency engine, located at a major source, is a new stationary RICE as it was constructed on or after June 12, 2006.

According to 40 CFR 63.6590(c)(6), this emergency engine must meet the requirements of subpart ZZZZ by meeting the requirements of 40 CFR 60 Subpart IIII for compression ignition engines. No further requirements apply for this emergency engine under subpart ZZZZ.

Authority for Requirement: 40 CFR Part 63 Subpart ZZZZ  
567 IAC 23.1(4)"cz"

NSPS:

Emission Standards (for engines with displacement (L/cyl) < 10):

According to 40 CFR 60.4205(b) and 4202, you must comply with the following emission standards in grams/kW-hr (grams/HP-hr):

Maximum Engine Power	Model Year(s)	NMHC + NOx	CO	PM	Opacity	Rule Ref
225 ≤ kW < 450 (302 ≤ HP < 604)	2007+	4.0 (3.0)	3.5 (2.6)	0.20 (0.15)	(1)	(2)

<sup>(1)</sup> Exhaust opacity must not exceed: 20 percent during the acceleration mode; 15 percent during the lugging mode; and 50 percent during the peaks in either the acceleration or lugging modes.

<sup>(2)</sup> 40 CFR 89.112 and 40 CFR 89.113.

Fuel Requirements:

You must use diesel fuel that has a maximum sulfur content of 15 ppm (0.0015%) by weight and a minimum cetane index of 40 or a maximum aromatic content of 35 percent by volume. 40 CFR 60.4207 and 40 CFR 1090.305.

Compliance Requirements:

1. You must operate and maintain the engine to comply with the required emission standards over the entire life of the engine (40 CFR 60.4206) by doing all of the following (40 CFR 60.4211(a)).
  - a) Operating and maintaining the engine and control device according to the manufacturer's emission-related written instructions;
  - b) Changing only those emission-related settings that are permitted by the manufacturer; and
  - c) Meeting the requirements of 40 CFR 89, 94 and/or 1068, as they apply to you.
2. You must demonstrate compliance with the applicable emission standards by purchasing an engine certified to the applicable emission standards. The engine must be installed and configured according to the manufacturer's emission-related specifications. 40 CFR 60.4211(c).
3. If you do not install, configure, operate, and maintain your engine and control device according to the manufacturer's emission-related written instructions, or you change emission-related settings in a way that is not permitted by the manufacturer, you must keep a maintenance plan and records of conducted maintenance to demonstrate compliance and must, to the extent practicable, maintain and operate the engine in a manner consistent with good air pollution control practice for minimizing emissions. In addition, you must conduct the following performance testing in accordance with 40 CFR 60.4212 to demonstrate compliance with applicable emission standards. You are required to notify the DNR 30 days

prior to the test date and are required to submit a stack test report to the DNR within 60 days after the completion of the testing. See 40 CFR 60.4211(g) for additional information.

Maximum Engine Power	Initial Test	Subsequent Test
$100 \leq \text{HP} \leq 500$	Within 1 year of engine startup, or non-permitted action <sup>(1)</sup>	Not required

<sup>(1)</sup> Non-permitted action means that you do not install, configure, operate, and maintain the engine and control device according to the manufacturer's emission-related written instructions, or you change the emission-related settings in a way that is not permitted by the manufacturer.

**Operating and Recordkeeping Requirements**

1. If your emergency engine does not meet the standards applicable to non-emergency engines, you must install a non-resettable hour meter prior to startup of the engine (40 CFR 60.4209(a)) and, starting with the model years in the following table, you must keep records of the operation of the engine in emergency and non-emergency service that are recorded through the non-resettable hour meter. The owner must record the time of operation of the engine and the reason the engine was in operation during that time. 40 CFR 60.4214(b).

Engine power	Starting model year
$130 \leq \text{KW} (175 \leq \text{HP})$	2011

2. There is no time limit on the use of the emergency engine in emergency situations. 40 CFR 60.4211(f)(1).
3. The engine may be operated for the purpose of maintenance checks and readiness testing for a maximum of 100 hours/year. See 40 CFR 60.4211(f)(2) for more information.
4. The engine may be operated for up to 50 hours per year for non-emergency purposes. This operating time cannot be used for peak shaving or to generate income for the facility (e.g. supplying power to the grid) and should be included in the total of 100 hours allowed for maintenance checks and readiness testing. See 40 CFR 60.4211(f)(3) for more information.

Authority for Requirement: 40 CFR 60 Subpart III  
567 IAC 23.1(2)"yyy"

**Monitoring Requirements**

*The owner/operator of this equipment shall comply with the monitoring requirements listed below.*

**Agency Approved Operation & Maintenance Plan Required?** Yes  No

**Facility Maintained Operation & Maintenance Plan Required?** Yes  No

**Compliance Assurance Monitoring (CAM) Plan Required?** Yes  No

Authority for Requirement: 567 IAC 24.108(3)

## IV. General Conditions

This permit is issued under the authority of the Iowa Code subsection 455B.133(8) and in accordance with 567 Iowa Administrative Code (IAC). When 567 IAC as amended May 15, 2024, and cited in this permit becomes State Implementation Plan (SIP) approved, it will supersede 567 IAC as amended February 8, 2023. Prior to May 15, 2024, all Title V rule citations in this Title V permit were found and cited in 567 IAC Chapter 22. During the period from May 15, 2024, to the date that 567 IAC as amended May 15, 2024, is approved into the SIP, both 567 IAC as amended May 15, 2024, and 567 IAC as amended February 8, 2023 form the legal basis for the applicable requirements included in this permit. A crosswalk showing the citation changes is attached to this permit in Appendix B.

### G1. Duty to Comply

1. The permittee must comply with all conditions of the Title V permit. Any permit noncompliance constitutes a violation of the Act and is grounds for enforcement action; for a permit termination, revocation and reissuance, or modification; or for denial of a permit renewal application. *567 IAC 24.108(9)"a"*
2. Any compliance schedule shall be supplemental to, and shall not sanction noncompliance with, the applicable requirements on which it is based. *567 IAC 24.105(2)"h"(3)*
3. Where an applicable requirement of the Act is more stringent than an applicable requirement of regulations promulgated under Title IV of the Act, both provisions shall be enforceable by the administrator and are incorporated into this permit. *567 IAC 24.108(1)"b"*
4. Unless specified as either "state enforceable only" or "local program enforceable only", all terms and conditions in the permit, including provisions to limit a source's potential to emit, are enforceable by the administrator and citizens under the Act. *567 IAC 24.108(14)*
5. It shall not be a defense for a permittee, in an enforcement action, that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. *567 IAC 24.108(9)"b"*
6. For applicable requirements with which the permittee is in compliance, the permittee shall continue to comply with such requirements. For applicable requirements that will become effective during the permit term, the permittee shall meet such requirements on a timely basis. *567 IAC 24.108(15)"c"*

### G2. Permit Expiration

1. Except as provided in rule 567—24.104(455B), permit expiration terminates a source's right to operate unless a timely and complete application for renewal has been submitted in accordance with rule 567—24.105(455B). *567 IAC 24.116(2)*
2. To be considered timely, the owner, operator, or designated representative (where applicable) of each source required to obtain a Title V permit shall submit on forms or electronic format specified by the Department. Additional copies to local programs or EPA are not required for application materials submitted through the electronic format specified by the Department. The application must include all emission points, emission units, air pollution control equipment, and monitoring devices at the facility. All emissions generating activities, including fugitive emissions, must be included. The definition of a complete application is as indicated in 567 IAC 24.105(2). *567 IAC 24.105*

### G3. Certification Requirement for Title V Related Documents

Any application, report, compliance certification or other document submitted pursuant to this permit shall contain certification by a responsible official of truth, accuracy, and completeness. All certifications shall state that, based on information and belief formed after reasonable



inquiry, the statements and information in the document are true, accurate, and complete. 567 IAC 24.107(4)

#### **G4. Annual Compliance Certification**

By March 31 of each year, the permittee shall submit compliance certifications for the previous calendar year. The certifications shall include descriptions of means to monitor the compliance status of all emissions sources including emissions limitations, standards, and work practices in accordance with applicable requirements. The certification for a source shall include the identification of each term or condition of the permit that is the basis of the certification; the compliance status; whether compliance was continuous or intermittent; the method(s) used for determining the compliance status of the source, currently and over the reporting period consistent with all applicable department rules. For sources determined not to be in compliance at the time of compliance certification, a compliance schedule shall be submitted which provides for periodic progress reports, dates for achieving activities, milestones, and an explanation of why any dates were missed and preventive or corrective measures. The compliance certification shall be submitted to the administrator, director, and the appropriate DNR Field office. 567 IAC 24.108(15)"e"

#### **G5. Semi-Annual Monitoring Report**

By March 31 and September 30 of each year, the permittee shall submit a report of any monitoring required under this permit for the 6 month periods of July 1 to December 31 and January 1 to June 30, respectively. All instances of deviations from permit requirements must be clearly identified in these reports, and the report must be signed by a responsible official, consistent with 567 IAC 24.107(4). The semi-annual monitoring report shall be submitted to the director and the appropriate DNR Field office. 567 IAC 24.108 (5)

#### **G6. Annual Fee**

1. The permittee is required under subrule 567 IAC 24.106 to pay an annual fee based on the total tons of actual emissions of each regulated air pollutant. Beginning July 1, 1996, Title V operating permit fees will be paid on July 1 of each year. The fee shall be based on emissions for the previous calendar year.
2. The fee amount shall be calculated based on the first 4,000 tons of each regulated air pollutant emitted each year. The fee to be charged per ton of pollutant will be available from the department by June 1 of each year. The Responsible Official will be advised of any change in the annual fee per ton of pollutant.
3. The emissions inventory shall be submitted annually by March 31 with forms specified by the department documenting actual emissions for the previous calendar year.
4. The fee shall be submitted annually by July 1 with forms specified by the department.
5. If there are any changes to the emission calculation form, the department shall make revised forms available to the public by January 1. If revised forms are not available by January 1, forms from the previous year may be used and the year of emissions documented changed. The department shall calculate the total statewide Title V emissions for the prior calendar year and make this information available to the public no later than April 30 of each year.
6. Phase I acid rain affected units under section 404 of the Act shall not be required to pay a fee for emissions which occur during the years 1993 through 1999 inclusive.
7. The fee for a portable emissions unit or stationary source which operates both in Iowa and out of state shall be calculated only for emissions from the source while operating in Iowa.
8. Failure to pay the appropriate Title V fee represents cause for revocation of the Title V permit as indicated in 567 IAC 24.115(1)"d".

### **G7. Inspection of Premises, Records, Equipment, Methods and Discharges**

Upon presentation of proper credentials and any other documents as may be required by law, the permittee shall allow the director or the director's authorized representative to:

1. Enter upon the permittee's premises where a Title V source is located or emissions-related activity is conducted, or where records must be kept under the conditions of the permit;
2. Have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit;
3. Inspect, at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit; and
4. Sample or monitor, at reasonable times, substances or parameters for the purpose of ensuring compliance with the permit or other applicable requirements. *567 IAC 24.108 (15)"b"*

### **G8. Duty to Provide Information**

The permittee shall furnish to the director, within a reasonable time, any information that the director may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee also shall furnish to the director copies of records required to be kept by the permit, or for information claimed to be confidential, the permittee shall furnish such records directly to the administrator of EPA along with a claim of confidentiality. *567 IAC 24.108 (9)"e"*

### **G9. General Maintenance and Repair Duties**

The owner or operator of any air emission source or control equipment shall:

1. Maintain and operate the equipment or control equipment at all times in a manner consistent with good practice for minimizing emissions.
2. Remedy any cause of excess emissions in an expeditious manner.
3. Minimize the amount and duration of any excess emission to the maximum extent possible during periods of such emissions. These measures may include but not be limited to the use of clean fuels, production cutbacks, or the use of alternate process units or, in the case of utilities, purchase of electrical power until repairs are completed.
4. Schedule, at a minimum, routine maintenance of equipment or control equipment during periods of process shutdowns to the maximum extent possible. *567 IAC 21.8(1)*

### **G10. Recordkeeping Requirements for Compliance Monitoring**

1. In addition to any source specific recordkeeping requirements contained in this permit, the permittee shall maintain the following compliance monitoring records, where applicable:

- a. The date, place and time of sampling or measurements
- b. The date the analyses were performed.
- c. The company or entity that performed the analyses.
- d. The analytical techniques or methods used.
- e. The results of such analyses; and
- f. The operating conditions as existing at the time of sampling or measurement.
- g. The records of quality assurance for continuous compliance monitoring systems (including but not limited to quality control activities, audits and calibration drifts.)

2. The permittee shall retain records of all required compliance monitoring data and support information for a period of at least 5 years from the date of compliance monitoring sample, measurement report or application. Support information includes all calibration and maintenance records and all original strip chart recordings for continuous compliance monitoring, and copies of all reports required by the permit.

3. For any source which in its application identified reasonably anticipated alternative operating scenarios, the permittee shall:
  - a. Comply with all terms and conditions of this permit specific to each alternative scenario.
  - b. Maintain a log at the permitted facility of the scenario under which it is operating.
  - c. Consider the permit shield, if provided in this permit, to extend to all terms and conditions under each operating scenario. *567 IAC 24.108(4), 567 IAC 24.108(12)*

**G11. Evidence used in establishing that a violation has or is occurring.**

Notwithstanding any other provisions of these rules, any credible evidence may be used for the purpose of establishing whether a person has violated or is in violation of any provisions herein.

1. Information from the use of the following methods is presumptively credible evidence of whether a violation has occurred at a source:
  - a. A monitoring method approved for the source and incorporated in an operating permit pursuant to 567 Chapter 24;
  - b. Compliance test methods specified in 567 Chapter 21; or
  - c. Testing or monitoring methods approved for the source in a construction permit issued pursuant to 567 Chapter 22.
2. The following testing, monitoring or information gathering methods are presumptively credible testing, monitoring, or information gathering methods:
  - a. Any monitoring or testing methods provided in these rules; or
  - b. Other testing, monitoring, or information gathering methods that produce information comparable to that produced by any method in subrule 21.5(1) or this subrule. *567 IAC 21.5(1)-567 IAC 21.5(2)*

**G12. Prevention of Accidental Release: Risk Management Plan Notification and Compliance Certification**

If the permittee is required to develop and register a risk management plan pursuant to section 112(r) of the Act, the permittee shall notify the department of this requirement. The plan shall be filed with all appropriate authorities by the deadline specified by EPA. A certification that this risk management plan is being properly implemented shall be included in the annual compliance certification of this permit. *567 IAC 24.108(6)*

**G13. Hazardous Release**

The permittee must report any situation involving the actual, imminent, or probable release of a hazardous substance into the atmosphere which, because of the quantity, strength and toxicity of the substance, creates an immediate or potential danger to the public health, safety or to the environment. A verbal report shall be made to the department at (515) 725-8694 and to the local police department or the office of the sheriff of the affected county as soon as possible but not later than six hours after the discovery or onset of the condition. This verbal report must be followed up with a written report as indicated in 567 IAC 131.2(2). *567 IAC Chapter 131-State Only*

**G14. Excess Emissions and Excess Emissions Reporting Requirements**

1. Excess Emissions. Excess emission during a period of startup, shutdown, or cleaning of control equipment is not a violation of the emission standard if the startup, shutdown or cleaning is accomplished expeditiously and in a manner consistent with good practice for minimizing emissions. Cleaning of control equipment which does not require the shutdown of the process equipment shall be limited to one six-minute period per one-hour period. An incident of excess emission (other than an incident during startup, shutdown or cleaning of control equipment) is a

violation. If the owner or operator of a source maintains that the incident of excess emission was due to a malfunction, the owner or operator must show that the conditions which caused the incident of excess emission were not preventable by reasonable maintenance and control measures. Determination of any subsequent enforcement action will be made following review of this report. If excess emissions are occurring, either the control equipment causing the excess emission shall be repaired in an expeditious manner or the process generating the emissions shall be shutdown within a reasonable period of time. An expeditious manner is the time necessary to determine the cause of the excess emissions and to correct it within a reasonable period of time. A reasonable period of time is eight hours plus the period of time required to shut down the process without damaging the process equipment or control equipment. A variance from this subrule may be available as provided for in Iowa Code section 455B.143. In the case of an electric utility, a reasonable period of time is eight hours plus the period of time until comparable generating capacity is available to meet consumer demand with the affected unit out of service, unless, the director shall, upon investigation, reasonably determine that continued operation constitutes an unjustifiable environmental hazard and issue an order that such operation is not in the public interest and require a process shutdown to commence immediately.

## 2. Excess Emissions Reporting

a. Initial Reporting of Excess Emissions. An incident of excess emission (other than an incident of excess emission during a period of startup, shutdown, or cleaning) shall be reported to the appropriate field office of the department within eight hours of, or at the start of the first working day following the onset of the incident. The reporting exemption for an incident of excess emission during startup, shutdown or cleaning does not relieve the owner or operator of a source with continuous monitoring equipment of the obligation of submitting reports required in 567-subrule 21.10(6). An initial report of excess emission is not required for a source with operational continuous monitoring equipment (as specified in 567-subrule 21.10(1) ) if the incident of excess emission continues for less than 30 minutes and does not exceed the applicable emission standard by more than 10 percent or the applicable visible emission standard by more than 10 percent opacity. The initial report may be made by electronic mail (E-mail), in person, or by telephone and shall include as a minimum the following:

- i. The identity of the equipment or source operation from which the excess emission originated and the associated stack or emission point.
- ii. The estimated quantity of the excess emission.
- iii. The time and expected duration of the excess emission.
- iv. The cause of the excess emission.
- v. The steps being taken to remedy the excess emission.
- vi. The steps being taken to limit the excess emission in the interim period.

b. Written Reporting of Excess Emissions. A written report of an incident of excess emission shall be submitted as a follow-up to all required initial reports to the department within seven days of the onset of the upset condition, and shall include as a minimum the following:

- i. The identity of the equipment or source operation point from which the excess emission originated and the associated stack or emission point.
- ii. The estimated quantity of the excess emission.
- iii. The time and duration of the excess emission.
- iv. The cause of the excess emission.

- v. The steps that were taken to remedy and to prevent the recurrence of the incident of excess emission.
- vi. The steps that were taken to limit the excess emission.
- vii. If the owner claims that the excess emission was due to malfunction, documentation to support this claim. *567 IAC 21.7(1)-567 IAC 21.7(4)*

**G15. Permit Deviation Reporting Requirements**

A deviation is any failure to meet a term, condition or applicable requirement in the permit. Reporting requirements for deviations that result in a hazardous release or excess emissions have been indicated above (see G13 and G14). Unless more frequent deviation reporting is specified in the permit, any other deviation shall be documented in the semi-annual monitoring report and the annual compliance certification (see G4 and G5). *567 IAC 24.108(5)"b"*

**G16. Notification Requirements for Sources That Become Subject to NSPS and NESHAP Regulations**

During the term of this permit, the permittee must notify the department of any source that becomes subject to a standard or other requirement under 567-subrule 23.1(2) (standards of performance of new stationary sources) or section 111 of the Act; or 567-subrule 23.1(3) (emissions standards for hazardous air pollutants), 567-subrule 23.1(4) (emission standards for hazardous air pollutants for source categories) or section 112 of the Act. This notification shall be submitted in writing to the department pursuant to the notification requirements in 40 CFR Section 60.7, 40 CFR Section 61.07, and/or 40 CFR Section 63.9. *567 IAC 23.1(2), 567 IAC 23.1(3), 567 IAC 23.1(4)*

**G17. Requirements for Making Changes to Emission Sources That Do Not Require Title V Permit Modification**

1. Off Permit Changes to a Source. Pursuant to section 502(b)(10) of the CAAA, the permittee may make changes to this installation/facility without revising this permit if:
  - a. The changes are not major modifications under any provision of any program required by section 110 of the Act, modifications under section 111 of the act, modifications under section 112 of the act, or major modifications as defined in 567 IAC Chapter 24.
  - b. The changes do not exceed the emissions allowable under the permit (whether expressed therein as a rate of emissions or in terms of total emissions);
  - c. The changes are not modifications under any provisions of Title I of the Act and the changes do not exceed the emissions allowable under the permit (whether expressed therein as a rate of emissions or as total emissions);
  - d. The changes are not subject to any requirement under Title IV of the Act (revisions affecting Title IV permitting are addressed in rules 567—24.140(455B) through 567 - 24.144(455B));
  - e. The changes comply with all applicable requirements.
  - f. For each such change, the permitted source provides to the department and the administrator by certified mail, at least 30 days in advance of the proposed change, a written notification, including the following, which must be attached to the permit by the source, the department and the administrator:
    - i. A brief description of the change within the permitted facility,
    - ii. The date on which the change will occur,
    - iii. Any change in emission as a result of that change,
    - iv. The pollutants emitted subject to the emissions trade
    - v. If the emissions trading provisions of the state implementation plan are

invoked, then Title V permit requirements with which the source shall comply; a description of how the emissions increases and decreases will comply with the terms and conditions of the Title V permit.

vi. A description of the trading of emissions increases and decreases for the purpose of complying with a federally enforceable emissions cap as specified in and in compliance with the Title V permit; and

vii. Any permit term or condition no longer applicable as a result of the change.  
*567 IAC 24.110(1)*

2. Such changes do not include changes that would violate applicable requirements or contravene federally enforceable permit terms and conditions that are monitoring (including test methods), record keeping, reporting, or compliance certification requirements. *567 IAC 24.110(2)*

3. Notwithstanding any other part of this rule, the director may, upon review of a notice, require a stationary source to apply for a Title V permit if the change does not meet the requirements of subrule 24.110(1). *567 IAC 24.110(3)*

4. The permit shield provided in subrule 24.108(18) shall not apply to any change made pursuant to this rule. Compliance with the permit requirements that the source will meet using the emissions trade shall be determined according to requirements of the state implementation plan authorizing the emissions trade. *567 IAC 24.110(4)*

5. No permit revision shall be required, under any approved economic incentives, marketable permits, emissions trading and other similar programs or processes, for changes that are provided for in this permit. *567 IAC 24.108(11)*

#### **G18. Duty to Modify a Title V Permit**

##### **1. Administrative Amendment.**

a. An administrative permit amendment is a permit revision that does any of the following:

i. Correct typographical errors

ii. Identify a change in the name, address, or telephone number of any person identified in the permit, or provides a similar minor administrative change at the source;

iii. Require more frequent monitoring or reporting by the permittee; or

iv. Allow for a change in ownership or operational control of a source where the director determines that no other change in the permit is necessary, provided that a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new permittee has been submitted to the director.

b. The permittee may implement the changes addressed in the request for an administrative amendment immediately upon submittal of the request. The request shall be submitted to the director.

c. Administrative amendments to portions of permits containing provisions pursuant to Title IV of the Act shall be governed by regulations promulgated by the administrator under Title IV of the Act.

##### **2. Minor Title V Permit Modification.**

a. Minor Title V permit modification procedures may be used only for those permit modifications that satisfy all of the following:

- i. Do not violate any applicable requirement;
  - ii. Do not involve significant changes to existing monitoring, reporting or recordkeeping requirements in the Title V permit;
  - iii. Do not require or change a case by case determination of an emission limitation or other standard, or an increment analysis;
  - iv. Do not seek to establish or change a permit term or condition for which there is no corresponding underlying applicable requirement and that the source has assumed in order to avoid an applicable requirement to which the source would otherwise be subject. Such terms and conditions include any federally enforceable emissions caps which the source would assume to avoid classification as a modification under any provision under Title I of the Act; and an alternative emissions limit approved pursuant to regulations promulgated under section 112(i)(5) of the Act;
  - v. Are not modifications under any provision of Title I of the Act; and
  - vi. Are not required to be processed as significant modification under rule 567 - 24.113(455B).
- b. An application for minor permit revision shall be on the minor Title V modification application form and shall include at least the following:
- i. A description of the change, the emissions resulting from the change, and any new applicable requirements that will apply if the change occurs;
  - ii. The permittee's suggested draft permit;
  - iii. Certification by a responsible official, pursuant to 567 IAC 24.107(4), that the proposed modification meets the criteria for use of minor permit modification procedures and a request that such procedures be used; and
  - iv. Completed forms to enable the department to notify the administrator and the affected states as required by 567 IAC 24.107(7).
- c. The permittee may make the change proposed in its minor permit modification application immediately after it files the application. After the permittee makes this change and until the director takes any of the actions specified in 567 IAC 24.112(4) "a" to "c", the permittee must comply with both the applicable requirements governing the change and the proposed permit terms and conditions. During this time, the permittee need not comply with the existing permit terms and conditions it seeks to modify. However, if the permittee fails to comply with its proposed permit terms and conditions during this time period, the existing permit terms and conditions it seeks to modify may be enforced against the facility.

### 3. Significant Title V Permit Modification.

Significant Title V modification procedures shall be used for applications requesting Title V permit modifications that do not qualify as minor Title V modifications or as administrative amendments. These include but are not limited to all significant changes in monitoring permit terms, every relaxation of reporting or recordkeeping permit terms, and any change in the method of measuring compliance with existing requirements. Significant Title V modifications shall meet all requirements of 567 IAC Chapter 24, including those for applications, public participation, review by affected states, and review by the administrator, as those requirements that apply to Title V issuance and renewal.

The permittee shall submit an application for a significant permit modification not later than three months after commencing operation of the changed source unless the existing Title V

permit would prohibit such construction or change in operation, in which event the operation of the changed source may not commence until the department revises the permit. *567 IAC 24.111-567 IAC 24.113*

#### **G19. Duty to Obtain Construction Permits**

Unless exempted in 567 IAC 22.1(2) or to meet the parameters established in 567 IAC 22.1(1)"c", the permittee shall not construct, install, reconstruct or alter any equipment, control equipment or anaerobic lagoon without first obtaining a construction permit, or conditional permit, or permit pursuant to rule 567 IAC 22.8, or permits required pursuant to rules 567 IAC 22.4, 567 IAC 22.5, 567 IAC 31.3, and 567 IAC 33.3 as required in 567 IAC 22.1(1). A permit shall be obtained prior to the initiation of construction, installation or alteration of any portion of the stationary source or anaerobic lagoon. *567 IAC 22.1(1)*

#### **G20. Asbestos**

The permittee shall comply with 567 IAC 23.1(3)"a", and 567 IAC 23.2(3)"g" when activities involve asbestos mills, surfacing of roadways, manufacturing operations, fabricating, insulating, waste disposal, spraying applications, demolition and renovation operations (*567 IAC 23.1(3)"a"*); training fires and controlled burning of a demolished building (*567 IAC 23.2*).

#### **G21. Open Burning**

The permittee is prohibited from conducting open burning, except as provided in 567 IAC 23.2. *567 IAC 23.2 except 23.2(3)"j"; 567 IAC 23.2(3)"j" - State Only*

#### **G22. Acid Rain (Title IV) Emissions Allowances**

The permittee shall not exceed any allowances that it holds under Title IV of the Act or the regulations promulgated there under. Annual emissions of sulfur dioxide in excess of the number of allowances to emit sulfur dioxide held by the owners and operators of the unit or the designated representative of the owners and operators is prohibited. Exceedences of applicable emission rates are prohibited. "Held" in this context refers to both those allowances assigned to the owners and operators by USEPA, and those allowances supplementally acquired by the owners and operators. The use of any allowance prior to the year for which it was allocated is prohibited. Contravention of any other provision of the permit is prohibited. *567 IAC 24.108(7)*

#### **G23. Stratospheric Ozone and Climate Protection (Title VI) Requirements**

1. The permittee shall comply with the standards for labeling of products using ozone-depleting substances pursuant to 40 CFR Part 82, Subpart E:
  - a. All containers in which a class I or class II substance is stored or transported, all products containing a class I substance, and all products directly manufactured with a class I substance must bear the required warning statement if it is being introduced into interstate commerce pursuant to § 82.106.
  - b. The placement of the required warning statement must comply with the requirements pursuant to § 82.108.
  - c. The form of the label bearing the required warning statement must comply with the requirements pursuant to § 82.110.
  - d. No person may modify, remove, or interfere with the required warning statement except as described in § 82.112.
2. The permittee shall comply with the standards for recycling and emissions reduction pursuant to 40 CFR Part 82, Subpart F, except as provided for MVACs in Subpart B:
  - a. Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices pursuant to § 82.156.
  - b. Equipment used during the maintenance, service, repair, or disposal of appliances must



comply with the standards for recycling and recovery equipment pursuant to § 82.158.

c. Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to § 82.161.

d. Persons disposing of small appliances, MVACs, and MVAC-like appliances must comply with reporting and recordkeeping requirements pursuant to § 82.166. ("MVAC-like appliance" as defined at § 82.152)

e. Persons owning commercial or industrial process refrigeration equipment must comply with the leak repair requirements pursuant to § 82.156.

f. Owners/operators of appliances normally containing 50 or more pounds of refrigerant must keep records of refrigerant purchased and added to such appliances pursuant to § 82.166.

3. If the permittee manufactures, transforms, imports, or exports a class I or class II substance, the permittee is subject to all the requirements as specified in 40 CFR part 82, Subpart A, Production and Consumption Controls.

4. If the permittee performs a service on motor (fleet) vehicles when this service involves ozone-depleting substance refrigerant (or regulated substitute substance) in the motor vehicle air conditioner (MVAC), the permittee is subject to all the applicable requirements as specified in 40 CFR part 82, Subpart B, Servicing of Motor Vehicle Air Conditioners. The term "motor vehicle" as used in Subpart B does not include a vehicle in which final assembly of the vehicle has not been completed. The term "MVAC" as used in Subpart B does not include the air-tight sealed refrigeration system used as refrigerated cargo, or system used on passenger buses using HCFC-22 refrigerant,

5. The permittee shall be allowed to switch from any ozone-depleting or greenhouse gas generating substances to any alternative that is listed in the Significant New Alternatives Program (SNAP) promulgated pursuant to 40 CFR part 82, Subpart G, Significant New Alternatives Policy Program. *40 CFR part 82*

#### **G24. Permit Reopenings**

1. This permit may be modified, revoked, reopened, and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any permit condition. *567 IAC 24.108(9)"c"*

2. Additional applicable requirements under the Act become applicable to a major part 70 source with a remaining permit term of 3 or more years. Revisions shall be made as expeditiously as practicable, but not later than 18 months after the promulgation of such standards and regulations.

a. Reopening and revision on this ground is not required if the permit has a remaining term of less than three years;

b. Reopening and revision on this ground is not required if the effective date of the requirement is later than the date on which the permit is due to expire, unless the original permit or any of its terms and conditions have been extended pursuant to 40 CFR 70.4(b)(10)(i) or (ii) as amended to May 15, 2001.

c. Reopening and revision on this ground is not required if the additional applicable requirements are implemented in a general permit that is applicable to the source and the source receives approval for coverage under that general permit. *567 IAC 24.108(17)"a"*, *567 IAC 24.108(17)"b"*

3. A permit shall be reopened and revised under any of the following circumstances:

- a. The department receives notice that the administrator has granted a petition for disapproval of a permit pursuant to 40 CFR 70.8(d) as amended to July 21, 1992, provided that the reopening may be stayed pending judicial review of that determination;
  - b. The department or the administrator determines that the Title V permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of the Title V permit;
  - c. Additional applicable requirements under the Act become applicable to a Title V source, provided that the reopening on this ground is not required if the permit has a remaining term of less than three years, the effective date of the requirement is later than the date on which the permit is due to expire, or the additional applicable requirements are implemented in a general permit that is applicable to the source and the source receives approval for coverage under that general permit. Such a reopening shall be complete not later than 18 months after promulgation of the applicable requirement.
  - d. Additional requirements, including excess emissions requirements, become applicable to a Title IV affected source under the acid rain program. Upon approval by the administrator, excess emissions offset plans shall be deemed to be incorporated into the permit.
  - e. The department or the administrator determines that the permit must be revised or revoked to ensure compliance by the source with the applicable requirements. *567 IAC 24.114(1)*
4. Proceedings to reopen and reissue a Title V permit shall follow the procedures applicable to initial permit issuance and shall effect only those parts of the permit for which cause to reopen exists. *567 IAC 24.114(2)*
  5. A notice of intent shall be provided to the Title V source at least 30 days in advance of the date the permit is to be reopened, except that the director may provide a shorter time period in the case of an emergency. *567 IAC 24.114(3)*

#### **G25. Permit Shield**

1. The director may expressly include in a Title V permit a provision stating that compliance with the conditions of the permit shall be deemed compliance with any applicable requirements as of the date of permit issuance, provided that:
  - a. Such applicable requirements are included and are specifically identified in the permit;
  - or
  - b. The director, in acting on the permit application or revision, determines in writing that other requirements specifically identified are not applicable to the source, and the permit includes the determination or a concise summary thereof.
2. A Title V permit that does not expressly state that a permit shield exists shall be presumed not to provide such a shield.
3. A permit shield shall not alter or affect the following:
  - a. The provisions of Section 303 of the Act (emergency orders), including the authority of the administrator under that section;
  - b. The liability of an owner or operator of a source for any violation of applicable requirements prior to or at the time of permit issuance;
  - c. The applicable requirements of the acid rain program, consistent with Section 408(a) of the Act;
  - d. The ability of the department or the administrator to obtain information from the facility pursuant to Section 114 of the Act. *567 IAC 24.108 (18)*

**G26. Severability**

The provisions of this permit are severable and if any provision or application of any provision is found to be invalid by this department or a court of law, the application of such provision to other circumstances, and the remainder of this permit, shall not be affected by such finding. *567 IAC 24.108 (8)*

**G27. Property Rights**

The permit does not convey any property rights of any sort, or any exclusive privilege. *567 IAC 24.108 (9)"d"*

**G28. Transferability**

This permit is not transferable from one source to another. If title to the facility or any part of it is transferred, an administrative amendment to the permit must be sought consistent with the requirements of *567 IAC 24.111(1)*. *567 IAC 24.111 (1)"d"*

**G29. Disclaimer**

No review has been undertaken on the engineering aspects of the equipment or control equipment other than the potential of that equipment for reducing air contaminant emissions. *567 IAC 24.3(3)"c"*

**G30. Notification and Reporting Requirements for Stack Tests or Monitor Certification**

The permittee shall notify the department's stack test contact in writing not less than 30 days before a required test or performance evaluation of a continuous emission monitor is performed to determine compliance with applicable requirements of *567 – Chapter 23* or a permit condition. Such notice shall include the time, the place, the name of the person who will conduct the test and other information as required by the department. If the owner or operator does not provide timely notice to the department, the department shall not consider the test results or performance evaluation results to be a valid demonstration of compliance with applicable rules or permit conditions. Upon written request, the department may allow a notification period of less than 30 days. At the department's request, a pretest meeting shall be held not later than 15 days prior to conducting the compliance demonstration. A testing protocol shall be submitted to the department no later than 15 days before the owner or operator conducts the compliance demonstration. A representative of the department shall be permitted to witness the tests. Results of the tests shall be submitted in writing to the department's stack test contact in the form of a comprehensive report within six weeks (42 days) of the completion of the testing. Compliance tests conducted pursuant to this permit shall be conducted with the source operating in a normal manner at its maximum continuous output as rated by the equipment manufacturer, or the rate specified by the owner as the maximum production rate at which the source shall be operated. In cases where compliance is to be demonstrated at less than the maximum continuous output as rated by the equipment manufacturer, and it is the owner's intent to limit the capacity to that rating, the owner may submit evidence to the department that the source has been physically altered so that capacity cannot be exceeded, or the department may require additional testing, continuous monitoring, reports of operating levels, or any other information deemed necessary by the department to determine whether such source is in compliance.

Stack test notifications, reports and correspondence shall be sent to:

Stack Test Review Coordinator  
Iowa DNR, Air Quality Bureau  
6200 Park Ave  
Suite 200  
Des Moines, IA 50321  
(515) 343-6589

Within Polk and Linn Counties, stack test notifications, reports and correspondence shall also be directed to the supervisor of the respective county air pollution program.

*567 IAC 21.10(7)"a", 567 IAC 21.10(9)*

**G31. Prevention of Air Pollution Emergency Episodes**

The permittee shall comply with the provisions of 567 IAC Chapter 26 in the prevention of excessive build-up of air contaminants during air pollution episodes, thereby preventing the occurrence of an emergency due to the effects of these contaminants on the health of persons.

*567 IAC 26.1(1)*

**G32. Contacts List**

The current address and phone number for reports and notifications to the EPA administrator is:

Iowa Compliance Officer  
Air Branch  
Enforcement and Compliance Assurance Division  
U.S. EPA Region 7  
11201 Renner Blvd.  
Lenexa, KS 66219  
(913) 551-7020

The current address and phone number for reports and notifications to the department or the Director is:

Chief, Air Quality Bureau  
Iowa Department of Natural Resources  
6200 Park Ave  
Suite 200  
Des Moines, IA 50321  
(515) 313-8325

Reports or notifications to the DNR Field Offices or local programs shall be directed to the supervisor at the appropriate field office or local program. Current addresses and phone numbers are:

**Field Office 1**

1101 Commercial Court, Suite 10  
Manchester, IA 52057  
(563) 927-2640

**Field Office 2**

2300-15th St., SW  
Mason City, IA 50401  
(641) 424-4073

**Field Office 3**

1900 N. Grand Ave.  
Spencer, IA 51301  
(712) 262-4177

**Field Office 4**

1401 Sunnyside Lane  
Atlantic, IA 50022  
(712) 243-1934

**Field Office 5**

6200 Park Ave  
Suite 200  
Des Moines, IA 50321  
(515) 725-0268

**Field Office 6**

1023 West Madison Street  
Washington, IA 52353-1623  
(319) 653-2135

**Polk County Public Works Dept.**

Air Quality Division  
5885 NE 14th St.  
Des Moines, IA 50313  
(515) 286-3351

**Linn County Public Health**

Air Quality Branch  
1020 6<sup>th</sup> Street SE  
Cedar Rapids, IA 52401  
(319) 892-6000

## V. Appendix A:

- A. 40 CFR 63 Subpart A – General Provisions  
<https://www.ecfr.gov/current/title-40/chapter-I/subchapter-C/part-63/subpart-A>
- B. 40 CFR 63 Subpart MMMM – *National Emission Standards for Hazardous Air Pollutants for Surface Coating of Miscellaneous Metal Parts and Products*  
<https://www.ecfr.gov/current/title-40/chapter-I/subchapter-C/part-63/subpart-MMMM>
- C. 40 CFR 63 Subpart PPPP – *National Emission Standards for Hazardous Air Pollutants for Surface Coating of Plastic Parts and Products*  
<https://www.ecfr.gov/current/title-40/chapter-I/subchapter-C/part-63/subpart-PPPP>
- D. 40 CFR 63 Subpart DDDDD – *National Emission Standards for Hazardous Air Pollutants for Industrial, Commercial, and Institutional Boilers and Process Heaters*  
<https://www.ecfr.gov/current/title-40/chapter-I/subchapter-C/part-63/subpart-DDDDD>
- E. 40 CFR 63 Subpart ZZZZ – *National Emissions Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines*  
<https://www.ecfr.gov/current/title-40/chapter-I/subchapter-C/part-63/subpart-ZZZZ>
- F. 40 CFR 60 Subpart JJJJ – *Standards of Performance for Stationary Spark Ignition Internal Combustion Engines.*  
<https://www.ecfr.gov/current/title-40/chapter-I/subchapter-C/part-60/subpart-JJJJ>

## **Appendix B: Executive Order 10 (EO10) Rules Crosswalk**

Previous Chapter Number (Prior to 5/15/2024)	Current Chapter Number	Previous Title and Description (Prior to 5/15/2024)	Current Title and Description	Actions Taken
20	20 (Reserved)	Scope of Title - Definitions	N/A	Definitions moved to Ch. 21, 22 and 23. Rescinded Ch. 20. (Reserved)
21	21	Compliance	Compliance, Excess Emissions, and Measurement of Emissions	Kept and combined with rules from Chapters 24, 25, 26, and 29.
22	22	Controlling Pollution-Permits	Controlling Air Pollution - Construction Permitting	Kept construction permit rules and combined with Ch. 20 (definitions) and Ch. 28 (NAAQS). Moved operating permit rules to Chapter 24.
22.100 - 22.300(12)	(New) 24	N/A	Operating Permits	Moved operating permit rules from Ch. 22 to Ch. 24.
23	23	Emission Standards	Air Emission Standards	Kept
24	(New) 21	Excess Emissions	Compliance, Excess Emissions, and Measurement of Emissions	Moved rules and combined with Ch. 21. Moved TV rules here (to Ch. 24).
25	(New) 21	Emissions Measurement	Compliance, Excess Emissions, and Measurement of Emissions	Moved rules and combined with Ch. 21. Rescinded Ch. 25. (Reserved)
26	(New) 21	Emergency Air Pollution Episodes	Compliance, Excess Emissions, and Measurement of Emissions	Moved rules and combined with Ch. 21. Rescinded Ch. 26. (Reserved)
27	27	Local Program Acceptance	Local Program Acceptance	Kept
28	22	NAAQS	N/A	Moved rules and combined with Ch. 22. Rescinded Ch. 28. (Reserved)
29	(New) 21	Opacity Qualifications	Compliance, Excess Emissions, and Measurement of Emissions	Moved rules and combined with Ch. 21. Rescinded Ch. 29. (Reserved)
30	30	Fees	Fee	Kept
31	31	Nonattainment Areas	Nonattainment New Source Review	Kept
32	N/A	AFO Field Study	N/A	Rescinded Ch. 32. (Reserved)
33	33	Special regulations and construction permit requirements for major stationary sources—Prevention of significant deterioration (PSD) of air quality	Construction permit requirements for major stationary sources—Prevention of significant deterioration (PSD)	Kept
34	N/A	Emissions Trading-CAIR-CAMR	N/A	Rescinded Ch. 34. (Reserved)
35	N/A	Grant Assistance Programs	N/A	Rescinded Ch. 35. (Reserved)



Previous Chapter Number (Prior to 5/15/2024)	Current Chapter Number	Previous Title and Description (Prior to 5/15/2024)	Current Title and Description	Actions Taken
<b>20</b>	<b>20 (Reserved)</b>	<b>Scope of Title - Definitions</b>	<b>N/A</b>	<b>Definitions moved to Ch. 21, 22 and 23.</b> <b>Rescinded Ch. 20. (Reserved)</b>
20.1	N/A	Scope of title	N/A	
20.2	Ch. 21, 22, 23	Definitions	Definitions	See beginning of Ch. 21, 22, and 23
20.3	N/A	Air quality forms generally	N/A	

<b>21</b>	<b>21</b>	<b>Compliance</b>	<b>Compliance, Excess Emissions, and Measurement of Emissions</b>	<b>Kept and combined with rules from Chapters 24, 25, 26, and 29.</b>
21.1	21.1	Compliance Schedule	Definitions and compliance requirements	Added definitions from Ch. 21, some language updated
21.2	21.2	Variances	Variances	Some language updated
21.3	21.3	Emission reduction program	Reserved	Reserved
21.4	21.4	Circumvention of rules	Circumvention of rules	Minor language updated
21.5	21.5	Evidence used in establishing that a violation has or is occurring	Evidence used in establishing that a violation has occurred or is occurring	21.5(2) Reserved, some language updated
21.6	21.6	Temporary electricity generation for disaster situations	Temporary electricity generation for disaster situations	Minor language updated
24.1	21.7	Excess emission reporting	Excess emission reporting	Moved from Ch. 24, some language updated
24.2	21.8	Maintenance and repair requirements	Maintenance and repair requirements	Moved from Ch. 24, some language updated
N/A	21.9	N/A	Compliance with other requirements	New language
25.1	21.10	Testing and sampling of new and existing equipment	Testing and sampling of new and existing equipment	Moved from Ch. 25, some language updated
25.2	21.11	Continuous emission monitoring under the acid rain program	Continuous emission monitoring under the acid rain program	Moved from Ch. 25, some language updated
25.3	N/A	Mercury emissions testing and monitoring	N/A	Rescinded. Except 25.3(5)
25.3(5)	21.12	Affected sources subject to Section 112(g)	Affected sources subject to Section 112(g)	Moved from Ch. 25, some language updated
29.1	21.13	Methodology and qualified observer	Methodology and qualified observer	Moved from Ch. 29, some language updated
26.1	21.14	Prevention of air pollution emergency episodes - General	Prevention of air pollution emergency episodes	Moved from Ch. 26, some language updated
26.2	21.15	Episode criteria	Episode criteria	Moved from Ch. 26, some language updated
26.3	21.16	Preplanned abatement strategies	Preplanned abatement strategies	Moved from Ch. 26, some language updated
26.4	21.17	Actions taken during episodes	Actions taken during episodes	Moved from Ch. 26, some language updated
Ch 26 Table III	Table I	Abatement strategies emission reduction actions alert level	Abatement strategies emission reduction actions alert level	Moved from Ch. 26, reference federal appendix table
Ch 26 Table IV	Table II	Abatement strategies emission reduction actions warning level	Abatement strategies emission reduction actions warning level	Moved from Ch. 26, reference federal appendix table
Ch 26 Table V	Table III	Abatement strategies emission reduction actions emergency level	Abatement strategies emission reduction actions emergency level	Moved from Ch. 26, reference federal appendix table

<b>22</b>	<b>22</b>	<b>Controlling Pollution-Permits</b>	<b>Controlling Air Pollution - Construction Permitting</b>	<b>Kept construction permit rules and combined with Ch. 20 (definitions) and Ch. 28 (NAAQS).</b> <b>Moved operating permit rules to Chapter 24.</b>
22.1	22.1	Permits required for new or existing stationary sources	Definitions and permit requirements for new or existing stationary sources	Added definitions from Ch. 20, some language updated
22.2	22.2	Processing permit applications	Processing permit applications	
22.3	22.3	Issuing permits	Issuing permits	
22.4	22.4	Special requirements for major stationary sources located in areas designated attainment or unclassified (PSD)	Major stationary sources located in areas designated attainment or unclassified (PSD)	
22.5	22.5	Special requirements for nonattainment areas	Major stationary sources located in areas designated Nonattainment	
22.6	22.6	Nonattainment area designations	Reserved	

Previous Chapter Number (Prior to 5/15/2024)	Current Chapter Number	Previous Title and Description (Prior to 5/15/2024)	Current Title and Description	Actions Taken
22.7	22.7	Alternative emission control program	Alternative emission control program	
22.8	22.8	Permit by rule	Permit by rule	
22.9	22.9	Special requirements for visibility protection	Special requirements for visibility protection	A lot of language updated or removed
22.10	22.10	Permitting requirements for country grain elevators, country grain terminal elevators, grain terminal elevators and feed mill equipment	Permitting requirements for country grain elevators, country grain terminal elevators, grain terminal elevators and feed mill equipment	
28.1	22.11	Ambient air quality standards - Statewide standards	Ambient air quality standards	Moved from Ch. 28, minor language updated
22.12 to 22.99	N/A	Reserved	N/A	Removed

22.100 - 22.300(12)	(New) 24	N/A	Operating Permits	Moved operating permit rules from Ch. 22 to Ch. 24.
22.100	24.100	Definitions for Title V operating permits	Definitions for Title V operating permits	Moved from Ch. 22, some language updated, many 40 CFR 70 definitions adopted by reference
22.101	24.101	Applicability of Title V operating permit requirements	Applicability of Title V operating permit requirements	Moved from Ch. 22, some language updated to correct punctuation and remove old dates
22.102	24.102	Source category exemptions	Source category exemptions	Moved from Ch. 22, some language updated to correct punctuation
22.103	24.103	Insignificant activities	Insignificant activities	Moved from Ch. 22, some language updated to correct typos and remove old dates
22.104	24.104	Requirement to have a Title V permit	Requirement to have a Title V permit	Moved from Ch. 22, some language updated no changes to rule text
22.105	24.105	Title V permit applications	Title V permit applications	Moved from Ch. 22, updated language to address electronic submissions and remove past application due dates
22.106	24.106	Annual Title V emissions inventory	Annual Title V emissions inventory	Moved from Ch. 22, no changes to rule text
22.107	24.107	Title V permit processing procedures	Title V permit processing procedures	Moved from Ch. 22, some language updated to update locations of public records and remove old CFR amendment dates
22.108	24.108	Permit content	Permit content	Moved from Ch. 22, some language updated to correct punctuation, remove old dates, and adopt 40 CFR 70 rules by reference
22.109	24.109	General permits	General permits	Moved from Ch. 22, language updated to adopt 40 CFR 70 rules by reference
22.110	24.110	Changes allowed without a Title V permit revision (off-permit revisions)	Changes allowed without a Title V permit revision (off-permit revisions)	Moved from Ch. 22, some language updated to remove redundant language
22.111	24.111	Administrative amendments to Title V permits	Administrative amendments to Title V permits	Moved from Ch. 22, no changes to rule text
22.112	24.112	Minor Title V permit modifications	Minor Title V permit modifications	Moved from Ch. 22, no changes to rule text
22.113	24.113	Significant Title V permit modifications	Significant Title V permit modifications	Moved from Ch. 22, no changes to rule text
22.114	24.114	Title V permit reopenings	Title V permit re-openings	Moved from Ch. 22 to Ch. 24, some language updated to adopt 40 CFR 70 rules by reference
22.115	24.115	Suspension, termination, and revocation of Title V permits	Suspension, termination, and revocation of Title V permits	Moved from Ch. 22, no changes to rule text
22.116	24.116	Title V permit renewals	Title V permit renewals	Moved from Ch. 22, no changes to rule text
22.117-22.119	24.117-24.119	Reserved	Reserved	Moved from Ch. 22, no changes to rule text
22.120	24.120	Acid rain program—definitions	Acid rain program—definitions	Moved from Ch. 22, some language updated to remove old CFR amendment dates and address electronic submissions
22.121	24.121	Measurements, abbreviations, and acronyms	Reserved	Moved from Ch. 22, no changes to rule text
22.122	24.122	Applicability	Applicability	Moved from Ch. 22, language updated to adopt 40 CFR 70 rules by reference
22.123	24.123	Acid rain exemptions	Acid rain exemptions	Moved from Ch. 22, some language updated to correct punctuation
22.124	24.124	Retired units exemption	Reserved	Moved from Ch. 22, no changes to rule text
22.125	24.125	Standard requirements	Standard requirements	Moved from Ch. 22, language updated to adopt 40 CFR 70 rules by reference
22.126	24.126	Designated representative—submissions	Designated representative—submissions	Moved from Ch. 22, language updated to adopt 40 CFR 70 rules by reference
22.127	24.127	Designated representative—objections	Designated representative—objections	Moved from Ch. 22, language updated to adopt 40 CFR 70 rules by reference
22.128	24.128	Acid rain applications—requirement to apply	Acid rain applications—requirement to apply	Moved from Ch. 22, language updated to adopt 40 CFR 70 rules by reference

22.129	24.129	Information requirements for acid rain permit applications	Information requirements for acid rain permit applications	Moved from Ch. 22, no changes to rule text
Previous Chapter Number (Prior to 5/15/2024)	Current Chapter Number	Previous Title and Description (Prior to 5/15/2024)	Current Title and Description	Actions Taken
22.130	24.130	Acid rain permit application shield and binding effect of permit application	Acid rain permit application shield and binding effect of permit application	Moved from Ch. 22, language updated to adopt 40 CFR 70 rules by reference
22.131	24.131	Acid rain compliance plan and compliance options—general	Acid rain compliance plan and compliance options—general	Moved from Ch. 22, language updated to adopt 40 CFR 70 rules by reference
22.132	24.132	Repowering extensions	Reserved	Moved from Ch. 22, no changes to rule text
22.133	24.133	Acid rain permit contents—general	Acid rain permit contents—general	Moved from Ch. 22, language updated to adopt 40 CFR 70 rules by reference
22.134	24.134	Acid rain permit shield	Acid rain permit shield	Moved from Ch. 22, language updated to adopt 40 CFR 70 rules by reference
22.135	24.135	Acid rain permit issuance procedures—general	Acid rain permit issuance procedures—general	Moved from Ch. 22, no changes to rule text
22.136	24.136	Acid rain permit issuance procedures—completeness	Acid rain permit issuance procedures—completeness	Moved from Ch. 22, no changes to rule text
22.137	24.137	Acid rain permit issuance procedures—statement of basis	Acid rain permit issuance procedures—statement of basis	Moved from Ch. 22, no changes to rule text
22.138	24.138	Issuance of acid rain permits	Issuance of acid rain permits	Moved from Ch. 22, some language updated to remove old dates and deadlines
22.139	24.139	Acid rain permit appeal procedures	Acid rain permit appeal procedures	Moved from Ch. 22, no changes to rule text
22.140	24.140	Permit revisions—general	Permit revisions—general	Moved from Ch. 22, some language updated to remove old dates
22.141	24.141	Permit modifications	Permit modifications	Moved from Ch. 22, no changes to rule text
22.142	24.142	Fast-track modifications	Fast-track modifications	Moved from Ch. 22, language updated to adopt 40 CFR 70 rules by reference
22.143	24.143	Administrative permit amendment	Administrative permit amendment	Moved from Ch. 22, some language updated to remove fax option
22.144	24.144	Automatic permit amendment	Automatic permit amendment	Moved from Ch. 22, language updated to adopt 40 CFR 70 rules by reference
22.145	24.145	Permit reopenings	Permit re-openings	Moved from Ch. 22, language updated to adopt 40 CFR 70 rules by reference
22.146	24.146	Compliance certification—annual report	Compliance certification—annual report	Moved from Ch. 22, no changes to rule text
22.147	24.147	Compliance certification—units with repowering extension plans	Reserved	Moved from Ch. 22, no changes to rule text
22.148	24.148	Sulfur dioxide opt-ins	Sulfur dioxide opt-ins	Moved from Ch. 22, some language updated to update the 40 CFR Part 74 amendment date
22.149 - 22.199	24.149 - 24.299	Reserved	Reserved	Moved from Ch. 22, no changes to rule text
22.200	24.200 - 24.299	Definitions for voluntary operating permits	Reserved	Moved from Ch. 22, no changes to rule text
22.201	24.200 - 24.299	Eligibility for voluntary operating permits	Reserved	Moved from Ch. 22, no changes to rule text
22.203	24.200 - 24.299	Voluntary operating permit applications	Reserved	Moved from Ch. 22, no changes to rule text
22.204	24.200 - 24.299	Voluntary operating permit fees	Reserved	Moved from Ch. 22, no changes to rule text
22.205	24.200 - 24.299	Voluntary operating permit processing procedures	Reserved	Moved from Ch. 22, no changes to rule text
22.206	24.200 - 24.299	Permit content	Reserved	Moved from Ch. 22, no changes to rule text
22.207	24.200 - 24.299	Relation to construction permits	Reserved	Moved from Ch. 22, no changes to rule text
22.208	24.200 - 24.299	Suspension, termination, and revocation of voluntary operating permits	Reserved	Moved from Ch. 22, no changes to rule text
22.209	24.200 - 24.299	Change of ownership for facilities with voluntary operating permits	Reserved	Moved from Ch. 22, no changes to rule text
22.210 - 22.299	24.200 - 24.299	Reserved	Reserved	Moved from Ch. 22, no changes to rule text
22.300	24.300	Operating permit by rule for small sources	Operating permit by rule for small sources	Moved from Ch. 22, no changes to rule text

23	23	Emission Standards	Air Emission Standards	Kept
23.1	23.1	Emission standards	Emission standards	Kept, language updated, tables used
23.2	23.2	Open burning	Open burning	Kept, some language updated
23.3	23.3	Specific contaminants	Specific contaminants	Kept, some language updated
23.4	23.4	Specific processes	Specific processes	Kept, some language updated
23.5	23.5	Anaerobic lagoons	Anaerobic lagoons	Kept, some language updated
23.6	23.6	Alternative emission limits (the “bubble concept”)	Reserved	Removed

Previous Chapter Number (Prior to 5/15/2024)	Current Chapter Number	Previous Title and Description (Prior to 5/15/2024)	Current Title and Description	Actions Taken
<b>24</b>	<b>(New) 21</b>	<b>Excess Emissions</b>	<b>Compliance, Excess Emissions, and Measurement of Emissions</b>	<b>Moved rules and combined with Ch. 21.</b> <b>Moved operating permit rules here (to Ch. 24).</b>
24.1	21.7	Excess emission reporting	Excess emission reporting	Moved from Ch. 24, some language updated
24.2	21.8	Maintenance and repair requirements	Maintenance and repair requirements	Moved from Ch. 24, some language updated
<b>25</b>	<b>(New) 21</b>	<b>Emissions Measurement</b>	<b>Compliance, Excess Emissions, and Measurement of Emissions</b>	<b>Moved rules and combined with Ch. 21.</b> <b>Rescinded Ch. 25. (Reserved)</b>
25.1	21.10	Testing and sampling of new and existing equipment	Testing and sampling of new and existing equipment	Moved from Ch. 25, some language updated
25.2	21.11	Continuous emission monitoring under the acid rain program	Continuous emission monitoring under the acid rain program	Moved from Ch. 25, some language updated
25.3		Mercury emissions testing and monitoring	N/A	Rescinded. Except 25.3(5)
25.3(5)	21.12	Affected sources subject to Section 112(g)	Affected sources subject to Section 112(g)	Moved from Ch. 25, some language updated
<b>26</b>	<b>(New) 21</b>	<b>Emergency Air Pollution Episodes</b>	<b>Compliance, Excess Emissions, and Measurement of Emissions</b>	<b>Moved rules and combined with Ch. 21.</b> <b>Rescinded Ch. 26. (Reserved)</b>
26.1	21.14	Prevention of air pollution emergency episodes - General	Prevention of air pollution emergency episodes	Moved from Ch. 26, some language updated
26.2	21.15	Episode criteria	Episode criteria	Moved from Ch. 26, some language updated
26.3	21.16	Preplanned abatement strategies	Preplanned abatement strategies	Moved from Ch. 26, some language updated
26.4	21.17	Actions taken during episodes	Actions taken during episodes	Moved from Ch. 26, some language updated
Ch 26 Table III	Table I	Abatement strategies emission reduction actions alert level	Abatement strategies emission reduction actions alert level	Moved from Ch. 26, reference federal appendix table
Ch 26 Table IV	Table II	Abatement strategies emission reduction actions warning level	Abatement strategies emission reduction actions warning level	Moved from Ch. 26, reference federal appendix table
Ch 26 Table V	Table III	Abatement strategies emission reduction actions emergency level	Abatement strategies emission reduction actions emergency level	Moved from Ch. 26, reference federal appendix table
<b>27</b>	<b>27</b>	<b>Local Program Acceptance</b>	<b>Local Program Acceptance</b>	<b>Kept</b>
27.1	27.1	General	General	Kept, some language updated
27.2	27.2	Certificate of acceptance	Certificate of acceptance	Kept, some language updated
27.3	27.3	Ordinance or regulations	Ordinance or regulations	Kept, some language updated
27.4	27.4	Administrative organization	Administrative organization	Kept, some language updated
27.5	27.5	Program activities	Program activities	Kept, some language updated
<b>28</b>	<b>22</b>	<b>NAAQS</b>	<b>N/A</b>	<b>Moved rules and combined with Ch. 22.</b> <b>Rescinded Ch. 28. (Reserved)</b>
28.1	22.11	Ambient air quality standards - Statewide standards	Ambient air quality standards	<b>Moved from Ch. 28, minor language updated</b>  Rescinded Ch. 28. (Reserved)
<b>29</b>	<b>(New) 21</b>	<b>Opacity Qualifications</b>	<b>Compliance, Excess Emissions, and Measurement of Emissions</b>	<b>Moved rules and combined with Ch. 21.</b> <b>Rescinded Ch. 29. (Reserved)</b>
29.1	21.13	Methodology and qualified observer	Methodology and qualified observer	Moved from Ch. 29, some language updated

Previous Chapter Number (Prior to 5/15/2024)	Current Chapter Number	Previous Title and Description (Prior to 5/15/2024)	Current Title and Description	Actions Taken
<b>30</b>	<b>30</b>	<b>Fees</b>	<b>Fee</b>	<b>Kept</b>
30.1	30.1	Purpose	Purpose	Kept, language updated
30.2	30.2	Fees associated with new source review applications	Fees associated with new source review applications	Kept, some language updated
30.3	30.3	Fees associated with asbestos demolition or renovation notification	Fees associated with asbestos demolition or renovation notification	Kept, some language updated
30.4	30.4	Fees associated with Title V operating permits	Fees associated with Title V operating permits	Kept, some language updated
30.5	30.5	Fee advisory groups	Fee advisory groups	Kept, language updated
30.6	30.6	Process to establish or adjust fees and notification of fee rates	Process to establish or adjust fees and notification of fee rates	Kept, some language updated
30.7	30.7	Fee revenue	Reserved	Language removed

<b>31</b>	<b>31</b>	<b>Nonattainment Areas</b>	<b>Nonattainment New Source Review</b>	<b>Kept</b>
31.1	31.1	Permit requirements relating to nonattainment areas	Permit requirements relating to nonattainment areas	Kept, some language updated
31.2	31.2	Conformity of general federal actions to the Iowa state implementation plan or federal implementation plan - Rescinded	Reserved	Language removed
31.3	31.3	Nonattainment new source review requirements for areas designated nonattainment on or after May 18, 1998	Nonattainment new source review (NNSR) requirements for areas designated nonattainment	Kept, some language updated
31.4	31.4	Preconstruction review permit program	Preconstruction review permit program	Kept
31.5 - 31.8	31.5 - 31.8	Reserved	Reserved	Kept
31.9	31.9	Actuals PALs	Actuals PALs	Kept, some language updated
31.10	31.10	Validity of rules	Validity of rules	Kept
31.11 - 31.19	N/A	Reserved	N/A	Rescinded and removed
31.20	N/A	Special requirements for nonattainment areas designated before May 18, 1998	N/A	Rescinded and removed

<b>32</b>	<b>N/A</b>	<b>AFO Field Study</b>	<b>N/A</b>	<b>Rescinded Ch. 32. (Reserved)</b>
32.1	N/A	Animal feeding operations field study	N/A	Rescinded, reserved, and language removed
32.2	N/A	Definitions	N/A	Rescinded, reserved, and language removed
32.3	N/A	Exceedance of the health effects value (HEV) for hydrogen sulfide	N/A	Rescinded, reserved, and language removed
32.4	N/A	Exceedance of the health effects standard (HES) for hydrogen sulfide	N/A	Rescinded, reserved, and language removed
32.5	N/A	Iowa Air Sampling Manual	N/A	Rescinded, reserved, and language removed

<b>33</b>	<b>33</b>	<b>Special regulations and construction permit requirements for major stationary sources—Prevention of significant deterioration (PSD) of air quality</b>	<b>Construction permit requirements for major stationary sources—Prevention of significant deterioration (PSD)</b>	<b>Kept</b>
33.1	33.1	Purpose	Purpose	Kept, some language updated
33.2	33.2	Reserved	Reserved	Kept
33.3	33.3	Special construction permit requirements for major stationary sources in areas designated attainment or unclassified (PSD)	PSD construction permit requirements for major stationary sources	Kept, some language updated
33.4 - 33.8	33.4 - 33.8	Reserved	Reserved	Kept
33.9	33.9	Plantwide applicability limitations (PALs)	Plantwide applicability limitations (PALs)	Kept, some language updated
33.10	33.10	Exceptions to adoption by reference	Exceptions to adoption by reference	Kept, some language updated

Previous Chapter Number (Prior to 5/15/2024)	Current Chapter Number	Previous Title and Description (Prior to 5/15/2024)	Current Title and Description	Actions Taken
<b>34</b>	<b>N/A</b>	<b>Emissions Trading-CAIR-CAMR</b>	<b>N/A</b>	<b>Rescinded Ch. 34. (Reserved)</b>
34.1	N/A	Purpose	N/A	Rescinded, reserved, and language removed
34.2 - 34.199	N/A	Reserved	N/A	Rescinded, reserved, and language removed
34.200	N/A	Provisions for air emissions trading and other requirements for the Clean Air Interstate Rule (CAIR) - rescinded	N/A	Rescinded, reserved, and language removed
34.201	N/A	CAIR NOx annual trading program general provisions - rescinded	N/A	Rescinded, reserved, and language removed
34.202	N/A	CAIR designated representative for CAIR NOx sources - rescinded	N/A	Rescinded, reserved, and language removed
34.203	N/A	Permits - rescinded	N/A	Rescinded, reserved, and language removed
34.204	N/A	Reserved	N/A	Rescinded, reserved, and language removed
34.205	N/A	CAIR NOx allowance allocations - rescinded	N/A	Rescinded, reserved, and language removed
34.206	N/A	CAIR NOx allowance tracking system - rescinded	N/A	Rescinded, reserved, and language removed
34.207	N/A	CAIR NOx allowance transfers - rescinded	N/A	Rescinded, reserved, and language removed
34.208	N/A	Monitoring and reporting - rescinded	N/A	Rescinded, reserved, and language removed
34.209	N/A	CAIR NOx opt-in units - rescinded	N/A	Rescinded, reserved, and language removed
34.210	N/A	CAIR SO2 trading program - rescinded	N/A	Rescinded, reserved, and language removed
34.211 - 34.219	N/A	Reserved	N/A	Rescinded, reserved, and language removed
34.220	N/A	CAIR NOx ozone season trading program - rescinded	N/A	Rescinded, reserved, and language removed
34.221	N/A	CAIR NOx ozone season trading program general provisions - rescinded	N/A	Rescinded, reserved, and language removed
34.222	N/A	CAIR designated representative for CAIR NOx ozone season sources - rescinded	N/A	Rescinded, reserved, and language removed
34.223	N/A	CAIR NOx ozone season permits - rescinded	N/A	Rescinded, reserved, and language removed
34.224	N/A	Reserved	N/A	Rescinded, reserved, and language removed
34.225	N/A	CAIR NOx ozone season allowance allocations - rescinded	N/A	Rescinded, reserved, and language removed
34.226	N/A	CAIR NOx ozone season allowance tracking system - rescinded	N/A	Rescinded, reserved, and language removed
34.227	N/A	CAIR NOx ozone season allowance transfers - rescinded	N/A	Rescinded, reserved, and language removed
34.228	N/A	CAIR NOx ozone season monitoring and reporting - rescinded	N/A	Rescinded, reserved, and language removed
34.229	N/A	CAIR NOx ozone season opt-in units - rescinded	N/A	Rescinded, reserved, and language removed
34.230 - 34.299	N/A	Reserved	N/A	Rescinded, reserved, and language removed
34.300	N/A	Provisions for air emissions trading and other requirements for the Clean Air Mercury Rule (CAMR) - rescinded	N/A	Rescinded, reserved, and language removed
34.301	N/A	Mercury (Hg) budget trading program general provisions - rescinded	N/A	Rescinded, reserved, and language removed
34.302	N/A	Hg designated representative for Hg budget sources - rescinded	N/A	Rescinded, reserved, and language removed
34.303	N/A	General Hg budget trading program permit requirements - rescinded	N/A	Rescinded, reserved, and language removed
34.304	N/A	Hg allowance allocations - rescinded	N/A	Rescinded, reserved, and language removed
34.305	N/A	Hg allowance tracking system - rescinded	N/A	Rescinded, reserved, and language removed

AQB Rule Tracking Crosswalk

34.306	N/A	Hg allowance transfers - rescinded	N/A	Rescinded, reserved, and language removed
<b>Previous Chapter Number (Prior to 5/15/2024)</b>	<b>Current Chapter Number</b>	<b>Previous Title and Description (Prior to 5/15/2024)</b>	<b>Current Title and Description</b>	<b>Actions Taken</b>
34.307	N/A	Monitoring and reporting - rescinded	N/A	Rescinded, reserved, and language removed
34.308	N/A	Performance specifications - rescinded	N/A	Rescinded, reserved, and language removed

<b>35</b>	<b>N/A</b>	<b>Grant Assistance Programs</b>	<b>N/A</b>	<b>Rescinded Ch. 35. (Reserved)</b>
35.1	N/A	Purpose	N/A	Rescinded, reserved, and language removed
35.2	N/A	Definitions	N/A	Rescinded, reserved, and language removed
35.3	N/A	Role of the department of natural resources	N/A	Rescinded, reserved, and language removed
35.4	N/A	Eligible projects	N/A	Rescinded, reserved, and language removed
35.5	N/A	Forms	N/A	Rescinded, reserved, and language removed
35.6	N/A	Project selection	N/A	Rescinded, reserved, and language removed
35.7	N/A	Funding sources	N/A	Rescinded, reserved, and language removed
35.8	N/A	Type of financial assistance	N/A	Rescinded, reserved, and language removed
35.9	N/A	Term of loans	N/A	Rescinded, reserved, and language removed
35.10	N/A	Reduced award	N/A	Rescinded, reserved, and language removed
35.11	N/A	Fund disbursement limitations	N/A	Rescinded, reserved, and language removed
35.12	N/A	Applicant cost share	N/A	Rescinded, reserved, and language removed
35.13	N/A	Eligible costs	N/A	Rescinded, reserved, and language removed
35.14	N/A	Ineligible costs	N/A	Rescinded, reserved, and language removed
35.15	N/A	Written agreement	N/A	Rescinded, reserved, and language removed
35.16	N/A	Financial assistance denial	N/A	Rescinded, reserved, and language removed